

CEE High-Performance T8 Specification

For Terms and Usage, see next page

Equipment	Specification			
High Performance T8 Lighting Systems	Energy-efficiency specifications based on performance characteristics relating to 4' T8 lamp with a not-to-exceed nominal wattage of 32W. The lamps and ballast must be tested in accordance with the appropriate IESNA and ANSI reference standards, and must meet OSHA/NRTL and UL safety guidelines. These lamps should be applied in accordance with national best practices in lighting design such as (1) IESNA Recommended Practices and (2) Lighting power densities prescribed by local and state building codes.			
Performance Characteristics for Systems				
Mean System Efficacy	≥ 90 MLPW for Instant Start Ballasts ≥ 88 MLPW for Programmed Rapid Start Ballasts			
Performance Characteristics for Lamps				
Color Rendering Index (CRI)	≥ 80			
Minimum Initial Lamp Lumens	≥ 3100 Lumens ¹			
Lamp Life ²	≥ 24,000 hrs at three hours per start.			
Lumen Maintenance -or- Minimum Mean Lumens	≥ 94% -or- ≥ 2900 Mean Lumens			
Performance Characteristics for Ballasts³				
Ballast Efficacy Factor (BEF) BEF = [BF x 100] / Ballast Input Watts Based on: (1) Type of ballast (2) No. of lamps driven by ballast (3) Ballast Factor	Instant-Start Ballast (BEF)			
	Lamps	Low BF ≤ 0.85	Norm 0.85 < BF ≤ 1.0	High BF ≥ 1.01
	1	≥ 3.08	≥ 3.11	≥ 3.03
	2	≥ 1.60	≥ 1.58	≥ 1.55
	3	≥ 1.04	≥ 1.05	≥ 1.04
	4	≥ 0.79	≥ 0.80	≥ 0.77
	6	N/A	N/A	≥ 0.52
	Programmed Rapid-Start Ballast (BEF)			
	1	≥ 2.84	≥ 2.84	≥ 2.95
	2	≥ 1.48	≥ 1.47	≥ 1.51
	3	≥ 0.97	≥ 1.00	≥ 1.00
	4	≥ 0.76	≥ 0.75	≥ 0.75
	6	N/A	N/A	≥ 0.50
	Ballast Frequency	20 to 33 kHz or ≥ 40 kHz		
Power Factor	≥ 0.90			
Total Harmonic Distortion	≤ 20%			

¹ For lamps with color temperatures ≥4500 K, 2950 minimum initial lamp lumens are specified pending further consideration by CEE.

² Life rating is based on a Rapid Start or Programmed-Rapid Start Ballast tested in accordance to ANSI C82.11. When used on an Instant Start Ballast, life may be slightly reduced depending upon the operating hours per start.

³ Multi-Voltage Ballasts must meet or exceed the listed Ballast Efficiency Factor when operated on at least one of the intended operating voltages.

DEFINITIONS

Color Rendering: The effect that the spectral characteristic of the light emitted by the lamp has on the color appearance of the objects illuminated by the lamp.

Initial Lumens: Amount of luminous flux emitted by a lamp after 100 hours of operation at 25°C.

Lamp Life: Number of operating hours that a lamp lasts (based upon the lamp-ballast combination) at 3 hours duty cycle.

Lumen Maintenance: Ratio of mean lumens to initial lumens.

Mean Lumens: Amount of luminous flux emitted by a lamp at 40% of the rated lamp life.

Ballast Efficacy Factor (BEF): Measurement used to compare the efficiency of differing lighting systems. Ratio of ballast factor to the ballast supply power times 100.

Ballast Factor (BF): Measurement of the ability to produce light (lumens) from fluorescent lamps. Ratio of lamp lumens produced when the lamp or lamps are operated by a given ballast to the lamp lumens produced when the lamp or lamps are operated on a reference ballast.

Ballast Frequency: The frequency at which the ballast operates the lamp, measured in Hertz (Hz) or kilohertz (kHz).

Mean System Efficacy: Measure of "efficiency" of a lamp in terms of the ratio between mean visible output (mean lumen) to lamp/ballast electric power input (Watts), measured in Mean Lumens per Watt (MLPW).

Power Factor: The ballast Power Factor is the measurement of how effectively it converts the voltage and current supplied by the power source into watts of usable power delivered to the ballast.

Total Harmonic Distortion: Total harmonic distortion (THD) measures the degree to which the current wave shape is distorted from a sinusoidal wave, expressed as a percentage. Detrimental harmonic components may interfere with electronic equipment.

© 2005 Consortium for Energy Efficiency, Inc.

Terms of Usage

The above specifications may not be reproduced, disseminated, published or transferred in any form or by any means, except with the prior written permission of CEE or as specifically provided below.

CEE grants its Members and Participants permission to use the material for their own use in implementing or administering the specific CEE Initiative to which the material relates on the understanding that: (a) CEE's copyright notice will appear on all copies; (b) no modifications to the material will be made; (c) you will not claim ownership or rights in the material; (d) the material will not be published, reproduced, transmitted, stored, sold, or distributed for profit, including in any advertisement or commercial publication; (e) the materials will not be copied or posted on any Internet site, server or computer network without CEE's express consent; and (f) the foregoing limitations have been communicated to all persons who obtain access to or use of the materials as the result of your access and use thereof.

CEE does not make, sell or distribute any products or services, other than CEE membership services, and CEE does not play any implementation role in the programs offered and operated by or on behalf of its members. The accuracy of member program information and of manufacturer product information discussed or compiled in this site is the sole responsibility of the organization furnishing such information to CEE, and CEE is not responsible for any inaccuracies or misrepresentations which may appear therein.

CEE does not itself test or cause to be tested any equipment or technology for merchantability, fitness for purpose, product safety, or energy efficiency and makes no claim with respect thereto. The references and descriptions of products or services within the site are provided "As Is" without any warranty of any kind, express or implied. CEE is not liable for any damages, including consequential damages, of any kind which may result to the user from the use of the site, or any of the product or services described therein.