

ENVELOPE – DAYLIT ZONE WORKSHEET

CEC-NRCC-ENV-04-E (Revised 08/15)

CALIFORNIA ENERGY COMMISSION



CERTIFICATE OF COMPLIANCE		NRCC-ENV-04-E
Envelope - Daylit Zone Worksheet		(Page 1 of 2)
Project Name:	Date Prepared:	

*NOTE: This worksheet applies only to buildings with three or fewer stories, climate zones 2 through 15, having an enclosed conditioned or unconditioned space > 5,000 ft² that is directly under a roof with a ceiling height > 15 ft and ≥ 0.5 watts per square foot, unless exempted by the **EXCEPTIONS** in §140.3(c).*

A. MINIMUM SKYLIGHT AREA FOR LARGE ENCLOSED SPACES (definitions in §130.1(d), requirements in §140.3(c))

- | | |
|----|---|
| 1. | Enter building plan reference page(s) for large enclosed space _____; and |
| 2. | Enter building plan reference page(s) for daylit zone plans for enclosed space _____ or attach a separate daylit zone design plan with this form; then Go to Step 1 below. |

B. CALCULATE DAYLIT AREA

The minimum Skylit Zone requirements can be met by using either Skylit Daylit Zones or Primary Sidelit Daylit Zones or Combinations.

Step 1 Calculate the minimum prescriptively required total Daylit Zone Area, per §140.3(c)1

1.	Floor area of enclosed space	A	ft ²	Floor area
2.	Minimum prescriptively required total daylit area is (0.75 x floor area (A) – the area of any permanent obstructions), see §140.3(c)1 & §130.1(d)1A for additional details.	B	ft ²	Minimum prescriptively required Total Daylit Zone Area

Step 2 Calculate Total Daylit Zone Area

3.	Skylit Daylit Zone Area, determined in accordance with §130.1(d)1A and as shown on the building plans.	C	ft ²	Skylit Daylit Zone Area
4.	Primary Sidelit Daylit Zone Area determined in accordance with §130.1(d)1B and as shown on the building plans.	D	ft ²	Primary Sidelit Daylit Zone Area
5.	Areas of Primary Sidelit Daylit Zone Area that overlap with the Skylit Daylit Zone Area	E	ft ²	Overlap Zone Area
6.	Total daylit Zone Area F = C+D-E	F	ft ²	Total Daylit Zone Area

C. COMPARE DAYLIT ZONE AREA

Step 1 Compare

- | | |
|----|---|
| 1. | Check if Total Daylit Zone Area (F) is equal to or greater than Minimum Prescriptively Required Daylit Zone Area (B). Space PASSES if F ≥ B. |
|----|---|



CERTIFICATE OF COMPLIANCE		NRCC-ENV-04-E
Envelope - Daylit Zone Worksheet		(Page 2 of 2)
Project Name:	Date Prepared:	

DOCUMENTATION AUTHOR'S DECLARATION STATEMENT	
1. I certify that this Certificate of Compliance documentation is accurate and complete.	
Documentation Author Name:	Documentation Author Signature:
Company:	Signature Date:
Address:	CEA/ HERS Certification Identification (if applicable):
City/State/Zip:	Phone:
RESPONSIBLE PERSON'S DECLARATION STATEMENT	
I certify the following under penalty of perjury, under the laws of the State of California:	
<ol style="list-style-type: none"> The information provided on this Certificate of Compliance is true and correct. I am eligible under Division 3 of the Business and Professions Code to accept responsibility for the building design or system design identified on this Certificate of Compliance (responsible designer). The energy features and performance specifications, materials, components, and manufactured devices for the building design or system design identified on this Certificate of Compliance conform to the requirements of Title 24, Part 1 and Part 6 of the California Code of Regulations. The building design features or system design features identified on this Certificate of Compliance are consistent with the information provided on other applicable compliance documents, worksheets, calculations, plans and specifications submitted to the enforcement agency for approval with this building permit application. I will ensure that a completed signed copy of this Certificate of Compliance shall be made available with the building permit(s) issued for the building, and made available to the enforcement agency for all applicable inspections. I understand that a completed signed copy of this Certificate of Compliance is required to be included with the documentation the builder provides to the building owner at occupancy. 	
Responsible Designer Name:	Responsible Designer Signature:
Company :	Date Signed:
Address:	License:
City/State/Zip:	Phone:

Minimum Skylight Area for Large Enclosed Spaces Worksheets

*This worksheet applies only to buildings with three or fewer stories, in climate zones 2 through 15, having an enclosed conditioned or unconditioned space > 5,000 ft² that is directly under a roof with a ceiling height > 15 ft and ≥ 0.5 watts per square foot, unless exempted by the **EXCEPTIONS** in §140.3(c).*

A. Minimum Skylight Area for Large Enclosed Spaces

1. Enter the reference page number from the building plans which reference the information for large enclosed spaces.
2. Enter the reference page number from the building plans which references the daylit zone designs on the plans attach a separate daylit zone design plan with this form, NRCC-ENV-04-E.

B. Calculating Daylit Zone

The minimum Skylit Zone requirements can be met by using either Skylit Daylit Zones or Primary Sidelit Daylit Zones or Combinations.

Step 1

1. Enter the floor area of the conditioned or unconditioned enclosed space next to A.
2. First calculate the minimum prescriptively required total daylit area. Additional information can be found on the Nonresidential Compliance Manual examples or see §140.3(c)1 & §130.1(d)1A. Use Equation $0.75 \times \text{Floor Area (A1.)} - \text{area of any permanent obstructions}$. Enter value in B2.

Step 2

3. Calculate the Skylit Daylit Zone Area (C3.) in accordance with §130.1(d)1A and shown on the building plans. Enter the Skylit Daylit Zone Area value in (C3.).
 - **SKYLIT DAYLIT ZONE area** is the rough area in plan view under each skylight, plus 0.7 times the average ceiling height in each direction from the edge of the rough opening of the skylight, minus any area on a plan beyond a permanent obstruction that is taller than the following: A permanent obstruction that is taller than one-half the distance from the floor to the bottom of the skylight. The bottom of the skylight is measured from the bottom of the skylight well for skylights having wells, or the bottom of the skylight if no skylight well exists. For the purpose of determining the skylit daylit zone, the geometric shape of the skylit daylit zone shall be identical to the plan view geometric shape of the rough opening of the skylight; for example, for a rectangular skylight the skylit daylit zone plan area shall be rectangular, and for a circular skylight the skylit daylit zone plan area shall be circular.
4. Calculate the Primary Sidelit Daylit Zone area (D4.) in accordance with §130.1(d)1B. Enter the Skylit Daylit Zone Area value in (C4.).
 - **PRIMARY SIDELIT DAYLIT ZONE** is the area on a plan directly adjacent to each vertical glazing, one window head height deep into the area, and window width plus 0.5 times window head height wide on each side of the rough opening of the window, minus any area on a plan beyond a permanent obstruction that is 6 feet or taller as measured from the floor.
5. Calculate or measure the overlap area of the Primary Sidelit Daylit Zone Area with the Skylit Daylit Zone Area and enter the Overlap Zone Area in (B5.)
6. Calculate the Daylit Zone Area by using equation $F = C + D - E$ and enter the Total Daylit Zone Area.

C. Compare Daylit Area Zone

Step 1

1. Here we compare if the Total Daylit Zone Area (F) is ≥ than Minimum Prescriptively Required Daylit Zone Area (B). If $F \geq B$ then compliance is met with the Total Daylit Zone Area.