#### STATE OF CALIFORNIA **ROOFING-VENTILATION-RADIANT BARRIER** CEC-CF2R-ENV-04-E (Revised 01/20)

CALIFORNIA ENERGY COMMISSION

		_	
	9	(er s	2
E		-	
er.	2		a
		10	
140		-	1

CERTIFICATE OF INSTALLATION		CF2R-ENV-04-E		
Roofing-Ventilation-Radiant Barrier - For Non-HERS Registe	ered Projects	(Page 1 of 3)		
Project Name:	Enforcement Agency:	Permit Number:		
Dwelling Address:	City:	Zip Code:		

A. General Information					
01	1 Construction Type				
02	2 Total Attic Area (ft <sup>2</sup> )				
03	3 Radiant Barrier Installed?				
04	4 Attic Space Ventilated or Unventilated?				
05	5 Minimum Ventilation Method of Compliance				
Note: In order to comply with the 1/300 exception, a Class I or II vapor retarder is required to be installed in climate zones 14 and 16.					

# B. Radiant Barrier 01 Brand Name and Product Number 02 Installation Type

# C. Schedule of Lower Vents

The Net Free Area (NFA) of a manufactured product is stated on the packaging or on the manufacturer's specification data sheet. For nonmanufactured products, assume that the net free area is one third of the total aperture area.

02	00	
02	03	04
NFA Per Vent (in <sup>2</sup> )		
(Manufacturer's	Number of Vents	Total NFA Per Vent Type
Specification Sheet)	Installed	(in²)
-	(Manufacturer's	NFA Per Vent (in²) (Manufacturer's Number of Vents

# **D. Schedule of Upper Vents**

The Net Free Area of a manufactured product is stated on the packaging or on the manufacturer's specification data sheet. For nonmanufactured products, assume that the net free area is one third of the total aperture area.

01	02	03	04			
	NFA Per Vent (in <sup>2</sup> )/Per					
Type of Vent	Liner Foot (ft)					
(For instance, eyebrow vent, eave vent, round vent,	(Manufacturer's	Number of Vents/Linear	Total NFA Per Vent Type			
ridge vent)	Specification Sheet)	Feet Installed	(in <sup>2</sup> )			

E. Required Vent Area			
01	Combined NFA of Installed Upper and Lower Vents (in <sup>2</sup> )		
02	Minimum Required Combined NFA of Upper and Lower Vents (in <sup>2</sup> )		
03	NFA of Installed Upper Vents (in <sup>2</sup> )		
04	Minimum Required NFA of Upper Vents (in <sup>2</sup> )		
05	Compliance Statement:		

F. Ra	F. Radiant Barrier – Additional Requirements					
Radi	Radiant Barrier					
01	Radiant barrier must be installed on all vertical surfaces in the attic including gable ends.					
02	The emittance of the radiant barrier shall be less than or equal to 0.05 as tested with ASTM C1371, or E408.					
03	The product shall meet all requirements for California certified insulation materials [radiant barriers] of the Department of Consumer Affairs, Bureau of Home Furnishings and Thermal Insulation, as specified by CCR, Title 24, Part 12, Chapter 12-13, Standards for Insulating Material					
04	When determining the Total Attic Area, the area over unconditioned spaces such as the garage is included when the attic spaces are connected.					

#### STATE OF CALIFORNIA **ROOFING-VENTILATION-RADIANT BARRIER** CEC-CF2R-ENV-04-E (Revised 01/20)

CERTIFICATE OF INSTALLATION		CF2R-ENV-04-E	
Roofing-Ventilation-Radiant Barrier - For Non-HERS Register	ed Projects	(Page 2 of 3)	
Project Name:	Enforcement Agency:	Permit Number:	
Dwelling Address:	City:	Zip Code:	

G. A	G. Attic Ventilation – Additional Requirements					
Lowe	Lower Vents					
01	Lower vents are within one foot of the eave.					
Uppe	er Vents					
02	Upper vents are within three feet of the ridge.					
Vent	Area					
03	The NFA of upper vents must be within required NFA range of upper vents Note: per Exception to R806.2 of the CBC Title 24, Part2, Vol.2.5, if the net free ventilating area is less than 1:150, then the upper ventilation must be at least 40% and no more than 50%. Part 2 contains additional requirements that must be met if the area is less than 1:150.					
The responsible person's signature on this compliance document affirms that all applicable requirements in this table have been met.						

H. Ro	H. Roofing Products (Cool Roof) Installation Information										
01	02	03	04	05	06	07	08	09	10	11	12
						Installe	d		F	Required	
		CRRC		CRRC Listed	Initial Solar	Aged Solar			Aged Solar		
Tag/	Roof	Product ID	Product	Aged Solar	Reflectanc	Reflectanc	Thermal		Reflectanc	Thermal	
ID	Pitch	Number	Туре	Reflectance	e	е	Emittance	SRI	е	Emittance	SRI

I. Roofing Products (Cool Roof) – Additional Requirements					
01	Any roof area covered by building integrated photovoltaic panels and solar thermal panels are exempt from the above Cool Roof requirements.				
02	Liquid field applied coatings must comply with installation criteria from section 110.8(i)4.				
03	03 Mass roof 25 lb/ft <sup>2</sup> or greater: Mass roofs are not required to have a cool roof even if the climate zone specifies minimum performance requirements.				
The responsible person's signature on this compliance document affirms that all applicable requirements in this table have been met.					

#### STATE OF CALIFORNIA **ROOFING-VENTILATION-RADIANT BARRIER** CEC-CF2R-ENV-04-E (Revised 01/20)

CALIFORNIA ENERGY COMMISSION

		100	
4			4
7	23	2	1
1			Ζ.

CERTIFICATE OF INSTALLATION		CF2R-ENV-04-E		
Roofing-Ventilation-Radiant Barrier - For Non-HERS Registe	(Page 3 of 3)			
Project Name:	Enforcement Agency:	Permit Number:		
Dwelling Address:	City:	Zip Code:		
DOCUMENTATION AUTHOR'S DECLARATION STATEMENT				
1. I certify that this Certificate of Installation documentation is accurate and complete.				
Documentation Author Name:	Documentation Author Signature:	Documentation Author Signature:		
Documentation Author Company Name:	Date Signed:	Date Signed:		
Address:	CEA/HERS Certification Identification (if applicable):			
City/State/Zip:	Phone:			
RESPONSIBLE PERSON'S DECLARATION STATEMENT				
I certify the following under penalty of perjury, under the laws of the State of California:				
1. The information provided on this Certificate of Installation is true and correct.				
2. I am either: a) a responsible person eligible under Division 3 of the Business and Professions Code in the applicable classification to accept				
responsibility for the system design, construction, or installation of features, materials, components, or manufactured devices for the				
scope of work identified on this Certificate of Installation, and attest to the declarations in this statement, or b) I am an authorized				

representative of the responsible person and attest to the declarations in this statement on the responsible person's behalf.
The constructed or installed features, materials, components or manufactured devices (the installation) identified on this Certificate of Installation conforms to all applicable codes and regulations and the installation conforms to the requirements given on the Certificate of Compliance, plans, and specifications approved by the enforcement agency.

4.	I will ensure that a registered copy of this Certificate of Installation shall be posted or made available with the building permit(s) issued for	
	the building, and made available to the enforcement agency for all applicable inspections. I understand that a registered copy of this	
	Certificate of Installation is required to be included with the documentation the builder provides to the building owner at occupancy.	

Responsible Builder/Installer Name:	Responsible Builder/Installer Signature:	
Company Name: (Installing Subcontractor or General Contractor or Builder/Owner)	Position With Company (Title):	
Address:	CSLB License:	
City/State/Zip:	Phone:	Date Signed:

# CF2R-ENV-04-E User Instructions

### A. General Information

- 1. Construction Type: Using the drop down menu, select the roofing construction type (e.g., cathedral ceiling or attic).
- 2. Total Attic Area (ft<sup>2</sup>): Enter the total attic area over conditioned space in square feet (ft<sup>2</sup>). Include areas over unconditioned space when the attic spaces are not separated by a continuous air barrier.
- 3. Radiant Barrier Installed?: Using the drop down menu, select "Yes" if a radiant barrier is being installed.
- 4. Attic Space Ventilated or Unventilated?: Using the drop down menu, indicate whether the attic space is ventilated or unventilated.
- 5. Minimum Ventilation Method of Compliance: Using the drop down menu, indicate the method of compliance used to meet the minimum ventilation requirements (e.g., 1/150 or 1/300). Note: In order to comply with the 1/300 exception, a Class I or II vapor retarder is required to be installed in climate zones 14 and 16.

# **B. Radiant Barrier**

- 1. Brand Name and Product Number: Enter the brand name and product number of the product used.
- 2. Installation Type: Using the drop down menu, indicate the installation type from the following list:
  - i. Attached to underside of roof deck;
  - ii. Attached to bottom of truss/rafters;
  - iii. Attached between truss/rafters;
  - iv. Draped over top of truss/rafters;
  - v. Attached to underside of roof deck with air space; or
  - vi. Attached to underside of roof deck with baffle.

One of these six installation methods must be used; no other methods are allowed.

# **C. Schedule of Lower Vents**

In Table C, list all the lower vents that are installed in the attic(s). Lower vents are within one foot of the eave. For each type of vent, indicate:

- 1. Type of Vent: For example, eyebrow vent, eave vent, or round vent.
- 2. NFA per Vent/per Linear Foot: Net free area (NFA) of each individual vent (in<sup>2</sup>) or net free area (NFA) per linear foot. The net free area (NFA) of a manufactured product is stated on the packaging or on the manufacturer's specification data sheet. For non-manufactured products, assume that the net free area is one third of the total aperture area.
- 3. Number of Vents/Linear Feet Installed: Indicate how many vents, or how many linear feet of this type are installed in the attic(s).
- 4. Total NFA Per Vent Type: Calculated value; not a user input.

#### **D. Schedule of Upper Vents**

In table D., list all the installed upper vents in the same way as was done for lower vents (see Section C. above). Upper vents are within three feet of the ridge.

#### E. Required Vent Area

Table E. sets out the minimum required net free area (NFA) of total vents (upper plus lower), and the required NFA of upper vents. All values are calculated based on the inputs in Tables B, C, and D.

A minimum ratio between upper vents and lower vents must be achieved—the exception to R806.2 of the CBC Title 24, Part2, Vol.2.5, states if the net free ventilating area is less than 1:150, then the upper ventilation must be at least 40% and no more than 50%. Part 2 contains additional requirements that must be met if the area is less than 1:150.

#### F. Radiant Barrier – Additional Requirements

Table F. lists additional requirements for Radiant Barriers.

#### **G.** Attic Ventilation – Additional Requirements

Table G. lists additional requirements for Lower Vents, Upper Vents, and Vent Area.

# H. Roofing Products (Cool Roof) Installation Information

- 1. Tag/ID: A label (if any) from the plans, such as R1.
- 2. Roof Pitch: Indicate whether the roof pitch is  $\leq 2:12$  or >2:12
- 3. CRRC Product ID Number: If a cool roof is installed, obtain the Product ID Number from the Cool Roof Rating Council's (CRRC) product packaging label or rated products directory (<u>http://coolroofs.org/products/results</u>).
- 4. Product Type: Using the drop down menu, indicate the product type being used (e.g., asphalt shingles, clay tiles, etc.).
- 5. CRRC Listed Aged Solar Reflectance: State whether the 3-year Aged Solar Reflectance value of the product used is listed on the CRRC product packaging label or rated products directory—Yes or No.
- 6. Installed Initial Solar Reflectance: Enter the Initial Solar Reflectance value of the product used; obtained from the CRRC product packaging label or rated products directory.
- 7. Installed Aged Solar Reflectance: Enter the Aged Solar Reflectance value of the product used; obtained from the CRRC product packaging label or label or rated product directory.
  - NOTE: If the 3-year aged value is not available then use the equation in Section 110.8(i)2 of the Energy Standards to calculate the 3-year Aged Solar Reflectance. One can also use the "Calculated Aged Solar Reflectance" from the Solar Reflectance Index (SRI) Calculation Worksheet" available on the California Energy Commission's website.
- 8. Installed Thermal Emittance: Enter the Thermal Emittance value of the product used; obtained from the CRRC product packaging label or rated products directory. This can be either the initial or aged value.
- 9. Installed SRI: If applicable, obtain the value of the product used from the CRRC rated products directory, or the "Solar Reflectance Index (SRI) Calculation Worksheet" available at the California Energy Commission's website.
- 10. Proposed Aged Solar Reflectance: Report the Proposed Aged Solar Reflectance value from the CF1R.
- 11. Proposed Thermal Emittance: Report the Proposed Thermal Emittance value from the CF1R.
- 12. Proposed SRI: Report the Proposed SRI value if applicable, from the CF1R-NCB, -ADD, or -ALT-01.

# I. Roofing Products (Cool Roof) – Additional Requirements

This section contains additional requirements for Roofing Products. Other exceptions apply for additions and/or alterations.