

CEC-CF2R-PLB-02-E

SAMPLE FORM – NOT VALID FOR SUBMISSION TO BUILDING DEPARTMENTS

CERTIFICATE OF INSTALLATION

Note: This table completed by HERS Registry.

Project Name:	Enforcement Agency:
Dwelling Address:	Permit Number:
City and Zip Code:	Permit Application Date:

A. Design Dwelling Unit Water Heating Systems Information (other than HPWH)

This table reports features of the water heating system(s) other than **HPWH** systems specified on the registered CF1R compliance document for this project.

01	02	03	04	05	06	07	08	09	10
	Water			# of Like (or Identical)			-0/1	Dwelling Unit	10.
	Heating	Water		Water		Rated	Rated	DHW System	
Dwelling	System ID	Heating	Water	Heaters in	Fuel	Input	Input	Distribution	Compact
Unit Name	or Name	System Type	Heater Type	System	Type	Type	Value	Type	Distrib.
					10	0	-4		
					40	ja.	-6,		

A2. Design Dwelling Unit HPWH System Information

This table reports the water heating system(s) that were specified on the registered CF1R compliance document for this project.

01	02	03	04	05	06	07	08	09
Dwelling	Water	Modeled	# of Like (or	Tank	Exterior Tank	Dwelling	Compact	Simulated
Unit Name	Heating	Equipment	Identical)	Location	Insulation R-	Unit DHW	Distribution	Equipment
	System ID	Make and	Water	1/10	value	System		Make and
	or Name	Model	Heaters in	110	.0	Distribution		Model
	,	200	System	U	100	Туре		
		100	1.0	~ ~),			
	- 0		111-	5	4			

B. Installed Dwelling Unit Water Heating Systems Information

This table reports features of the water heating system other than **HPWH** systems installed in this project.

01	02	03	04	05	06	07	08	09	10
Dwelling Unit Name	Water Heating System ID or Name	Water Heating System Type	Water Heater Type	# of Like (or Identical) Water Heaters in System	Fuel Type	Rated Input Type	Rated Input Value	Dwelling Unit DHW System Distribution Type	Compact Distrib.
0									

Registration Number: Registration Date/Time: CA Building Energy Efficiency Standards - 2022 Residential Compliance



CEC-CF2R-PLB-02-E

SAMPLE FORM – NOT VALID FOR SUBMISSION TO BUILDING DEPARTMENTS

B2. Installed Dwelling Unit HPWH System Information

This table reports the water heating system(s) installed in this project.

01	02	03	04	05	06	07	08
Dwelling Unit Name	Water Heating System ID or Name	Modeled Equipment Make and Model	# of Like (or Identical) Water Heaters in System	Tank Location	Exterior Tank Insulation R- value	Dwelling Unit DHW System Distribution Type	Compact Distribution
						20	1

C. Design Dwelling Unit Water Heating Efficiency Information

This table reports the water heater(s) efficiency features specified on the registered CF1R compliance document for this project.

	1				100	
01	02	03	04	05	06	07
Water						00,
Heating System ID or Name	Heating Efficiency Type	Heating Efficiency Value	Standby Loss (%)	Exterior Insulation R-Value	Water Heater Storage Volume (gal)	Tank Location
				Α,		
				200	7/7	

D. Installed Dwelling Unit Water Heating Efficiency Information

This table reports the water heater(s) efficiency features installed in this project.

01	02	03	04	05	06	07
Water Heating System ID or Name	Heating Efficiency Type	Heating Efficiency Value	Standby Loss (%)	Exterior Insulation R-Value	Water Heater Storage Volume (gal)	Tank Location
	0.0		Silie	25		

E. Installed Water Heater Manufacturer Information

01	02	03
Water Heating System ID or	90	
Name	Manufacturer	Model Number
401		

Registration Number: Registration Date/Time: CA Building Energy Efficiency Standards - 2022 Residential Compliance



CALIFORNIA ENERGY COMMISSION

CEC-CF2R-PLB-02-E

SAMPLE FORM – NOT VALID FOR SUBMISSION TO BUILDING DEPARTMENTS

F. Mandatory Measures for all Domestic Hot Water Distribution Systems

	Favinment shall meet the applicable requirements of the Appliance Efficiency Degulations (Costion 110.2/b)1)
01	Equipment shall meet the applicable requirements of the Appliance Efficiency Regulations (Section 110.3(b)1).
02	Unfired storage tanks are insulated with an external R-3.5 or combination of R-16 internal and external Insulation. (Section 110.3(c)4).
	 All domestic hot water piping shall be insulated as specified in Section 609.11 of the California Plumbing Code. Insulation buried
	below grade must be installed in a waterproof and non-crushable casing or sleeve.
	• Piping that penetrates framing members shall not be required to have pipe insulation for the distance of the framing penetration.
00	Piping that penetrates metal framing shall use grommets, plugs, wrapping or other insulating material to assure that no contact is
03	made with the metal framing. Insulation shall butt securely against all framing members.
	 Piping installed in interior or exterior walls that is surrounded on all sides by at least 1 inch (2.5 cm) of insulation. Piping installed in crawlspace with a minimum of 1 inches (2.5 cm) of crawlspace insulation above and below.
	 Piping installed in attics with a minimum of 4 inches (10 cm) of attic insulation on top. Pipe insulation shall fit tightly and all elbows and tees shall be fully insulated.
	For Gas or Propane Water Heaters: Ensure either a or bare installed (Section 150.0(n))
	a) A designated space at least 2.5 feet by 2.5 feet and 7 feet tall within 3 feet from the water heater
	 A designated space at reast 2.5 feet by 2.5 feet and 7 feet tall within 3 feet from the water fleater A dedicated 125V, 20A electrical receptacle connected to the electric panel with a 120/240V 3 conductor, 10 AWG copper
	branch circuit, within 3 feet from the water heater and is accessible with no obstructions.
	The conductor shall be labeled with the word "Spare" on both ends; and
	 A reserved single pole circuit breaker space next to the circuit breaker next to the branch circuit labeled "Future" 240V shall
	be provided.
	 A condensate drain no more than 2 inches higher than the base on water heater for natural draining.
	1300
	b) A designated space at least 2.5 feet by 2.5 feet and 7 feet tall more than 3 feet from the water heater
	 A dedicated 240 volt branch circuit shall be installed within 3 feet from the designated space. The
	 branch circuit shall be rated at 30 amps minimum. The blank cover shall be identified as "240V ready";
	<u>and</u>
0.4	 The main electrical service panel shall have a reserved space to allow for the installation of a double
04	pole circuit breaker for a future HPWH installation. The reserved space shall be permanently
	marked as "For Future 240V use"; and
	marked as Torrutare 2400 use, and
	 Either a dedicated cold water supply, or the cold water supply shall pass through the designated HPWH
	location just before reaching the gas or propane water heater; and
	 The hot water supply pipe coming out of the gas or propane water heater shall be routed first
	through the designated HPWH location before serving any fixtures; and
	The hot and cold water piping at the designated HPWH location shall be exposed and readily
	accessible for future installation of a HPWH; and
	 A condensate drain no more than 2 inches higher than the base of the installed water heater, and allows
10	natural draining without pump assistance.
1	
The re	snonsible person's signature on this compliance document affirms that all applicable requirements in

The responsible person's signature on this compliance document affirms that all applicable requirements in this table have been met.

Registration Number: Registration Date/Time: CA Building Energy Efficiency Standards - 2022 Residential Compliance



CEC-CF2R-PLB-02-E

SAMPLE FORM – NOT VALID FOR SUBMISSION TO BUILDING DEPARTMENTS

G. Compact Hot Water Distribution (CHWDS) (RA4.4.6)

For dwelling units with multiple systems, enter the master bath distance and kitchen distance to the closest water heater, and enter the average of the furthest fixture to each water heater

01	02	03	04	05	06	07
Dwelling Name	Number of Stories	Master Bath distance of furthest fixture to Water Heater in feet	Kitchen distance from furthest fixture to Water Heater in feet	Furthest Third furthest fixture to Water Heater in feet (Avg for multiple water heaters)	Weighted Distance	Qualification Distance
					Chic	. 0

The responsible person's signature on this compliance document affirms that all applicable requirements in this table have been met.

H. Parallel Piping Requirements (PP) (RA4.4.4)

Systems that utilize this distribution type shall comply with these requirements.

01	Each central manifold has 15 feet or less of pipe between manifold and water heater.
02	For manifolds that include valves, the manifold must be readily accessible in accordance with the plumbing code.
03	Hot water distribution system piping from the manifold to the fixtures and appliances must take the most direct path. For instance, piping from a second story manifold cannot supply the first floor.
04	The hot water distribution piping must be separated by at least 2 inches from any other hot water supply piping, and at least 6 inches from any cold water supply piping. Alternatively, the hot water supply piping must be insulated to the thicknesses shown in TABLE 120.3-A.

The responsible person's signature on this compliance document affirms that all applicable requirements in this table have been met.

I. Point of Use Requirements (POU) (RA4.4.5)

Systems that utilize this distribution type shall comply with these requirements

1	All hot water supply pipe run lengths are equal to or less than the maximum values shown below, based on the pipe diameter. If a combination of piping is used in a single run, then one half the allowed length of each size is the maximum installed length. The maximum allowed length of piping for the longest run terminating in:
01	3/8 inch - For only one pipe size - max length allowed is 15 feet For combination pipe sizes the max allowed length of 3/8-inch piping is 7.5 feet, of 1/2 inch piping is 5 feet, and 3/4 inch piping is 2.5 feet.
(1/2 inch - For only one pipe size – max length allowed is 10 feet For combination pipe sizes the allowed length of 1/2-inch piping is 5 feet, and 3/4 inch piping is 2.5 feet.
	3/4 inch - For only one pipe size = 5 feet

The responsible person's signature on this compliance document affirms that all applicable requirements in this table have been met.

Registration Number: Registration Date/Time: CA Building Energy Efficiency Standards - 2022 Residential Compliance



CALIFORNIA ENERGY COMMISSION

CEC-CF2R-PLB-02-E

SAMPLE FORM – NOT VALID FOR SUBMISSION TO BUILDING DEPARTMENTS

J. Mandatory Requirements for all Recirculation Systems (RA4.4.7)

Systems that utilize a recirculation system shall comply with these requirements.

	, , , , , , , , , , , , , , , , , , , ,
01	A check valve located between the recirculation pump and the water heater to prevent unintentional recirculation.
02	Piping must take the most direct path between water heater and fixtures.
03	Insulation is not required on the cold water line when it is used as the return.
04	If more than one loop is installed, each loop shall have its own pump and controls.

The responsible person's signature on this compliance document affirms that all applicable requirements in this table have been met.

K. Recirculation Non-Demand Controls Requirements (R-ND) (RA4.4.8)

Systems that utilize this distribution type shall comply with these requirements.

The active control shall be either: timer, temperature, or time and temperature. Timers shall be set to less than 24 hours. The temperature sensor shall be connected to the piping and to the controls for the pump.

The responsible person's signature on this compliance document affirms that all applicable requirements in this table have been met.

L. Demand Recirculation Manual Control (R-DRmc) (RA4.4.9)/Sensor Control Requirements (RDRsc) (RA4.4.10)

Systems that utilize either of these distribution types shall comply with these requirements

01	The system operates "on-demand", meaning that the pump begins to operate shortly before or immediately after hot water draw begins, and stops when the return water temperature reaches a certain threshold value. For Demand Recirculation Manual Control, the pump shall be turned on using a manual switch system. For Demand Recirculation Sensor Control, the pump shall be turned on using a sensor system.		
02	The controls shall be located in the kitchen, bathroom, and any hot water fixture location that is at least 20 feet from the water heater.		
03	Manual controls may be active by wired or wireless mechanisms.		
04	Sensor controls may be activated by wired or wireless mechanisms, including buttons, motion sensors, door switches and flow switches. Each control shall have standby power of 1 Watt or less.		
05	 Pump and control placement shall meet one of the following criteria: When a dedicated return line has been installed the pump, controls and thermo-sensor are installed at the end of the supply portion of the recirculation loop; or The pump and controls are installed on the dedicated return line near the water heater and the thermo-sensor is installed in an accessible location as close to the end of the supply portion of the recirculation loop as possible; or When the cold water line is used as the return, the pump, demand controls and thermo-sensor shall be installed in an accessible location at the end of supply portion of the hot water distribution line (typically under a sink). 		
06	After the pump has been activated, the controls shall allow the pump to operate until the water temperature at the thermo-sensor rises to one of the following values: Not more than 10°F (5.6°C) above the initial temperature of the water in the pipe; or Not more than 102°F (38.9°C).		
07	Controls shall limit operation to no more than 5 minutes following activation.		

The responsible person's signature on this compliance document affirms that all applicable requirements in this table have been met.



CALIFORNIA ENERGY COMMISSION

CEC-CF2R-PLB-02-E

SAMPLE FORM – NOT VALID FOR SUBMISSION TO BUILDING DEPARTMENTS

DOCUMENTATION AUTHOR'S DECLARATION STATEMENT

1. I certify that this Certificate of Installation documentation is accurate and complete.

Documentation Author Name:	Documentation Author Signature:
Documentation Author Company Name:	Date Signed:
Address:	CEA/HERS Certification Identification (If applicable):
City/State/Zip:	Phone:

RESPONSIBLE PERSON'S DECLARATION STATEMENT

- 2. I certify the following under penalty of perjury, under the laws of the State of California:
 - 1. The information provided on this Certificate of Installation is true and correct.
 - 2. I am either: a) a responsible person eligible under Division 3 of the Business and Professions Code in the applicable classification to accept responsibility for the system design, construction, or installation of features, materials, components, or manufactured devices for the scope of work identified on this Certificate of Installation, and attest to the declarations in this statement, or b) I am an authorized representative of the responsible person and attest to the declarations in this statement on the responsible person's behalf.
 - 3. The constructed or installed features, materials, components or manufactured devices (the installation) identified on this Certificate of Installation conforms to all applicable codes and regulations and the installation conforms to the requirements given on the Certificate of Compliance, plans, and specifications approved by the enforcement agency.
 - 4. I understand that a registered copy of this Certificate of Installation shall be posted or made available with the building permit(s) issued for the building, and made available to the enforcement agency for all applicable inspections, and I will take the necessary steps to ensure this requirement is accomplished.
 - 5. I understand that a registered copy of this Certificate of Installation is required to be included with the documentation the builder provides to the building owner at occupancy, and I will take the necessary steps to ensure this requirement is accomplished.

Responsible Builder/Installer Name:	Responsible Builder/Installer Signature:	
Company Name: (Installing Subcontractor or General Contractor or Builder/Owner)	Position With Company (Title):	
Address:	CSLB License:	
City/State/Zip:	Phone:	Date Signed:

For assistance or questions regarding the Energy Standards, contact the Energy Hotline at: 1-800-772-3300

Registration Number: Registration Date/Time: CA Building Energy Efficiency Standards - 2022 Residential Compliance

CERTIFICATE OF INSTALLATION – USER INSTRUCTIONS	CF2R-PLB-02-E
Single Dwelling Unit Hot Water System Distribution	(Page 1 of 3)

CF2R-PLB-02-E User Instructions

A. Design Dwelling Unit Water Heating Systems Information

This table reports the water heating system features that were specified on the registered CF1R compliance document for this project. This section is for information/verification purposes only and requires no user input.

A2. Design Dwelling Unit HPWH System Information

This table reports the water heating system features that were specified on the registered CF1R compliance document for this project. This section is for information/verification purposes only and requires no user input.

B. Installed Dwelling Unit Water Heating Systems Information

This table reports the water heating system information that is being installed. Require one line for each installed water heater.

- 1. Dwelling Unit Name Reference information from Table A.
- 2. Water Heating System ID or Name Reference information from Table A.
- 3. Water Heating System Type Reference information from Table A. The different kinds of water heating system type are DHW, or Combined Hydronic.
- 4. Water Heater Type Reference information from Table A. The different kinds of water heaters are Large/Commercial Storage, Small/Consumer Storage, Residential-Duty Commercial Storage, Heat Pump, Boiler, Large/Commercial Instantaneous, Small/Consumer Instantaneous, Residential-Duty Commercial Instantaneous or Indirect.
- 5. # of Like (or Identical) Water Heaters in system Reference information from Table A.
- 6. Fuel Type Reference information from Table A. The different kinds of fuel types are heat pump, electric resistance, natural gas, and propane.
- 7. Rated Input Type Reference information from Table A. For natural gas and propane, the input type is Btu/hr. For heat pump and electric resistance the input type is kW.
- 8. Rated Input Value User input. Numerical value of the rated input. Must be equal to or less than value indicated on the CF1R.
- 9. Dwelling Unit DHW System Distribution Type Reference information from Table A.
- 10. Compact Distribution Reference information from Table A.

B2. Installed Dwelling Unit HPWH System Information

This table reports the water heating system information that is being installed. Require one line for each installed water heater. Not applicable for central systems.

- 1. Dwelling Unit Name Reference information from Table A2.
- 2. Water Heating System ID or Name Reference information from Table A2.
- 3. Modeled Equipment Make and Model User input must be equal to the value indicated on Table A2 as default and allow user to override with an equivalent system based on the simulated equipment in Table A2. A2 as default and allow user to override with an equivalent system based on the simulated

CERTIFICATE OF INSTALLATION – USER INSTRUCTIONS	CF2R-PLB-02-E
Single Dwelling Unit Hot Water System Distribution	(Page 2 of 3)

equipment in Table A2.04 # of Like (or Identical) Water Heaters in System – Reference information from Table A2.

- 4. Tank Location User input. Must be equal to value indicated in Table A2.
- 5. Exterior Tank Insulation R-value User input. Must be equal to or higher than value indicated in Table A2.
- 6. Dwelling Unit DHW System Distribution Type Reference information from Table A2.
- 7. Compact Distribution Reference information from Table A2.

C. Design Dwelling Unit Water Heating Efficiency Information

This table reports the water heating system features that were specified on the registered CF1R compliance document for this project. This section is for information/verification purposes only and requires no user input.

D. Installed Dwelling Unit Water Heating Efficiency Information

This table reports the water heating system efficiency features installed in this project.

- 1. Water Heating System ID or Name Reference information from Table C.
- 2. Heating Efficiency Type Reference information from Table C. Different efficiency types are Energy Factor, AFUE, UEF and Thermal Efficiency.
- 3. Heating Efficiency Value User input must be equal to or higher efficiency than value indicated on Table C.
- 4. Standby Loss User input. Must be equal to or less than value indicated in Table C. Value may be N/A if CF1R value is N/A.
- 5. Exterior Insulation R-Value User input. Must be equal to or higher than value indicated in Table C. Value may be N/A if CF1R value is N/A.
- 6. Water Heater Storage Volume (gal) User input. Must be equal to the value indicated in Table C. Value may be N/A if water heater type is instantaneous with zero storage.
- 7. Tank location User input. Must be equal to value indicated in Table C.

E. Installed Water Heater Manufacturer Information

This table reports the manufacturer information of the installed water heater(s). Require one line for each installed water heater. Not applicable for central systems.

- 1. Water Heating System ID or Name Reference information from Table B or B2.
- 2. Manufacturer User input. Enter the name of the water heater manufacturer.
- 3. Model Number User input. Enter the model number of the water heater.

F. Mandatory Measures for all Domestic Hot Water Distribution Systems

This table lists the requirements for all DHW systems. Installer must ensure all the requirements on this table are met.

G. Compact Hot Water Distribution Basic

If performance compliance is used, this table lists the values used in the performance calculation and require no user input.

If prescriptive compliance is used, fill out this table.

1. Dwelling Name. Reference information from Table A2.

Registration Number: Registration Date/Time: CA Building Energy Efficiency Standards - 2022 Residential Compliance

CERTIFICATE OF INSTALLATION – USER INSTRUCTIONS	CF2R-PLB-02-E
Single Dwelling Unit Hot Water System Distribution	(Page 3 of 3)

- 2. Enter the master bath distance of furthest fixture to water heater in feet. For multiple water heaters, enter the distance to the closest water heater.
- 3. Enter the kitchen distance from furthest fixture to water heater in feet. For multiple water heaters, enter the distance to the closest water heater.
- 4. Enter furthest third fixtures from fixture to water heater in feet. For multiple water heaters, enter the average of the furthest distance of each water heater.
- 5. Weighted Distance Calculated value no user input required.
- 6. Qualification Distance Calculated value no user input required.

H. Parallel Piping Requirements

This table only applies to systems indicated as **Parallel Piping.** In addition to the mandatory requirements in Table J, the installer must ensure the requirements in this table are met.

I. Point of Use Requirements

This table only applies to systems indicated as **Point of Use**. In addition to the mandatory requirements in Table J, the installer must ensure the requirements in this table are met.

J. Mandatory Requirements for all Recirculation System

The requirements of this table apply to all recirculation systems listed below.

K. Recirculation Non-Demand Controls Requirements

This table only applies to systems indicated as **Recirculation Non-demand Controls.** In addition to the mandatory requirements in Table J and M, the installer must ensure the requirements in this table are met.

L. Demand Recirculation Manual Control/Sensor Control Requirements

This table only applies to systems indicated as **Demand Recirculation Manual Control** or **Demand Recirculation Senor Control**. In addition to the mandatory requirements in Table H and K, the installer must ensure the requirements in this table are met.

Documentation Declaration Statements

- 1. The person who prepared the CF2R will sign and complete the fields for their name, company (if applicable), address, phone number, certification information (if applicable), date and signature.
- 2. The person who is assuming responsibility for the project being built to comply with Title 24, Part 6, will complete the fields for their name, company (if applicable), address, phone number, license number (if applicable), date and signature.