



HERS VERIFIED INDIVIDUAL DWELLING UNIT HOT WATER SYSTEM DISTRIBUTION

CALIFORNIA ENERGY COMMISSION

CEC-LMCV-PLB-22-H

SAMPLE FORM – NOT VALID FOR SUBMISSION TO BUILDING DEPARTMENTS

CERTIFICATE OF VERIFICATION

Note: This table completed by HERS Registry.

Project Name:	Enforcement Agency:
Dwelling Address:	Permit Number:
City and Zip Code:	Permit Application Date:

A. Design HERS Verified Dwelling Unit Water Heating Systems Information (other than HPWH)

This table reports features of the water heating system(s) other than HPWH system specified on the registered LMCC compliance document for this project.

01	02	03	04	05	06	07	08	09	10	11	12
Dwelling Unit Name	Water Heating System ID or Name	Water Heating System Type	Water Heater Type	# of Like (or Identical) Water Heaters in System	Fuel Type	Rated Input Type	Rated Input Value	Central DHW System Distribution	Dwelling Unit DHW System Distribution Type	Compact Distrib.	Drain Water Heat Recovery

A2. Design HERS Verified Dwelling Unit HPWH System Information

This table reports the water heating system(s) that were specified on the registered LMCC compliance document for this project.

01	02	03	04	05	06	07	08	09
Dwelling Unit Name	Water Heating System ID or Name	Modeled Equipment Make and Model	# of Like (or Identical) Water Heaters in System	Tank Location	Exterior Tank Insulation R-value	Dwelling Unit DHW System Distribution Type	Compact Distribution	Simulated Equipment Make and Model

B. Installed HERS Verified Dwelling Unit Water Heating Systems Information

This table reports the water heating system features installed in this project.

01	01	02	03	04	05	06	07	08	09	10	11
Dwelling Unit Name	Water Heating System ID or Name	Water Heating System Type	Water Heater Type	# of Like (or Identical) Water Heaters in System	Fuel Type	Rated Input Type	Rated Input Value	Central DHW System Distribution	Dwelling Unit DHW System Distribution Type	Compact Distrib.	Drain Water Heat Recovery

Registration Number:

Registration Date/Time:

HERS Provider:

CA Building Energy Efficiency Standards – 2022 Low-Rise Multifamily Compliance

January 2022



HERS VERIFIED INDIVIDUAL DWELLING UNIT HOT WATER SYSTEM DISTRIBUTION

CALIFORNIA ENERGY COMMISSION

CEC-LMCV-PLB-22-H

SAMPLE FORM – NOT VALID FOR SUBMISSION TO BUILDING DEPARTMENTS

B2. Installed HERS Verified Dwelling Unit HPWH System Information

This table reports the water heating system(s) installed in this project.

01	02	03	04	05	06	07	08
Dwelling Unit Name	Water Heating System ID or Name	Modeled Equipment Make and Model	# of Like (or Identical) Water Heaters in System	Tank Location	Exterior Tank Insulation R-value	Dwelling Unit DHW System Distribution Type	Compact Distribution

C. Design HERS Verified Dwelling Unit Water Heating Efficiency Information

This table reports the water heater(s) efficiency features specified on the registered LMCC compliance document for this project. (Not needed for central systems)

01	02	03	04	05	06	07
Water Heating System ID or Name	Heating Efficiency Type	Heating Efficiency Value	Standby Loss (%)	Exterior Insulation R-Value	Water Heater Storage Volume (gal)	Tank location

D. Installed HERS Verified Dwelling Unit Water Heating Efficiency Information

This table reports the water heater(s) efficiency features installed in this project. (Not needed for central systems)

01	02	03	04	05	06	07
Water Heating System ID or Name	Heating Efficiency Type	Heating Efficiency Value	Standby Loss (%)	Exterior Insulation R-Value	Water Heater Storage Volume (gal)	Tank location
08	Compliance Statement					

E. Installed Water Heater Manufacturer Information

01	02	03
Water Heating System ID or Name	Manufacturer	Model Number



HERS VERIFIED INDIVIDUAL DWELLING UNIT HOT WATER SYSTEM DISTRIBUTION

CALIFORNIA ENERGY COMMISSION

CEC-LMCV-PLB-22-H

SAMPLE FORM – NOT VALID FOR SUBMISSION TO BUILDING DEPARTMENTS

F. Mandatory Measures for all Domestic Hot Water Distribution Systems

01	Equipment shall meet the applicable requirements of the Appliance Efficiency Regulations (Section 110.3(b)1).	
02	Unfired Storage Tanks are insulated with an external R-3.5 or combination of R-16 internal and external Insulation. (Section 110.3(c)4).	
03	<ul style="list-style-type: none"> The following pipes are insulated, to the thicknesses required by Table 120.3A, except for those sections of pipe that are subject to one of the exceptions below: All domestic hot water piping shall be insulated as specified in Section 609.11 of the California Plumbing Code. Insulation buried below grade must be installed in a water proof and non-crushable casing or sleeve. Piping that penetrates framing members shall not be required to have pipe insulation for the distance of the framing penetration. Piping that penetrates metal framing shall use grommets, plugs, wrapping or other insulating material to assure that no contact is made with the metal framing. Insulation shall butt securely against all framing members. Piping installed in interior or exterior walls that is surrounded on all sides by at least 1 inch (2.5 cm) of insulation. Piping installed in crawlspace with a minimum of 1 inches (2.5 cm) of crawlspace insulation above and below. Piping installed in attics with a minimum of 4 inches (10 cm) of attic insulation on top Pipe insulation shall fit tightly and all elbows and tees shall be fully insulated. 	
04	<p>For Gas or Propane Water Heaters: Ensure either a or b are installed (Section 150.0(n))</p> <p>a) A designated space at least 2.5 feet by 2.5 feet and 7 feet tall within 3 feet from the water heater</p> <ul style="list-style-type: none"> A dedicated 125V, 20A electrical receptacle connected to the electric panel with a 120/240V 3 conductor, 10 AWG copper branch circuit, within 3 feet from the water heater and is accessible with no obstructions; <ul style="list-style-type: none"> The conductor shall be labeled with the word "Spare" on both ends; and A reserved single pole circuit breaker space next to the circuit breaker next to the branch circuit labeled "Future" 240V shall be provided. A condensate drain no more than 2 inches higher than the base on water heater for natural draining <p>b) A designated space at least 2.5 feet by 2.5 feet and 7 feet tall more than 3 feet from the water heater</p> <ul style="list-style-type: none"> <u>A dedicated 240 volt branch circuit shall be installed within 3 feet from the designated space. The branch circuit shall be rated at 30 amps minimum. The blank cover shall be identified as "240V ready"; and</u> <u>The main electrical service panel shall have a reserved space to allow for the installation of a double pole circuit breaker for a future HPWH installation. The reserved space shall be permanently marked as "For Future 240V use"; and</u> <u>Either a dedicated cold water supply, or the cold water supply shall pass through the designated HPWH location just before reaching the gas or propane water heater; and</u> <u>The hot water supply pipe coming out of the gas or propane water heater shall be routed first through the designated HPWH location before serving any fixtures; and</u> <u>The hot and cold water piping at the designated HPWH location shall be exposed and readily accessible for future installation of a HPWH; and</u> <u>A condensate drain no more than 2 inches higher than the base of the installed water heater, and allows natural draining without pump assistance.</u> 	
05	Verification Status:	<input type="checkbox"/> <u>Pass</u> - all applicable requirements are met; or <input type="checkbox"/> <u>Fail</u> - one or more applicable requirements are not met. Enter reason for failure in corrections notes field below; or <input type="checkbox"/> <u>All N/A</u> - This entire table is not applicable
06	Correction Notes:	

The responsible person's signature on this compliance document affirms that all applicable requirements in this table have been met unless otherwise noted in the Verification Status and the Correction Notes.



HERS VERIFIED INDIVIDUAL DWELLING UNIT HOT WATER SYSTEM DISTRIBUTION

CALIFORNIA ENERGY COMMISSION

CEC-LMCV-PLB-22-H

SAMPLE FORM – NOT VALID FOR SUBMISSION TO BUILDING DEPARTMENTS

G. HERS-Verified Compact Hot Water Distribution Expanded Credit (CHWDS-H-EX) (RA3.6.5)

For dwelling units with multiple systems, enter the master bath distance and kitchen distance to the closest water heater, and enter the average of the furthest fixture to each water heater.

01	02	03	04	05	06	07	08	09
Dwelling Name	Number of Stories	Master Bath distance of furthest fixture to Water Heater in feet	Kitchen distance from furthest fixture to Water Heater in feet	Furthest Third furthest fixture to Water Heater in feet (Avg for multiple water heaters)	Weighted Distance	Qualification Distance	Design Compactness Factor	Calculated Compactness Factor
10	No hot water piping >1 inch diameter is allowed.							
11	Length of 1 inch diameter piping is limited to 8 feet or less.							
12	Two and three story buildings cannot have hot water distribution piping in the attic, unless the water heater is also located in the attic.							
13	Eligible recirculating systems must be HERS-Verified Demand Recirculation: Manual Control conforming to RA4.4.17.							
14	Verification Status:	<input type="checkbox"/> <u>Pass</u> - all applicable requirements are met; or <input type="checkbox"/> <u>Fail</u> - one or more applicable requirements are not met. Enter reason for failure in corrections notes field below; or <input type="checkbox"/> <u>All N/A</u> - This entire table is not applicable						
15	Correction Notes:							

The responsible person's signature on this compliance document affirms that all applicable requirements in this table have been met unless otherwise noted in the Verification Status and the Correction Notes.

H. Compact Hot Water Distribution (CHWDS) (RA4.4.6)

For dwelling units with multiple systems, enter the master bath distance and kitchen distance to the closest water heater, and enter the average of the furthest fixture to each water heater.

01	02	03	04	05	06	07	08	09
Dwelling Name	Number of Stories	Master Bath distance of furthest fixture to Water Heater in feet	Kitchen distance from furthest fixture to Water Heater in feet	Furthest Third furthest fixture to Water Heater in feet (Avg for multiple water heaters)	Weighted Distance	Qualification Distance	Design Compactness Factor	Calculated Compactness Factor

The responsible person's signature on this compliance document affirms that all applicable requirements in this table have been met.

Registration Number:

Registration Date/Time:

HERS Provider:



HERS VERIFIED INDIVIDUAL DWELLING UNIT HOT WATER SYSTEM DISTRIBUTION

CALIFORNIA ENERGY COMMISSION

CEC-LMCV-PLB-22-H

SAMPLE FORM – NOT VALID FOR SUBMISSION TO BUILDING DEPARTMENTS

I. HERS-Verified Drain Water Heat Recovery System (DWHR-H)

DWHR devices shall comply with these requirements.

Design DWHR System Information						
01	02	03	04			
System ID/Name	Rated Effectiveness	Installation Configuration	Percent of shower served by the DWHR device			
Installed DWHR System Information						
05	06	07	08	09	10	11
System Name/ID	Manufacturer	Model #	Rated effectiveness	Installation Configuration	Percent of shower served by the DWHR device	DWHR System Certified by CEC (Yes/No)
12	For water heating system serving a single dwelling, the DWHR system shall, at the minimum, recover heat from the master bathroom shower and must at least transfer that heat either back to the respective shower(s) or the water heater.					
13	For central water heating system serving multiple dwellings, the DWHR system shall, at the minimum, recover heat from half the showers located above the first floor and must at least transfer that heat either back to all the respective showers or the water heater.					
14	The DWHR unit(s) shall be installed within 1 degrees of the rated slope. Sloped DWHR shall have a minimum lengthwise slope of 1 degree. The lateral level tolerance shall be within plus or minus 1 degree.					
15	Verification Status:		<input type="checkbox"/> <u>Pass</u> - all applicable requirements are met; or <input type="checkbox"/> <u>Fail</u> - one or more applicable requirements are not met. Enter reason for failure in corrections notes field below; or <input type="checkbox"/> <u>All N/A</u> - This entire table is not applicable			
16	Correction Notes:					

The responsible person’s signature on this compliance document affirms that all applicable requirements in this table have been met unless otherwise noted in the Verification Status and the Correction Notes.

J. HERS-Verified Pipe Insulation Credit Requirements (PIC-H) (RA3.6.3)

Systems that utilize this distribution type shall comply with these requirements.

01	HERS rater shall perform a visual inspection that all hot water piping comply with the insulation requirements in 150.0(J).	
02	Verification Status:	<input type="checkbox"/> <u>Pass</u> - all applicable requirements are met; or <input type="checkbox"/> <u>Fail</u> - one or more applicable requirements are not met. Enter reason for failure in corrections notes field below; or <input type="checkbox"/> <u>All N/A</u> - This entire table is not applicable
03	Correction Notes:	

The responsible person’s signature on this compliance document affirms that all applicable requirements in this table have been met unless otherwise noted in the Verification Status and the Correction Notes.

Registration Number:

Registration Date/Time:

HERS Provider:

CA Building Energy Efficiency Standards – 2022 Low-Rise Multifamily Compliance

January 2022



HERS VERIFIED INDIVIDUAL DWELLING UNIT HOT WATER SYSTEM DISTRIBUTION

CALIFORNIA ENERGY COMMISSION

CEC-LMCV-PLB-22-H

SAMPLE FORM – NOT VALID FOR SUBMISSION TO BUILDING DEPARTMENTS

K. HERS-Verified Parallel Piping Requirements (PP-H) (RA3.6.4)

Systems that utilize this distribution type shall comply with these requirements.

01	Each central manifold has 5 feet or less of pipe between manifold and water heater.	
02	For manifolds that include valves, the manifold must be readily accessible in accordance with the plumbing code.	
03	Hot water distribution system piping from the manifold to the fixtures and appliances must take the most direct path. For example, piping from a second story manifold cannot supply the first floor.	
04	The hot water distribution piping must be separated by at least 2 inches from any other hot water supply piping, and at least 6 inches from any cold water supply piping. Alternatively, the hot water supply piping must be insulated to the thicknesses shown in TABLE 120.3-A.	
05	Verification Status:	<input type="checkbox"/> <u>Pass</u> - all applicable requirements are met; or <input type="checkbox"/> <u>Fail</u> - one or more applicable requirements are not met. Enter reason for failure in corrections notes field below; or <input type="checkbox"/> <u>All N/A</u> - This entire table is not applicable
06	Correction Notes:	

The responsible person's signature on this compliance document affirms that all applicable requirements in this table have been met unless otherwise noted in the Verification Status and the Correction Notes.

L. Parallel Piping Requirements (PP) (RA4.4.4)

Systems that utilize this distribution type shall comply with these requirements.

01	Each central manifold has 15 feet or less of pipe between manifold and water heater	
02	For manifolds that include valves, the manifold must be readily accessible in accordance with the plumbing code.	
03	Hot water distribution system piping from the manifold to the fixtures and appliances must take the most direct path. For instance, piping from a second story manifold cannot supply the first floor	
04	The hot water distribution piping must be separated by at least 2 inches from any other hot water supply piping, and at least 6 inches from any cold water supply piping. Alternatively, the hot water supply piping must be insulated to the thicknesses shown in TABLE 120.3-A.	

The responsible person's signature on this compliance document affirms that all applicable requirements in this table have been met.

M. Point of Use Requirements (POU) (RA4.4.5)

Systems that utilize this distribution type shall comply with these requirements.

01	<p>All hot water supply pipe run lengths are equal to or less than the maximum values shown below, based on the pipe diameter. If a combination of piping is used in a single run, then one half the allowed length of each size is the maximum installed length. The maximum allowed length of piping for the longest run terminating in:</p> <p>3/8 inch - For only one pipe size - max length allowed is 15 feet For combination pipe sizes the max allowed length of 3/8-inch piping is 7.5 feet, of 1/2 inch piping is 5 feet, and 3/4 inch piping is 2.5 feet.</p> <p>1/2 inch - For only one pipe size – max length allowed is 10 feet For combination pipe sizes the allowed length of 1/2-inch piping is 5 feet, and 3/4 inch piping is 2.5 feet.</p> <p>3/4 inch - For only one pipe size = 5 feet</p>	
----	--	--

The responsible person's signature on this compliance document affirms that all applicable requirements in this table have been met.

Registration Number:

Registration Date/Time:

HERS Provider:

CA Building Energy Efficiency Standards – 2022 Low-Rise Multifamily Compliance

January 2022



SAMPLE FORM – NOT VALID FOR SUBMISSION TO BUILDING DEPARTMENTS

N. Mandatory Requirements for all Recirculation Systems (RA4.4.7)

Systems that utilize this distribution type shall comply with these requirements.

Table with 2 columns: ID (01-04) and Requirement description.

The responsible person’s signature on this compliance document affirms that all applicable requirements in this table have been met.

O. Recirculation Non-Demand Controls Requirements (R-ND) (RA4.4.8)

Systems that utilize this distribution type shall comply with these requirements.

Table with 2 columns: ID (01) and Requirement description.

The responsible person’s signature on this compliance document affirms that all applicable requirements in this table have been met.

P. Demand Recirculation Manual Control (R-DRmc) (RA4.4.9)/Sensor Control (RDRsc) (RA4.4.10) Requirements

Systems that utilize this distribution type shall comply with these requirements.

Table with 2 columns: ID (01-07) and Requirement description.

The responsible person’s signature on this compliance document affirms that all applicable requirements in this table have been met.



SAMPLE FORM – NOT VALID FOR SUBMISSION TO BUILDING DEPARTMENTS

Q. HERS-Verified Demand Recirculation Manual Control (RDRmc-H) (RA3.6.6)/Sensor Control (RDRsc-H) (RA3.6.7) Requirements

Systems that utilize this distribution type shall comply with these requirements.

01	HERS rater shall perform a visual inspection to verify that the demand pump, manual/sensor controls and thermo-sensor are present and operating properly consistent with the applicable requirements of RA4.4.9 and RA4.4.10	
02	Verification Status:	<input type="checkbox"/> <u>Pass</u> - all applicable requirements are met; or <input type="checkbox"/> <u>Fail</u> - one or more applicable requirements are not met. Enter reason for failure in corrections notes field below; or <input type="checkbox"/> <u>All N/A</u> - This entire table is not applicable
03	Correction Notes:	

The responsible person’s signature on this compliance document affirms that all applicable requirements in this table have been met unless otherwise noted in the Verification Status and the Correction Notes.

R. Determination of HERS Verification Compliance

All applicable sections of this document shall indicate compliance with the specified verification protocol requirements in order for this Certificate of Verification as a whole to be determined to be in compliance.

01	
----	--

For information and data collection only. Not valid until registered with a HERS provider



HERS VERIFIED INDIVIDUAL DWELLING UNIT HOT WATER SYSTEM DISTRIBUTION

CALIFORNIA ENERGY COMMISSION

CEC-LMCV-PLB-22-H

SAMPLE FORM – NOT VALID FOR SUBMISSION TO BUILDING DEPARTMENTS

DOCUMENTATION AUTHOR'S DECLARATION STATEMENT

1. I certify that this Certificate of Verification documentation is accurate and complete.

1. I certify that this Certificate of Verification documentation is accurate and complete.	
Documentation Author Name:	Documentation Author Signature:
Company:	Date Signed:
Address:	CEA/HERS Certification Information (if applicable):
City/State/Zip:	Phone:

RESPONSIBLE PERSON'S DECLARATION STATEMENT

2. I certify the following under penalty of perjury, under the laws of the State of California:

- The information provided on this Certificate of Verification is true and correct.
- I am the certified HERS Rater who performed the verification identified and reported on this Certificate of Verification (responsible rater).
- The installed features, materials, components, manufactured devices, or system performance diagnostic results that require HERS verification identified on this Certificate of Verification comply with the applicable requirements in Reference Appendices RA2, RA3, and the requirements specified on the Certificate of Compliance for the building approved by the enforcement agency.
- The information reported on applicable sections of the Certificate(s) of Installation (LMCI) signed and submitted by the person(s) responsible for the construction or installation conforms to the requirements specified on the Certificate(s) of Compliance (LMCC) approved by the enforcement agency.
- I understand that a registered copy of this Certificate of Verification shall be posted, or made available with the building permit(s) issued for the building, and made available to the enforcement agency for all applicable inspections, and I will take the necessary steps to ensure this requirement is accomplished.
- I understand that a registered copy of this Certificate of Verification is required to be included with the documentation the builder provides to the building.

BUILDER OR INSTALLER INFORMATION AS SHOWN ON THE CERTIFICATE OF INSTALLATION

Company Name (Installing Subcontractor, General Contractor, or Builder/Owner):	
Responsible Builder or Installer Name:	CSLB License:

HERS PROVIDER DATA REGISTRY INFORMATION

Sample Group Number (if applicable):	Dwelling Test Status in Sample Group (if applicable):
--------------------------------------	---

HERS RATER INFORMATION

HERS Rater Company Name:	
Responsible Rater Name:	Responsible Rater Signature:
Responsible Rater Certification Number w/ this HERS Provider:	Date Signed:

For assistance or questions regarding the Energy Standards, contact the Energy Hotline at: 1-800-772-3300

Registration Number:

Registration Date/Time:

HERS Provider:

CA Building Energy Efficiency Standards – 2022 Low-Rise Multifamily Compliance

January 2022

CERTIFICATE OF VERIFICATION – DATA FIELD DEFINITIONS AND CALCULATIONS	LMCV-PLB-22-H
HERS Verified Individual Dwelling Unit Hot Water System Distribution	(Page 1 of 4)

LMCV-PLB-22-H User Instructions

A. Design HERS Verified Central Water Heating Systems Information

This table reports the water heating system features that were specified on the registered LMCC compliance document for this project. For information only and requires no user input.

A1. Design HERS Verified Dwelling Unit HPWH System Information

This table reports the water heating system features that were specified on the registered LMCC compliance document for this project. This section is for information/verification purposes only and requires no user input.

B. Installed HERS Verified Dwelling Unit Water Heating Systems Information

This table reports the water heating system information that is being installed. Require one line for each system.

1. Dwelling Unit Name - Reference information from LMCC.
2. Water Heating System ID or Name – Reference information from LMCC.
3. Water Heating System Type – Reference information from LMCC. The different kinds of water heating system type are DHW, or Combined Hydronic.
4. Water Heater Type – Information from LMCC. The different kinds of water heaters are Large/Commercial Storage, Small/Consumer Storage, Residential-Duty Commercial Storage, Heat Pump, Boiler, Large/Commercial Instantaneous, Small/Consumer Instantaneous, Residential-Duty Commercial Instantaneous or Indirect.
5. # of Like (or Identical) Water Heaters in system – Reference information from LMCC.
6. Fuel Type – Reference information from LMCC. The different kinds of fuel types are natural gas, propane, oil, or electricity.
7. Rated Input Type – Reference information from LMCC. For natural gas, propane and oil fuel type the input type is Btu/hr. For electric the input type is kW.
8. Rated Input Value – User input. Numerical value of the rated input. Must be equal to or less than value indicated on the LMCC.
9. Central DHW System Distribution - Reference information from LMCC.
10. Dwelling Unit DHW System Distribution Type - Reference information from LMCC.
11. Compact Distribution - Reference information from LMCC.
12. Drain Water Heat Recovery - Reference information from LMCC.

B2. Installed HERS Verified Dwelling Unit HPWH System Information

This table reports the water heating system information that is being installed. Require one line for each installed water heater. Not applicable for central systems.

1. Dwelling Unit Name – Reference information from Table A2.
2. Water Heating System ID or Name – Reference information from Table A2. AFUE, UEF and Thermal Efficiency.
3. Modeled Equipment Make and Model – User input must be equal to the value indicated on Table C as default and allow user to override with an equivalent system based on the simulated equipment in Table A2.
4. # of Like (or Identical) Water Heaters in System – Reference information from Table A2.

CERTIFICATE OF VERIFICATION – DATA FIELD DEFINITIONS AND CALCULATIONS	LMCV-PLB-22-H
HERS Verified Individual Dwelling Unit Hot Water System Distribution	(Page 2 of 4)

5. Tank Location – User input. Must be equal to value indicated in Table B2.
6. Exterior Tank Insulation R-value – User input. Must be equal to or higher than value indicated in Table A2.
7. Dwelling Unit DHW System Distribution Type – Reference information from Table A2.
8. Compact Distribution – Reference information from Table A2.

C. Design HERS Verified Dwelling Unit Water Heating Efficiency Information

This table reports the water heating system features that were specified on the registered LMCC compliance document for this project. For information only and requires no user input.

D. Installed HERS Verified Dwelling Unit Water Heating Efficiency Information

This table reports the water heating system information that is being installed. Require one line for each central system.

1. Water Heating System ID or Name – Reference information from LMCC
2. Heating Efficiency Type – Reference information from LMCC. Different efficiency types are Energy Factor, AFUE, UEF and Thermal Efficiency.
3. Heating Efficiency Value – User input. Numerical value of the Heating Efficiency. Must be equal to or higher efficiency than value indicated on the LMCC.
4. Standby Loss – User input. Must be equal to or less than value indicated on the LMCC. Value may be N/A if LMCC value is N/A.
5. Exterior Insulation R-Value – User input. Must be equal to or higher than value indicated on the LMCC. Value may be N/A if LMCC value is N/A.
6. Water Heater Storage Volume (gal) – User input. Value may be N/A if water heater type is instantaneous with zero storage.
7. Tank location – User input. Must be equal to system type indicated on the LMCC.

E. Installed Water Heater Manufacturer Information

This table reports the manufacturer information of the installed water heater(s). Require one line for each installed water heater

1. Water Heating System ID or Name – Reference information from LMCC.
2. Manufacturer – User input. Enter the name of the water heater manufacturer.
3. Model Number – User input. Enter the model number of the water heater.

F. Mandatory Measures for all Domestic Hot Water Distribution Systems

This table lists the requirements for all DHW systems. HERS rater must ensure all the requirements in this table are met.

G. HERS-Verified Compact Hot Water Distribution Expanded Credit and

H. Compact Hot Water Distribution Basic

If performance compliance is used, this table lists the values used in the performance calculation and require no user input.

If prescriptive compliance is used, fill out this table

1. Reference information from LMCC
2. Enter the Master Bath distance of furthest fixture to Water Heater in feet. For multiple water heaters, enter the distance to the closest water heater.

CERTIFICATE OF VERIFICATION – DATA FIELD DEFINITIONS AND CALCULATIONS	LMCV-PLB-22-H
HERS Verified Individual Dwelling Unit Hot Water System Distribution	(Page 3 of 4)

3. Enter the Kitchen distance from furthest fixture to Water Heater in feet. For multiple water heaters, enter the distance to the closest water heater.
4. Enter Furthest Third fixtures from fixture to Water Heater in feet. For multiple water heaters, enter the average of the furthest distance of each water heater.
5. Calculated value – no user input required
6. Calculated value – no user input required

I. HERS-Verified Drain Water Heat Recovery System

This table lists the requirements for all central recirculation systems. HERS rater must ensure all the requirements in this table are met.

1. Reference information from LMCC.
2. Reference information from LMCC.
3. Reference information from LMCC.
4. Reference information from LMCC.
5. Reference information from LMCC.
6. Drain Water Heat Recovery Manufacturer’s name- Enter the name of the Manufacturer.
7. Drain Water Heat Recovery Manufacturer’s model number – Enter the Model number.
8. Rated Effectiveness’ – Enter the rated effectiveness of the DWHR device.
9. Installation Configuration – Enter type of configuration. Available options are Equal flow, unequal to shower, and unequal to water heater
10. Percent of shower served by the DWHR device – Enter the percent of showers served by this DWHR device.
11. DWHR System Certified by CEC – Enter “Yes” if certified or else enter “No”.

J. HERS-Verified Pipe Insulation Credit Requirements

This table only applies to systems indicated as **HERS-Verified Pipe Insulation Credit**. In addition to the mandatory requirements in Table F, the HERS rater must ensure the requirements in this table are met.

K. HERS-Verified Parallel Piping Requirements

This table only applies to systems indicated as **HERS-Verified Parallel Piping**. In addition to the mandatory requirements in Table F, the HERS rater must ensure the requirements in this table are met.

L. Parallel Piping Requirements

This table only applies to systems indicated as **Parallel Piping**. In addition to the mandatory requirements in Table F, the installer must ensure the requirements in this table are met.

M. Point of Use Requirements

This table only applies to systems indicated as **Point of Use** In addition to the mandatory requirements in Table F, the installer must ensure the requirements in this table are met.

N. Mandatory Requirements for all Recirculation Systems

The requirements of this table apply to all recirculation systems listed below.

CERTIFICATE OF VERIFICATION – DATA FIELD DEFINITIONS AND CALCULATIONS	LMCV-PLB-22-H
HERS Verified Individual Dwelling Unit Hot Water System Distribution	(Page 4 of 4)

O. Recirculation Non-Demand Controls Requirements

This table only applies to systems indicated as **Recirculation Non-demand controls**. In addition to the mandatory requirements in Table F and N, the installer must ensure the requirements in this table are met.

P. Demand Recirculation Manual Control/Sensor Control Requirements

This table only applies to systems indicated as **Demand Recirculation Manual Control, Demand Recirculation Sensor Control, HERS-Verified Demand Recirculation Manual Control or HERS-Verified Demand Recirculation Sensor Control**. In addition to the mandatory requirements in Table F and N, the installer must ensure the requirements in this table are met.

Q. HERS-Verified Demand Recirculation Manual Control (RDRmc-H) (RA3.6.6)/Sensor Control (RDRsc-H) (RA3.6.7)

This table only applies to systems indicated as **HERS-Verified Demand Recirculation Manual Control or HERS-Verified Demand Recirculation Sensor Control**. In addition to the mandatory requirements in Table F and N, the HERS rater must ensure the requirements in this table are met.

R. Determination of HERS Verification Compliance

1. This field is filled out automatically. Compliance requires that all individual criteria pass.

Documentation Declaration Statements

1. The person who prepared the LMCV will sign and complete the fields for their name, company (if applicable), address, phone number, certification information (if applicable), date and signature.
2. The person who is assuming responsibility for the project being built to comply with Title 24, Part 6, will complete the fields (if applicable) for their company, responsible builder or installer name, CSLB license number, sample group number, dwelling test status in sample group, HERS Rater company name, HERS Rater name, HERS Rater signature, HERS Rater certification number and date signed.