



ENERGY RESEARCH AND DEVELOPMENT DIVISION

Appendix A: Technology Descriptions

June 2024 | CEC-500-2024-054-AP




APPENDIX A: Technology Descriptions

Project plan included demonstration of three specific technologies. They are the gas-engine heat pump (GEHP), the evacuated tube collector (ETC), and Energy dual setpoint controller.

The GEHP Technology

While the traditional approach of water heating with a flame remains largely unchanged with incremental improvements in efficiencies up to 85 to 95 percent, natural-gas-engine-driven heat pumps offer an economic alternative to gas water heaters and boilers and an outstanding opportunity to reduce water heating costs and lower greenhouse gas (GHG) emissions. New advances in internal- combustion-engine technology in the automobile industry have led to significant improvements in reliability and efficiency of the GEHP with operating life exceeding 20,000 hours. Additionally, new emissions-control technology has led to cleaner emissions and lower criteria pollutants. However, the GEHP is still considered an emerging and underutilized technology. The most efficient and advanced GEHP is the Ilios HEWS 500-AS.

Figures A-1 and A-2 show the Ilios heat pump. A GEHP heat pump traditionally consists of a vapor-compression refrigeration cycle that includes a condenser, an evaporator, a throttling valve, and a compressor. Compressor-shaft work is provided by a reciprocating engine. A measure of efficiency is the coefficient of performance (COP), which is defined as the useful energy "out" (hot water), divided by the useful energy "in" (fuel). Depending upon operating conditions the Ilios unit's COP is between 1.2 to 2.2. By comparison, a typical gas fired boiler that produces 550,000 British thermal units (Btu)/hr of hot water would consume 687,500 Btu/ hr of gas (80 percent efficiency), or almost twice as much fuel as the Ilios.



Figures A-1 and A-2: Ilios Heat Pump

Source: Tecogen

The graphs below illustrate how the capacity (heat output) of the Ilios increases with outdoor air (Figure A-3) resulting higher COPs (Figure A-4). In Southern California climate conditions with milder winters and hot summers, the COP of the Ilios GEHP should be consistently high. With this higher COP there will be significant reduction of fuel use and GHG emissions.





Figure A-3: Outdoor Air Temperature Versus





Source: Solar Rating and Certification Corporation (SRCC) Source: Tecogen

The main features of this technology are:

- 90 kilowatts (kW) to 175 kW of hot water ideal for domestic hot water (DHW), swimming pools, space heating, or process heat.
- Hot water delivery temperature 100°F (38°C) to 160°F (71°C).
- Advanced thermodynamic cycle extracts available energy from the environment, and uses mechanical work from a gas engine (natural or gaseous propane) to pump this heat to a higher useful temperature.
- Highly efficient heat pump with reclaimed engine waste heat resulting in a COP of 1.2 to 2.2.
- Exceeds clean emission standards throughout the United States, including California.
- 50 percent reduction in carbon footprint saving 100 tons of carbon at typical installations.
- Ultra-low emissions with near-zero criteria pollutants.
- Minimal electrical power requirement similar to a household appliance (220 volts [V] alternating current [AC]/50 hertz [Hz]/10 amperes [A] service).

The Evacuated Tube Collector (ETC)

In use since the early 1900s, flat-plate collectors are time-tested, reliable, and currently dominate the market. ETCs are a more recent technology, introduced in the late 1970s. Several types are available, with the common element being a glass tube surrounding an absorber plate. Because the space inside the tube is a vacuum, which is a far superior insulator than air, these collectors have much better heat retention than the glazing/air space (R-7) design of flat-plate collectors, which makes them particularly highly efficient under many circumstances. Frames and manifolds for paralleling multiple tubes are available and can hold 4 to 20 tubes or more. Multiple banks can be plumbed together to increase system capacity. While overall weights and dimensions are similar between the two types, evacuated tubes usually have performance and installation advantages. Sealing and maintaining a vacuum is difficult, and this was a common problem that plagued early designs. Today the majority of ETCs use a continuous piece of glass to minimize the risk of vacuum loss. The ETC is considered an emerging and underutilized technology.

Collectors operate most efficiently when the temperature of the inlet fluid (Ti) is the same as or less than the ambient temperature (Ta) of the air. When Ti equals Ta, flat-plate collectors tend to be about 75 percent efficient, while evacuated tubes have an efficiency of about 50 percent. However, collectors rarely operate under these conditions. Table A-1 illustrates that the ETC performs better for high-temperature DHW application. Figure A-5 illustrates that performance of the ETC is superior in higher outdoor temperatures past 80°F (27°C), which is expected in many California climate zones for many months of the year, including the one for our test building. Figure A-6 is an illustration of the evacuated tube collector.

COMPARISON F	PERFORMANC	E: FLAT PLATE TO	EVACUATED	TUBE (SRCC DATA)			
	BTUS PER PANEL PER DAY						
Temp/ condition	Clear day ~2,	ay ~2,000 BTU/f2/day Partly cloudy ~1,500 BTU/f2/day		av i i i i i i i i i i i i i i i i i i i			
	Flat plate	Evacuated	Flat plate	Evacuated	Flat plate	Evacuated	
A9°F (Pool 1)	53,000	43,000	42,000	32,000	28,000	22,000	
B. 9°F (Pool 2)	48,000	41,000	36,000	31,000	22,000	20,000	
C. 36°F (DHW 1)	40,000	38,000	27,000	28,000	13,000	17,000	
D. 90°F (DHW 2)	24,000	32,000	12,000	22,000	2,000	12,000	
E. 144°F (A/C)	9,000	26,000	1,000	15,000	0	6,000	

Table A-1: Comparison Performance

Source: SRCC

The project is to study how best to integrate the two technologies in order to maximize energy savings and GHG reduction at the lowest possible cost. Cost will depend on size of the solar collectors, the storage tank size and the ancillary materials and equipment such as storage

tank, pumps and, trenching, piping and insulation distances. Please see Figure 3 in Chapter 5 for a schematic diagram of the proposed configuration. We will also use the Energx hot water loop controller to reduce line losses during low demand. Testing will be done with either the GEHP operating or the ETC operating to collect performance data for each subsystem.





Figure A-5: Evacuated Tube Performance





Source: Apricus

Source: SRCC

Energx dual setpoint controller

The Energx dual setpoint controller is an energy savings controller that reduces the water temperature setpoint when hot water is not required. The savings are primarily achieved in two ways, one by controlling the set point temperature of the water in the storage tank and secondly by controlling the firing rate of the boiler, as these boilers typically have three to four burners staged in series to meet various load changes.

Depending on the application and number of boiler stages, one to four original equipment manufacturer Honeywell logic controllers are used to process the temperature(s) in the storage tank and cycle the stages of the boiler on/off. An additional temperature controller and relays are integrated into the control to measure the ambient air temperature and change the water temperature setpoint. Even as the temperature is increased the controller will still optimize the firing rate/stages of the boiler.

Please note that at no time is the system locked out (demand limiting) – hot water is always available to occupants and the Energx control system will cause the boiler to maintain the tank water temperature setpoint. No fuzzy logic is used to automate the temperature set point adjustments. It is expected that the operator only needs to set it once with little if any adjustments throughout the change of seasons.


The controller being studied is a dual setpoint controller (Figure A-7), and has two tank water temperature setpoints, referred to here as high temperature and low temperature. When the ambient temperature rises the Energy controller will place the boiler water set point at the low temperature setting to conserve energy. Conversely, if the ambient air temperature is detected

to be below the threshold (such as at night or a cold day) the boiler will be placed on the highwater temperature setpoint in order to be able to provide more heat to the apartment fan coils (Figure A-8). The high-temperature setpoint is typically approximately 140°F (60°C) while the low temperature setpoint is approximately 120°F (49°C). Even with 120°F (49°C) water being supplied to the fan coils, heat is still available from the apartment fan coil units if a resident were to adjust their thermostat to call for heating. Domestic water at 120°F (49°C) is considered sufficient for bathing and washing, etc.



Figure A-7: Energx Raydronics Boiler

Figure A-8: Monitored Boiler Temperature



Source: Energx Controls

Source: Negawatt Consulting

The energy savings are achieved by allowing the system to operate at the low temperature water set point during the mild to hot weather conditions found much of the year throughout the Southern California area. According to Energx, there are hundreds of Raydronics systems within the SoCalGas service territory, each consuming approximately 350 therms per apartment unit per year. The potential market is of significant size.







ENERGY RESEARCH AND DEVELOPMENT DIVISION


Appendix B: Project Plans


June 2024 | CEC-500-2024-054-AP

















SYSTEM CONTROL SCHEDULE	DIFFERENTIAL CONTROLLER - STECA MODEL TR0603mc+		ENGINE EXHAUST BACKPRESSURE - CALCULATION As per Caterpillar Application and Installation Guide							
Sensors and Controls:			Backpress	ure is calo	ulated by		Equivalent Length	of Straight F	Pipe	_≪ ⊻
T-1 Temperature Sensor Solar Collectors	System voltage	230 V AC (± 15 %), 50 Hz	-	1	2.6	-				0 O
T-2 Temperature Sensor at top of Storage Tank (set at 145 degF)	System voltage optional	115 V AC (± 15 %), 60 Hz	P =	D	x 3.6 x 10 ⁶ +	Ps	Standard Elbow Long Elbow		33x D/12 20 x D/12	AT SOL
T-3 Temperature Sensor at upper third of Storage Tank (Set at 140 degF)	Standby	1.57 W	OR				45 deg Elbow	L =	15 x D/12	
	Temperature control class	1		L x S x	O ²		Square Elbow	L =	66 x D/12	CONTROLS &
T-4 Temperature Sensor at bottom of Storage Tank (set at floating temp)	Energy efficiency Number of inputs	1% 6	P =	187 x D		Ps	Assume:	2 inch exha	aust	
P-1 Solar Collector Loop Pump	Inputs	5 x temperature (Pt1000), 1 x temperature (Pt1000) or pulse					1 Standard Elbow	(33 x 2)/1	12	
P-2 Solar Heat Pump to Tank	Additional inputs	1 x Grundfos Direct Sensors™ (temperature / flow rate)		P= L=	Back pressure in i Total equivalent I		2 Long Elbows 2 45 deg Elbows	(20 x 2 x 2) (15 x 2 x 2)		
P-3 GEHP Heat Pump	Number of outputs	3		Q =	Exhaust gas flow i		Straight lenth L	30 ft	c)/ 12	
2-4 GEHP heat to Tank		2 x triac for speed control (R1, R2), max. 250 W (230 V) or PWM control signal for pump speed (PWM R1, PWM R2); 1 x		D = S =	Diameter of pipe Density of gas		TOTAL			Contraction of the local data
	Outputs	switch output relay (R3), max. 800 W (230 V) or R3 voltage		P, =	Pressure drop of s	ilencer				and frank
FS-1 Flow switch in GEHP piping		free								
DC-1 Differential Controller - Solar Loop	Hydraulic schemes	40	Assume : P. =		0 psi sino	e silencer is in	tegral to engine	-		BROFES
DC-2 Differential Controller - GEHP Loop	Ambient temperature Interfaces	0 °C +45 °C SD card, RS-232, RS-485 (Steca TPC 1 bus)	Diameter		2 inches					
Differential Controller: Steca Model TR0603mc+	Data logging	SD card, NS-232, NS-465 (Stelda FPC F bus)	Exhaust C Equiv Len		89 cfm 47					
	Degree of protection	IP 20 / DIN 40050		[
Control Schema	Dimensions (X x Y x Z)	170 x 170 x 46 mm [0.00 x 0.00 x 0.00 inch]	P =	37 x 0.00	3 x 89 x 89	+ 0				
DC-1 senses solar collector temp T-1 and storage tank water temperature T-2	Weight	450 g [0.00 oz]			187 x 2 ⁵					
If T-1 > T-2 turns on pumps P-1 and P-2 to transfer heat from solar to tank through Heat			P =	0.4977	1 psi					၂၂ တ
Exchanger HE-1			Max Allov	vable Bac	Pressure by Manu	f 40	n WC			5 S
-										🗒 ब
At T-2 temperature 145 degF, DC-1 shuts down pumps P-1 & P-2 and collector flows goes into									I	≥ i
stagnation										
DC-1 senses tank temperatures T-3 at tank upper location and cold water temperature T-4 at										II E ≼ 2
tank bottom										5 4
If T-3>T4 turns on pumps P-3 and P-4 to transfer heat from GEHP into storage tank										UPGRADE FOR: PARK WEST APARTMENTS I INCOLNED VID AT 1 A THERA BLVD
										II G CL A
FS-1 Senses flow and starts up GEHP										II 3 2
When T-3 reaches 140 degF, DC-2 shuts off pumps P-3 and P-4										
FS-1 When flow ceases, turns off GEHP										UPGRADE FOR : ARK WEST APARTMENT
	ц									2 -
										SHEET TITLE:
										REVISIO
										PWPM: Ahmed
										JOB NUMBER:
										SCALE AS NOT
										BY: H.Dion
										ISSUE DATE
										SHEET
	1		1							M-

EVACUATED TUBE SOLAR COLLECTORS ETC-1

Make: ErgSol Model: 100-6 df Fluid: De-mineralized Water No of Tubes/Panel: 20 Gross Area: 17.11 SqFt Aperture Area: 12.26 SqFt SRCC Rate btu/day: 20,000 btu SRCC OG 100 Certification: Yes No: 10001807

Heat Pipe: Copper Outer Tube Dia: 4 inches Tube Material: Glass

Collector Size: 68" x 80" Weight: 170 lbs Collector Flow Rate: 0.7 gpm

Operating Pressure: 20-70 psi Maximum Pressure: 150 psi

Stagnation Temperature: 450 degF

Total Number of Panels: 20 Collector Mounting: For EPDM Roof Deck Collector Angle: 30 degree Collector Orientation: 130 deg South Facing

STORAGE TANK ST-1

Make: Hanson Tank or Equal Model: GS-48-585-V Type: Vertical Capacity: 585 gallons, Application: Domestic Hot Water Surface Area: 94.5 SqFt, Pressure: 240 psig Temp: 210 degF No of Legs: 4 Construction: Steel Lining: Glass Dimension: 48" OD x 87" H with legs Weight: 1143 lbs (unfilled) Standard ASME rated vertical steel tank with connections as shown in drawings With 84" MAG Anode 11" x 15" manhole Factory insulation is a 2 component HCFC blown, polyurethane spray foam system. The foam is

rated CLASS | according to ASTM E-84 at two inches, flame spread index 25 with 345 smoke developed.

SOLAR THERMAL EXPANSION TANK ET-1

Make: B&G Xylem or Equal Type: Vertical Bladder Type Application: Glycol Solution Size: 20 Gallon Construction: Carbon Steel Bladder Type: Rubber Factory Pre-charge: 36 psig Max Pressure: 150 psig Max Operating Temp: 260 degF certification: ANSI/ASIME Diameter: 16 inch Length: 30 inch Air tight cushion. GEHP SYSTEM THERMAL EXPANSION TANK ET-2 Make: B&G Xylem or Equal Type: Vertical Bladder Type Application: Glycol Solution Size: 10 Gallon Construction: Carbon Steel Bladder Type: Rubber Factory Pre-charge: 36 psig Max Pressure: 150 psig Max Operating Temp: 260 degF_certification: ANSI/ASME Diameter: 12 inch Length: 16 inch Air tight cushion

EQUIPMENT SCHEDULE

GAS ENGINE HEAT PUMP GEHP-1

Make: Ilios/Tecogen, Model: HEWH-500-AS Fluid: Water Thermal Output: 400,000-600,000 btu/hr Rated COP: 1.2-2.2 Water Flow Rate: 50 gpm Water Delivery Temp: 100-160 degF Sound Rating: 72 dba@20 ft Electrical Power: 120V/1ph/60Hz Amps: 15A. Gas Pressure: 8-12 inch wc. Gas Conn: 1 inch. Max Gas Flow: 390 SCFH, Refrigerant: HFC-134A Water Connection: 2 inch Dimension: 7'3"L x 4'1" W x 7'1"H Weight: 4,200 lbs Exhaust Conn: 2 inch Ultra low-emission natural gas 4-cylinder engine (<50 hp). Internal 5 kW generator for parasitic loads. Spark Ignition, 0.5% Oxygen air fuel mixture, electronic ignition, 12V DC Battery 5W-20 Synthetic blend oil, Compact brazed plate condenser. Integral catalytic converter and silencer. Excluded from SCAQMD source test requirements

PUMP P-1

Make: B&G or Equal Model: Series 3530 Quantek Fluid: 80% Glycol Solution Location: Between Solar Collectors and Heat Exchanger HE-1 Flow: 30 gpm TDH : 90 ft WC HP : 1.50 hp Volts: 208/230 PH: 1 ph Hz: 60 hz Pump Body: Stainless Steel Impeller: Stainless Steel Shaft: Stainless Steel Gasket /O-ring : EPDM Flange: 1.5 inch Insulation Class: F Weight: 39.6 lbs Max Working Press: 175 psi. Max Working Temperature: 230 degF TEFC Motor, In-line Close Coupled pump with VFD accessory

EQUIPMENT



UPGRADE FOR : **(WEST APARTMENTS** OLN BLVD AT LA TIJERA BLVD LOS ANGELES, CA LINCOLN I PARK \

REVISIONS

Ahmed

BY: H.Dion

AS NOTED

M-7

JOB NUMBER SCALE

ISSUE DATE

S

Solar Collector Piping	Corrugated stainless steel tube 1.5 in diameter with temperature range of -450degF-+1112 degF. Recommended pressure at +392 degF 3/4 inch 159 psi
Solar collector pipe insulation	1 Inch thickness made of EFDM closed cell synthetic rubber, PVC and CFC free.Meets ASTM D635 Class VD for flammability and smoke density according to UL-94, Meets CA Title-24 Standards
DHW/GEHP piping	Copper tube, hard drawn, type L: to ASTM B88M. Bronze pipe flanges and flanged fittings, Class 150 and 300: to ANS/ASME B16.24.
DHW/GEHP pipe Insulation	1 inch thickness made of EFDM closed cell synthetic rubber, PVC and CFC free.Meets ASTM D635 Class VD for flammability and smoke density according to UL-94, Meets CA Title-24 Standards
DCW piping	Copper tube, hard drawn, type L: to ASTM B88M. Bronze pipe flanges and flanged fittings, Class 150 and 300: to ANSI/ASME B16.24.
Natural Gas Piping	Steel and wrought-iron pipe shall be not less than standard weight (Schedule 40) and shall comply with ASME B36.10, ASTM A53, ASTM A106 (NFPA 54; 5.6.2.2)
Storage Tank	Vertical 160# ASME (HLW) for potable hot water, glass lined 5-12 mils, Steel construction , angle leg support, handhold. Max temp 210 degF
Storage Tank insulation	Spray-on polyurethane foam factory insulation with topcost. Nominal "R" value is R-16 @ 2" thick. This exceeds ASHRAE requirements. With min 2 inches of foam insulation
Engine Exhaust	2 inch carbon steel with wided joints rated for engine exhaust temperature
Engine Exhaust Insulation	2 inch Calcium Silicate insulation with protective jacket and water proof jacket for pipe extending on outside the building


SOLAR SIDE	ater and 80% Gly	1001
Flow - Glycol		gpm
Water Temp from Solar	150	
Water TEMP to Solar		degF
Total BTU Q DHW SIDE	300000	btu
Flow Water		gpm
Inlet Water Temp from Tank		degF
Dutlet Water TEMP to Tank		degF
Total BTU Q	255000	
Approach GEHP Side High Temp-Tank Side High Temp Io of Passes: 1, Channels: 20, Rated PSI: 150 psig, M		degF
LATE AND FRAME HEAT EXCHANGER HE-2 Make: B&G Model: GPX AP20-DW-41-TL Fluids: Wa	iter	
tterplate space open to air. LATE AND FRAME HEAT EXCHANGER HE-2 Aake: B&G Model: GPX AP20-DW-41-TL Fluids: Wa GEHP SIDE		
LATE AND FRAME HEAT EXCHANGER HE-2 Make: 8&G Model: GPX AP20-DW-41-TL Fluids: Wa GEHP SIDE Flow	50	
LATE AND FRAME HEAT EXCHANGER HE-2 fake: B&G Model: GPX AP20-DW-41-TL Fluids: Wa GEHP SIDE Flow Water Temp from GEHP	50	deg
LATE AND FRAME HEAT EXCHANGER HE-2 Make: B&G Model: GPX AP20-DW-41-TL Fluids: Wa GEHP SIDE Flow Water Temp from GEHP Water TEMP to GEHP	50 150 130) deg) deg
LATE AND FRAME HEAT EXCHANCER HE-2 take: B&G Model: GPX AP20-DW-41-TL Fluids: Wa GEHP SIDE Flow Water TemP from GEHP Vater TEMP to GEHP Total BTU Q	50) deg) deg
LATE AND FRAME HEAT EXCHANGEN HE-2 fake: B&G Model: GPX AP20-DW-41-TL Fluids: Wa GeHP Stote Flow Water Temp from GEHP Water Temp from GEHP Total STU Q DHW SIDE	50 150 130 500000) deg) deg) btu
LATE AND FRAME HEAT EXCHANGER HE-2 fake: 88.6 Model: GPX AP20-DW-41-TL Fluids: Wa derb 900e Row Water Temp from GEHP Water TEMP to GEHP Total 911 Q DHW 910E Flow	50 150 500000 43) deg) deg) btu gpn
LATE AND FRAME HEAT EXCHANCER HE-2 take: B&G Model: GPX AP20-DW-41-TL Fluids: Wa GEHP SIDE Flow Water Temp from GEHP Vater TEMP to GEHP Total BTU Q DHW SIDE Flow Infut Water Temp from Tank	50 150 500000 43 120) deg) deg) btu) btu) deg
LATE AND FRAME HEAT EXCHANGEN HE-2 fake: B&G Model: GPX AP20-DW-41-TL Fluids: Wa GelP Stoe Flow Water Tempfrom GEHP Water TEMP to GEHP Total STU Q DHW STOE Flow Inlet Water Temp from Tank Quietie Water TEMP to Tank	56 156 130 500000 43 120 140) deg) deg) btu) gpn) deg) deg
LATE AND FRAME HEAT EXCHANGER HE-2 fake: 88.6 Model: GPX AP20-DW-41-TL Fluids: Wa derb 900e Row Water Temp from GEHP Water Temp from GEHP Total 917 U, Q DHW 900E Flow Inlet Water Temp from Tank Outlet Water TEMP to Tank Total 917 U, Q	56 156 130 500000 43 120 140 425000) deg) deg) btu) btu) deg) deg) btu
LATE AND FRAME HEAT EXCHANGER HE-2 fake: B&G Model: GPX AP20-DW-41-TL Fluids: Wa GelP Stote Flow Water Tempfrom GEHP Water TEMPfrom GEHP Total STU Q DWH STOE Flow Initiv Water Temp from Tank Outlet Water TEMP to Tank Outlet Water TEMP to Tank Total STU Q Approach. GEHP Side High Temp-Tank Side High Temp	56 150 130 500000 43 120 140 425000) deg) deg) btu) btu) deg) deg) btu) deg
LATE AND FRAME HEAT EXCHANGER HE-2 fake: 88.6 Model: GPX AP20-DW-41-TL Fluids: Wa derby Stote Flow Water Temp from GEHP Water Temp from GEHP UNW STOC Flow Inlet Water Temp from Tank Outlet Water Temp from Tank Total STU Q Approach GEHP Side High Temp-Tank Side High Temp No of Passes: J. Channels: 20, Rated PSI: 150 psig, N	50 15(13(500000 43 120 14(425000 10 14 X 120 14 X 120 14 14 14 14 14 14 14 14 14 14 14 14 14) deg) deg) btu) btu) deg) deg) btu) deg
LATE AND FRAME HEAT EXCHANGER HE-2 fake: B&G Model: GPX AP20-DW-41-TL Fluids: Wa GelP Stote Flow Water Tempfrom GEHP Water TEMPfrom GEHP Total STU Q DWH STOE Flow Initiv Water Temp from Tank Outlet Water TEMP to Tank Outlet Water TEMP to Tank Total STU Q Approach. GEHP Side High Temp-Tank Side High Temp	50 150 130 500000 42 120 140 425000 425000 140 425000 140 425000 140 140 140 140 140 140 140 140 140) btu gpn) deg) deg) btu) deg


PUMP P-2


Make: B&G or Equal, Model: Ecocirc XL 65-130, Fluid: Water Location: Between Storage Tank and Heat Exchanger HE-1 Flow: 20 ppm. TDH : 40 ft WC HP : 1.0 hp. Volts: 208/230 PH: 1 ph Hz: 60 hz Pump Body: Cast Iron, Impeller: Poly-phenylene Sulfide Shaft: Stainless Steel Gasket /O-ring : EPDM Flange: 1.5 inch Insulation Class: F Weight: 39.6 lbs Max Working Press: 125 psi, Max Working Temperature: 225 degF In-Line circulator. Electronically commutated permanent magnet motor

PUMP P-3


Make: B&G or Equal Model: Ecocirc XL 65-130 Fluid: Water Location: Between GEHP and Heat Exchanger HE-2 Flow: 50 gpm TDH : 45 ft WC HP : 1.0 hp Volts: 208/230 PH: 1 ph Hz: 60 hz Pump Body: Cast Iron Impeller: Poly-phenylene Sulfide Shaft: Stainless Steel Gasket /O-ring : EPDM Flange: 1.5 inch Insulation Class: F Weight: 39.6 lbs Max Working Press: 175 psi, Max Working Temperature: 230 degF In-Line circulator. Electronically commutated permanent magnet motor PUMP P-4 Make: B&G or Equal Model: Ecocirc XL 65-130 Fluid: Water Location: Between Storage Tank and Heat Exchanger HE-2 Flow: 43 gpm TDH : 40 ft WC HP : 1.0 hp Volts: 208/230 PH: 1 ph Hz; 60 hz Pump Body: Cast Iron Impeller: Poly-phenylene Sulfide Shaft: Stainless Steel Gasket /O-ring : EPDM Flange: 1.5 inch Insulation Class: F Weight: 39.6 lbs Max Working Press: 175 psi, Max Working Temperature: 230 degF In-Line circulator, Electronically commutated permanent magnet motor w/VFD







	ELECTRICAL S	PECIFICATIONS	
PHAT I GONERAL	connot be headly sean, three or here switches under a common plate and for switches as molated	R0054-RL	
1.01 SOUPE OF WORK	3 STANLESS SELL PLATES SHALL BE ANOTEN HER AND STELL INSTITUTE (AND) THE SEL, WITH BUILD EDGES, LONG" THOSE WITH SAIN SHOOTH FINISH. "SWIDTHE," HIBBELL INFOLT SCREE.	Description BOL	
A MON CONTROL OF PHS INTERN COMMENT OF THANDARS ALL LARGE EXPANDED, SUPPLIES, MO MAINTALL LARGE COMMENTS OFCONTO, NO & FUNCTIONER OF LA COMMENCE ACCESSOR FOR THE RESILUTION OF A COMPLEX MO DEVINUEL LLCTICOL STREM AL RECARD OF THESE SUPERIA ROOM AND REALCOLD OF THE REMARKS.	 PLASTIC COURP PLATE SHALL BE MAN WHACT INDIMORILISTIC, MAN STREAMT, SONITON-RESISTANT, SMOOTH AND SOLF-DYTWODISTING, HOBBILL TH'SOMES OF PLASS & STMOOTH PP SONES. 	A ALL COMPARENT SHILL BE PROPERTY GROUNDED AS INDICATED ON DRAWINGS AND AS REQUIRED BY THE LATEST. EXTEND OF APPLICABLE CODEX.	
8. THE CONTINUES BALL DAMME ALL DAMMESS AND SPECIFICATIONS IN A MANNEY IS DE FALLY CONTAINT OF ALL MORE REQUIRED LADOR THIS SECTION.	 WHERE DUTLETS ARE INDOLES IN THIS IS A THEORY OF A REAL AN AND THE SEE STRALESS WITH DOUBLE HINDED COLLERS, PASS & SCHOOLIN APPER-D 	9. FUNDOR AND INSTRUE ALL DRIVINDING CONDUCTORS, CONDUCT AND CLAMPIL. IN: STATE OF THE GROUNDING: COMBUCTORS SHALL BE NOT LESS INHY THAT SYLPPED IN THE NCC.	
C. THE CONTRACTOR SHUL OBTAIN AND PAY FOR ALL REQUESE PERMITS UNLESS OTHERMES. ARRIVED AND SOVEDILE ALL REQUESD INSPECTIONS FOR THE LIFEDITION OF THE MORE: INSPECTIONS CONTRACT.	ALL-4 Real-4	C BIADNE GYDANNES STSTUM EESTSTUMEE ID GYDAN DAVIL NOT EXCEED 25 GMAS.	
ADDENTIAL ADDRESSION OF THE ADDRESSION OF THE ADDRESSION OF CONTRACT, THE ADDRESSION OF THE ADDRESSION OF CONTRACT, THE ADDRESSION OF CONTRACT	THER GRUNNED STEL PLACE SHULL BE USED IN VIETY LARS. 2. MODULE PLACE EXAMPLE AND LOCATIONS DROWARS FOR THE EXACT DURING TO BE USED. MICHAE PLACES FOR BLEMANNE DUILITS SUBJECT WIT DURING DROWARD	 Each Brinch Chicat Shull be estimated with case size Green Ground, Eguination wite (Her Nec 280-83) (not indicated on Braining) within the Sake consult for all circuits of panelisandos. 	
A. MONY DOE LANDER TO SUPERVISE COMPT VARIE TO LANDER DELANDE ALTER SUPERVARIE. DOES HER ALTER ALTER ALTER ALTER SUPERVISE SUPERVISE, DOES HER DELANDE SUPERVISE, DOES HER DELANDE SUPERVISE, DOES HER DELANDE SUPERVISE, DOES HER DELANDE SUPERVISE, DOES HER DELANDES HER DELANDE	ESLAMPED WIN BUSINES DESINICS. 8. RETER 10 SECTION J.GR FOR LIBELING OF PLATES.	307 BUNCH SECNTS	
	 Inclusion of administration of the data of a contraint COLER PLATES OF PRESEND SEES COLLET BLACE IN FURNED AREAS, ATTCS, ETC., OR ETPOSED IN MECHANICAL EQUIPMENT ROOMS SHALL BE OF THE UNK MATTERN AS THE COLLET BLACE IN FURNED AREAS, ATTCS, ETC., OR ETPOSED IN MECHANICAL EQUIPMENT ROOMS SHALL BE 	A. NO WORE THAN THREE BRANCH CRICLITS PERMITED IN ONE CONDUCT CALLSS MIRCH RD CONSTRUCT	
лаз шестном, сонтносток'я незнонавших	or ne ume random na ne unalitada. 18. dober fales n loditars consulto from rabio ver skal hive fal carolit humers and source feed form inno labeld Met mander racks. The fermanes weread, see sector logitar labelan.	3 on Handulan	
A. IT DWLL BE THE CONTINUED RESPONDENTY TO DETAIN A COMPLETE SET OF GRAMMES. AND SPECIFICATIONS CONTINUED SHILL CHECK THE DRIVINGS OF THE OTHER TRUES AND. SHILL CHECKLY ALSO DE DRIVE SPECIFICATIONS AND DECEMBER AS ASSTRADBLITES.	WHY WARKING BLACK FOR (FORMARINE MARKER), SEE SECTION JUR FOR LIBELING. 11. REDUKE PLASTIC COVER PLATES WAESS HOLED DIFERMISE	A THE FOLLOWING ITING SHALL BE COUPPED WITH MIMOPLATES	
8. BEFORE SUBMITTING THE BID, THE LICETERUL CONTINUEDRE SHILL NOT THE LOR STE AND FILLY ACQUINT IMBERF WITH EXISTING CONTINUES IF IL THE RESTRUCTION OF THE CONTINUEDRE TO MODILE THE EXAMINING AND ALSOCIATE WHICH IN SOCIAL AMMENIA AS ID CONTINUE WITH THE CONTINUE AND THE CONTINUED ALL ADDR CONTINUES, AND RECTAINTERIST.	2.10 PHK280460	 ALL MOTHER MOTHER STATERER, CANTER FAMILE, WOTHER CONTERL MEMORE STATEMENT. ALL DESTIMATION MOTOR STATEMENT, MAN BERMATION PANEL RESERF CONTENTION OF MADE. ADD STATEMENT AND STATEMENT AND ADDRESS AND STATEMENT OF MADE. 	
C. THE WITH OF THESE DRIVINGS IS TO SECTIONE A COMPLETE AND OPENING. SYSTEM: WHERE DESING CONDITIONS OPENING ADDITIONS OPENINGS, AND SPECIAL DRIVINGS ADDITIONS OPENING ADDITIONS OPENING ADDITIONS AND SPECIAL DRIVINGS ADDITIONS OPENING ADDITIONS ADDITICANA ADDITIONS ADDITICANA ADDITIONS ADDITIONS ADDITI	A. FIRMEN AND INSTALL ALL BRANCH DRIGHT PAREBOUNDS AS HEREINAFTER SPECIFIED AND AS SHOWN ON THE DRIVINGS. PAREBOUNDS SIMULTOR THE DRIVING WITH THE TREMAL WARRENT AND CONTACT DREAKINGS.		
	8 CHURT BREVES SHUL BE RETER MANUAL IN THE THAN STORED BANG CHART MANUAL AND SHUL BE SERVICE-O ON EXTEMPERTOR PROVIDED INVERTIGATION FOR CHART OF THE THAN STORED BANG CHART MANUAL STOLET IN THE THAN STOLET AND CHART STOLET AND SHUL BE THE MANUAL OF THE THAN STOLET AND CHART STOLET AND SHUL BE THE SERVICE-O AND SHUL BE THE SERVICE OF THE SERVICE AND SHUL BE THE SERVICE OF THE SERVICE AND SHUL BE THE SERVICE OF THE SERVICE AND SHUL BE SERVICE OF THE SERVICE AND SHUL BE THE SERVICE AND SHUL BE THE SERVICE OF THE SERVICE AND SHUL BE THE SERVICE OF THE SERVICE AND SHUL BE THE SERVICE AND SHUL BE THE SERVICE OF THE SERVICE AND SHUL BE TH	3 SPEDIL LECTRON, DISTORS SHALL BE PROPERTY DONTIES AT ANCIDE RID PALL BRES 4 ALL READER DISTORT FAMIL REMAIN SHALL HAVE REMAINS FRADIUS PLATES AND PRAME & DISTO DISCUSSEY CARD	
 MORTER A DESCRIPTION OF MUNITAL OF STATE OF CHARLEY, MAY, COMPANY, AND AN UNLER, MORTER MUNITAL AND SPIROS AND MULTING DESCRIPTION, NEL CONTRACTOR STALE OF RESOLUCIES (IN PROBING AND AND STATEMAL AND SPIROS STATEMANT IN EXECUTIO DESCRIPTION AND OF DIMANEL ANQUE IN INFORMATION DESCRIPTION AND OPENALE DISTURIE AS RELIEVED IN THE OWNER AND DISOLET. 	HAMMEN MIT LOSS IL LISED FOR DEE MEN 75°C MEE. C. DORR SMLL HILE A PLASE CONSED DECEMPT FRAME WITH A THEO BEHTFEARON ONE OR ALL DECUT HID PANE, MANDERS FOR BINNEY MOUT PANELDARIE DECEMPT FRAME WITH A THEO BEHTFEARON ONE OR ALL DECUT. HID PANE, MANDERS FOR	4 ALL BRINDE DECENT FAND, BOHDET SMLL HERE EDERTERING DRATHED PRATEC HEREFARTS, ALSO, FROMER & THED DRECENT CHIE FOR LON GRANDE CREAT FANDERHOU. HE CARD & D & PLACED ON HER DRETER SEC OF THE FANDERHOU COOR BOHDE A CLEH FANTS TRAD. THE CARD SHILL REPORT LONG CREAT OF RAMED, CLEM, AND CORTAN.	
THE OWNER AND ENGINEER.	BRINKEN CHRIST FANNEISIGANES © MRISTIE ANNERSA DE FER ALL HANKLBOARDS, ENDERKED MATE LETTERS OM BLACK BACHRONAND INSTALL MARE PLATES OM THE INDA ABOVE DODA	5 N GROEN, DUPPENT SHELL E DUPPED AS DESIDITED ON THE ELECTRICAL DRAMMAS, INMERATES FOR PHYEROLOGIA AND SMITCHEMARDS SHELL RALLER ME PHARE CERSINITIAN, NOLLING AND PHARE OF THE SAME IN THE MARKER SHALL BE THE SHIE AS THE HAVE USED OF LALKERDE SHIFTING, DECOMPACE, AND AS SITTIN INMERIZIES FOR THE MARKE SHALL BE THE SHIE AS THE HAVE USED OF LALKERDE SHIFTING, DECOMPACE, AND AS SITTIN INMERIZIES FOR THE MARKE SHALL BE THE SHIE AS THE SHIE USED.	
	DOOR E ALL WHAT SHALL DE KEARLY ARKINGD AND LACED TODETHER	SALE AS THE ANNE USED ON ALL MOTOR STATTER, DECOMPLETE, AND P.B. STATOM INMEPLATES FOR THAT MADINE. 9. INMEPLATES SHALL BE FORMED TO AS FOLLOWS	
A. COTINE LODGE WEITERLE OF COMPANY WE REPORTED FROM CONFLICT BY THE GARDER BASE NOUS IN THE CARL, THE COTENT LODGE, AND RECORDERING THESE CITEMPA DE REDURED OF ACCOMPANY OF DESCRIPTION OF DESCRIPTION D'AMERICE NOTE, ALL LODGE MUTTINES AN COMPANY FOR THE CARLET RECTULATION OF THE ELECTION, WORK SHALL BE PROVIDED LANDER DE STOTUS OF THESE STOREDUCTION.	E. ALL DEFINIT BELACES USED FOR HARD THE CALLS AND AN INT A MADE	 Invertiles and a productor of a processing Invertiles and a processing of a processing processing of the process	
1.05 SPEDIAL REQUIREMENTS	6. BUS BARS SHALL BE REETINGULAR IN ORDES SECTION CONSTRUCTED OF CAPPER NEUTRIL, AND REDUND BUSES SHALL BE FALL SEE.	2. CAPTAL LETTERS SHALL BE LEED.	
A THE DRIVENES HOUCHE CONTROL ARTHOUGHENT OF DRIVING WORKER, LOCATORS OF WORKE OWNER/LEPS WITH DESCHAREDS, AMERIDANDS, CONVOLT BUILTING, AND OTHER WORK, MYCHARING WORK WY THE DRIVENES (MARKING) MARKETS, MCHINING OR BUILZING LUCTIONS LUCTIONS WILL NOT A PROVIDE WHITE APPROVE WITH APPROXIMAL OF THE UNDERS.	2.14 INTERDE LIGHTIG FICTURES N/A 2.15 INTERDE LIGHTIG FICTURES N/A	3 . Namely, res shall be freedow with cashing-plated self-latence fig. 6 schemes $1/4^{\prime}$ long	
1.06.309#77423	2.18 ENDERN ENHANG HINDRES N/N 2.13 LOW VOLTARE SMICHBER N/N	4. THE MOMBIN SEE OF ALL NAME PLATES AND LETTERING SHALL BE 3/4" HIGH BY 3" LONG. WITH 1/4" LETTERS.	
A. AFTER ANADO OF THE CONTRACT AND BETWEE ANY WATERIAS ARE DELINERED TO THE JOB STE, A COMPLET USF OF ALL WATERIAS PROPOSED TO BE FROMMED AND INSTALLED UNDER THIS SECTION WAST BE PROVIDED.	2.13 GRUIT AND WORD DISCOMPECTS	Too were an another an another an analysis of an and a second second second second second second second second	
4. State to the description interview of the net relations of the content transmission interview interview of the content transmission interview of the content transmission interview of the content transmission interview of the content of the	A DISDANETT (SHETH) SHITKES SHUL BE PASED, HEAV DUTY THE SHITKES METHIC MEM SPECIFICATIONS, SHITKES SHUL BE PROMOED WITH RESERVENT THE RUGS. PROMOE SHITKES WITH BE MARKED OF PALES, HE VOLTAGE, CARRENT AND INDEX AS	A. ככב או שהאם אפרטורים האפרטיד היו אינה אם אולטוני ולא כול באראר האפרטיד האפרטיד או אינה אפרטיד אינו אינה א אמו האפרטיד אינטאני להגוונים האפרטיד אינטאני אינט אינט אינט אינט אינט אינט א	
	A. DOZANCT SKYTEJ STOTES SHULL BY NOZI, MAN JUT: THE SINDER KETNE KAN STOTENTSKI SKYTES SHUL BY MEKED WEI RECEINT FRE FRE EDE SOTE STOTES WITH BY AMARE OF STOTES KETNE KAN STOTENTSKI SKYTES SHULL BY MEKE MELATER INVERT STOTENUT PRIMAL DUCH AND, MAN STOTEN STOTEN WITH STOTEN THERE AND INCOMENT IN STOTE STOTES TOTENUT PRIMAL DUCH AND, MAN STOTEN THE MEMORY AND STOTEN WITHOUT MEMORY AND INCOMENT IN STOTE STOTES STOTES SHULL BY AND STOTES AND STOTES AND AND STOTES STOTES SHULL BY MEMORY IN STOTES STOTES STOTES SHULL BY AND STOTES AND STOTES AND STOTES STOTES SHULL BY MEMORY IN STOTES STOTES SHULL BY AND STOTES AND STOTES AND STOTES AND STOTES AND AND STOTES AND STOTES STOTES SHULL BY AND STOTES AND STOTES AND STOTES AND AND STOTES AND STOTES STOTES STOTES AND STOTES AND STOTES AND STOTES AND AND STOTES AND STOTES STOTES STOTES AND STOTES AND STOTES AND AND STOTES AND AND AND AND AND AND STOTES STOTES AND	LIPPAC TO THE OWER BETORE RELAXING THUL RECEPTINGZ 310 DENNING OF FOOMHUNG, MUTTHUL, MID PROVIDES	
1.07 STANDARS AND WATCHAS	B SWITCHES SHILL BE HEAR JR (RAW ROHT ENCLOSINE) WHERE HORD BE RUTDOORS WEATHERMOOT.	STO GLAMME OF LEGIMENT, MILENEL, ME PREMIZE A. STE SHUL DE LETI BOOM GLAM WTER COMPLETION OF BORE EVEN BAY, LYON, COMPLETION OF THE MORE, LEVE THE PREMIZES GLAM OF ALL OFF THE DEBTS.	
A. AL BATENALS SHALL CONDEN WITH THE CURRENT PAPERSHIE INCUSTRY STANDARD, INCA (PATIONAL DECTINCA MANAGEMENTS ASSOCIATION), AND ADMINISTING STANDARDS INSTITUTIO, POR INDUCT MORE CIDENT ASSOCIATION, AND ADMINISTICATION OF A OF DESTINATION OF AND ADMINISTING AND ADMINISTICATION OF ADMINISTRY ADMIN	C. PROMOE NAMEFLATE. MODATING EQUIPMENT SCREED. ALL GENERAL SIMP SWITCHES OPERATING MOTOR LOADS SHALL BE HORSEPORER RATED OR BE MATED AT LEAST 1558 OF THE FLAL LOAD COMPLEX.		
 UNLESS OPERAGE MODULES, ALL MARENALS SHAL BE UNDERWEITERS LABORATORES. LISTED AND LABLES, OR GENTRED BY A MATOMALY RECORDED INSTANC LABORATORY. 	2.14 TRANSFORMERS N/A	 ALL EXEMPENT AND MITCHL COMPLETE WITH THE PROJECT SHALL IE INSTALLES COMPLETE, INSTALLES CARELLAID ALL RESOLD REMOVED FORM ROLES SUPPLIES. DITTION SUPPLIES OF ALL INITIAL AND COMPLETE SHALL BE DEFINED AND BULIERED IN A PERIES, LIMILIONED COMPLEX. 	
	2.15 ELEDITOR, CORRECTORS	311 HHREND OF WHE AND CABLE	
C. AND ALL THE CALL AND ALL ADDRESS AND ALL THE THE ALL ADDRESS AND ADDRESS AND ALL ADDRESS AND	A. UNLESS DIFERNMER HOULD, ALL WINN FOR MODING, SUMITING, CONTINUES, AND FORMATIN' DUALL BE MEDIATED BY THE ELECTIONAL CONTINUEDRE WHERE MODING FOR ACCOUNTING. ELECTION ARE FORMEDED BY OTHER DUALSHOE, WINNE SHALL BE THE RESPONDENTY OF THE ELECTIONER. CONTINUENCE IN DUTY HIRING WHER MERICIPAL WINN BE CONTINUE.	A. HANDLE WAS AND CABLE SS AS TO AIROD DAWARE TO COMPACIENTS AND THRE EVERY PRECAUTION TO AIROD SHARP BENGING OF SCIENCE OF THE CABLE SHALL NOT BE LAD HAR DAVIGED LIVEN THE GRADUD.	
1.08 DELIVERY AND STORAGE OF WATERALS	8 CONNECTION AND CONTRAL ANDRONG FOR ALL INCONTRAL AND CONTRAL EQUIPMENT SHALL BE FORMARIES ANDIR OTHER DISEASE, AND BE APPRINGED TO EXAMPLE CONCENTER IN THE ELECTRICAL CONTRACTOR.	 The contractor shall be required to result and result at the day direct all are and dalle damaged due to writere involved, not shall pay for the new writ or care. 	
A. THE CONTRACTOR SHALL INESTRATE LARK STRACT IN THE BRAISHIE DHIGHEN MADER LOOMINENT MUST FASS TO HEARI TO FINAL LOOP ROVES. IF NESTRAND, THE INMANDELINENT SHALL AL RECENTED TO SHIP HIS MATERIAL IN SECTIOR, SIZE TO FERMIT HASTING THREADY SUCH PERSTRACT, MESS IN THE SECOND.	APPROAD BY WE UNKER FOR LAMPECTOR BY WE LECTION, CONVERTOR. 2.18 SUPPORTING GENESS	J 12 JEETING AND INSPECTIONS	
8. THE CONTINUEND SHULL RETAIN IN HIS POSIZISION AND SHULL BE RESPONDED FOR ALL PREVALE AND DETAIDABLE PARTS OF PORTIONE OF RESTULTABLE SHOL AS PAGES, KEY LODGS, ADAPTERS, BLODGN CLIPE, AND NEETHS UNIT, PAUL COMPLETING OF BOOKS SHULL BE CONTENED TO BE OWNER PARTS ADAPTED FOR HOME.	A AL EXAMPLET COMMENTS SHILL BE SUPPORTE, AND AND AND AND AN AN AN AN AN THE WAST SIMMANT COOLS AND RESUMEMENTS COMPLY WITH OWPER 23 OF THE LATEST COC (CALEFORM BACARD COOL).	A. THE CONTRACTOR SHALL OBTING AND THY FOR ALL RECORDED PERMITS AND ARRIVALE ALL RECORDED INSPECTIONS FOR THE DECUTION OF THE MODEL UNDER THIS CONTRACT.	
skul je oejnered to tre ormer uran comfletan af tre kark. Prist 2 products	REUREURINS, COMPLY WIN DWPTER 23 OF THE LATEST COC (CALFORNA BUILDING COUL). PIRT 3 DECUTOW	R. THE ODVIRICING BUILL REPLACE ALL DAMAGED OF DEFERTIVE EDUPMENT OF MORE	
2.0 EXMINENT AND INVERTIGS	301 MENDINGNY AND COMPLETION OF INSTALLATION	C ALL CREATE SHILL BE TESTED FOR CONTINUTY AND CREAT NITEMATY BY THE CONTINUED. ADJASTIMONTS SHILL BE WASE FOR CREATES INTO CREATES AND ADDA STATE OF CREATES.	
A. AL WHERE'S REVENDED AND MEDICID UNDER THE CONTRACT SHALL BE MER FREE. FROM KOFEETS, MAD SHALL BE DURANNEED FOR A PRIME OF ONE ()) KAN THAN MAT OF ACCEPTING OF MER KANS, SANCE AND THALE, RELEARD NAMEN AND ALS TO SETTOTE, MERICES AN REALT ROMANNY, ME CONTRACTOR SUIL LINKIN AL, MERICESTM MERICUM, AND ALSON TO COMPET THE DURANT, MERICES THAL MERICENCING, MERICENCE AND ALSON ALSON MERICES, AND ALSON TO ALSON TO THE MERICES AND ALSON TO ALSO SUBJECTIVE AND ALSON ALSON MERICENCE AND THE ALSON TO ALSON SHALL BE CONTRACT AND ALSO TO ALSO SUBJECTIVE AND ALSON ALSON ALSON ALSON ALSON ALSON ALSON ALSON ALSON ALSON SHALL BE CONTRACT AND ALSO ALSO ALSON	A. NORDANSOF NO NEXT APPENDIXE SUIL DE AS APARTINT AS THE LISERCU, AND NEXTANDET, DITUDIET, APPENDIXE, SUIL DE ASTRONOMICO DE DITUDIE MURRALS SUIL DE NETACIS OF REVIED PORTO TO TANI, MORMETI NON PRESENT, AND SUCCENCY PERIAMO TO ETHER MURRALSOF DE MURRELS TANDA OF DE ASTRONOMICO SUIL DE ORDECASION MORTO ADDRELSOFT DE DAMAR.		
DEFECTIVE MALERIALS OF FINALTY MEDINANCHY, THE CONTRACTOR SINLL FUNKHA ALL ARESSANY MATERNALS AND LABOR TO CORRECT THE TROAME WHINDIT ANY COST TO THE DAMER, ANY DIFFECTIVE MATERNAL OF METHOD WERHINASHY MATERNALS AND LABOR TO CORRECT MALL AND CORRECTOR TO THE STANDARCHY TO THE COMPANY.		0. The conflicture pulse investments and perform any laborate stats research in the antident values destinction conflictions should state and a state of the performance of the work resulting rate hade rests for dash of the confliction rates should be and by the confliction.	
 ALL MADE EDUPMENT COMPONENTS SHALL HIVE THE INVAFICITIEST'S NIME, ADDRESS, IEDE, NUMBER, AND SERIA, NUMBER PERMINIPATY ATTACHED IN A CONVENIOUS IMMER. 	5 The CORTRESS SHE WARTER OF 46 ST 61 ST 67 THE WARDER DRIVENES BETS SHELL OF UNLED DATA AN ATTACH OF BOTH ADDRIVENES DRIVE WARTER OF RE KIRK 25 ST 67 TREMEDICE CONTRESS THE SHELL OF DRIVEN DRIVE RE SHELL CORRECTOR WAR ALL OWNERS AS ADDRESS OF BE RECORD ST 67 TREMS SHELL OF MCOMPARIES THEORY WITH RES DR N A ROLL LIGREL OWNERSTANDER: AND INTEGRAMM. WARRES	L. BE CONTRECTOR SHULL FURNISH DIE GAMER CONTROLTES OF IMPECTION AND APPROVAL BY THE ELECTRON. IMPECTION AUTOMATY ON ALL NORY COMPLETE AS RECOMED.	
ATTACAS A ADACTUDADA MANAGER.		 TILE IN HEARTS THE CONFERENCE OF ALL INFLORME CONTROLIES OF INSTALLATION AND CONTROLIES OF ACCEPTINGE FOR USHING SYSTEMS. INS SHALL INSIDE INCOM AND CONTROL SYSTEMS. 	
A. MOMER ANCONTS AS RADARD ON THE DAMAGES AND AS IMPORT STOTED. COMPARE SAME OF RADARD STOT. (THEN WHIL) CALINGUES, RESPECT WERE LEAVED. THEME "SMI", "IMP WHILL, FLOWER STOL, CALINGUES, LOUGE-STOL, REDUCES STOL, CALINGUES, LOUGE STOL, CALINGUES, CALINGUES, STOL, CALINGUES, LOUGE STOL, CALINGUES, STOL, CALINGUES, LOUGES, STOL, CALINGUES, STOL, CALINGUES, STOL, CALINGUES, STOL, CALINGUES, CALINGUES, STOL, CALINGUES, CALINGUES, STOL,	C AL COMPART NO WEDRIG COMPETED WIN THE PROJECT SHELLE WETRICG COMPLET, THERADARY COMPET, AND ALL RESIDE INSULA THEM ROLE SUPPLIES. EXTENDE SUPPLIES OF ALL MITTING. AND EXAMINENT SHELL & CLIMES AND RELIDENTS. INSULATION ROLE SUPPLIES.	G CONTRACT ORMANIS AND SPECTRUMONS, GREEN, PROMISION OF THE CONTRACT, NOLISING GREENE, AND SUPPLEASING COMPARIANT, CONTRACT, ELECTRICA, PROMISING AND INCOME-1 SECRETURIN SECTION APPLY TO MAKE OF THIS SECTION.	
GRAING BLACH, HLIMMINN CONDURT, OF SCHEIRLE 40 PHC. 8. ALL DIPTY CONDURTS (CD.) SYNLL BE SCHEIRLE 40 PHC UNLESS DIFERRIEE NOCKTED OM THE DANIMIE.	a. UPON COMPLETION OF THE INSTALLATION AND AS A CONDITION OF ITS ACCEPTINGE FURNING ONE COPY OF THE FINAL INSPECTION CONTINUES. TO THE COMPLET.	τατιπου, ποιουσιο για αποιατή γιατοποιού και οποίο γιατι το ακό το ποι ατιπο. Η ασημετά με παιέ για παρικά εξάποιατά () οι κατιμέποι (καί) και ευνησισεξό) οι κατατηπός (καις) το σε εσημετά Της σοπτίας σοσιμότα:	
 MEDE ORIGAT ORSSES IN OPHIGEN JOHN, PHONE MOTION TITLES MICH ALLOW DELECTION CONVELIT TO THEE THE MOMENT ALLOW BY THE USER. 	1.02 PREFAMILION COORDINITION	INE CONTRACT DOCUMENTS. 1. RESPONDENT/RS OF INSTALLANC CONTRACTORS	
2.01 COMUCTINS	A. THE CONTRACTOR SHALL CODEDNATE THIS WORK WITH ALL OPER CONTRACTORS FLOWASHING LADOR, MATERIALS AND WORK, SO THAT THE WORK AS MALL SHALL BE LATURING AND COMPLETED WATCHLY OR DOLLAR.	1 Norman Statements (Construction) A Galaxies construction (Inc) 4 Galaxies (Inc) (Construction) and the contention retronant (Inf According to Construction of the Title 3 Galaxies (Inc) of According on Edition of the Sale of Outrooms of Its Science Today in Conduct Load According to According to Contract one Edition of the Sale of Outrooms of Its Science Today in Conduct Load According to According to According to According to the Sale of Outrooms of Its Science Today in Conduct Load	
A. IPROVER A COMPLETE SYSTEM OF CONJUCTIONS IN PACENAL SYSTEMS AS SHOWN ON THE DRAWNOS AND THOSE MEETING.			
 LIOHTING AND POWER CONDUCTORS SHALL BE COPPER, 600 HOL, THE IMME/INNI, MJ. 12 MEMANA UNLESS OTHERINGE HOTEL. CONTING CONDUCTORS SHALL BE 6000, THE IMME/INNI, MJ.14 MEMANA SHE UNLESS OTHERINGE HOTEL. 	8. COMME TRE DAMANGE AND STREAMED AND STREAME THE BOW TO BE FREEMED BY THE DISTRECK, LEGENHAUL AND DREY TRADEL PARENE TRE FOR AN AND AND STREAMED AND LOWARD NEEDED AND TAMAN NEEDED TO TAMAN THE STREAM TO AND AND AND COMPLEXE MADE STREAM AND AND THE DESIGN AND AND AND AND AND AND AND AND AND AN	A. ELECTRON, CONVOLUTIO BLY A. ELECTRON, CONVOLUTIOR AND POSTORMANCE OF ALL ELECTRON, SERVICES INTORES. b. COMPLEX THEL. IN CONTROL ORD OF CONSTILLATION AND MAINTAINEEST PHIL-START CHECKLISTS PHOR TO SCHEDULING STATUTION PROCESSING OF CONSTILLATION AND MAINTAINEEST PHILOSOPHICS PHOL. PLANT STATUTION PROCESSING OF CONSTILLATION AND MAINTAINEEST PHOLOSOPHICS PHOLOSOPHICS STATUTION PROCESSING OF CONSTILLATION AND PROCESSING.	
2.04 FITTING	C. FORGAN ALL NOVE IN A MANNER MADY INL NOT CAUSE UNNECESSARY INCOMPLMENCE OF DANAER TO THE OCCUPANTS, NOR INTOPODE WITH THE ACTIVITIES IN THE BARDING.	I. RETAIN CERTIFICATE(S) OF INSTALLATION IN A 3-RING BINDER IN AN ORGANIZED FASHION. BINDER IS TO REMAIN ON THE VOB STE	
A CONVECTOR CONFLICT, COCHUR, INSTITUS AND CAPS VIED WITH MODI CONDUCT SHULL BE STEED, IMPORED AND DEVINATED INSTITUS SHULL BE INSTALLED.	 The continuous symple considered and schedule each paper methy with owner, and symple at least two werks while or previous symplection and work to be accordingned. 	4. Well controlling in mountain whether one became approximate the killing of the second s	
B. ENT FITTING, CONNECTORS AND COLUMNS SHALL BE STATE, JUNE, OF CHAINSM PLATES, COMPRESSION THY, WHY INSULATED THREAT.	NOTICE OF PREMIUMENTIAN AND KONCET TO BE ACCOMPLISED. 104 CORE CUTTING, ORLING, AND FAITURING	н сомнет Lanesme of all checking with connecting Equivalent. • сомнете не синтенству от ассотинсе нет не сомныст оосыманте.	
 R.Doble Steel conduct connecting stall be Inst-In-Type with wislaned therat. The finite shall be died or diabate plating. a. Eur conduct fittings shall be the compression type, set societ fittings shall not be used. 	A. NO HALS WE BE ALLOWD IN MY STRUCTURE WEINTED WITTON MYRDAL OF THE MEDITED B. STRUCTURE DIRECT.	L RE COMMUN INSTALLAR RE LIGHTING SISTING MIST BE IN AUTORIZIO LIGHTING CONTRES ACCOMMINE ISST EMPLOYER CONTRED BY A LICHTING CONTRES ACCOMPANYE TEST TECHNICH CONTREAL REPORTER OF MELLIER IN TIME AD THE COST OF TETANING AND DIFFERENT A LICHTINGER MEI SI AN AUTOROTORI INOTING DI CONTRES I TEST AUTORISTICE TO CONTRET TO CONTRACT DI CONTRALIS	
2.05 ANCTON AND PALL BORS	AB BERK UNINCTOR	RSING. 8. ALL HILARD ADDITING ISSNE WAS IN COMPLIED BY A LIGHTING CONTRAS ADDITING. ISST REMAINING UNLOTED BY THE	
A TOR WERKOR DIT LOCATIONS, BURES SHALL BE GRUMMED DHE-MICE DAMA STELL, MODINAL THE WITH REMOVALE, WHOTHE SCHEW SCHED LOLERS.	A. WORDINSON IS TO BE NEXT, BY EVENNESS WORNERS WITH ACCOUNTE SPERIASING, AND IN LINE WITH NORMAL, INDUSTRY WORK PROJECTS.	TEN. 1. A COMPARIANCE TIME AND A CONTROL # A LONG AND A CONTROL ACCIVICAL DE TRUMMA MANDA & M	
B. FOR EVERYON WET LOCATIONS, BONES SHALL DE NEMA DE OR NEMA 4 RATEL, GASTET MACHINE SORGY SECHED COURS. ANADERIA DALLARTES DALLA EL COMPARTE EVERTIDANE DEL DES NEMA LE LEMERODALE DE MATELLATEN LOCATION. DES NELLASE DED NET.	PRICINZAL B ININTAN WERTING GEARWARE ARDINO ELECTRON, EDURMENT, IN ACCORDANCE WITH DORE REQUIREMENTS AS A INNINAN	PROJECT COMPLETION. THE DATINGSE IS ANALYZEE TO THE PROJ. 6 SUCCESSFLE COMPLETION OF THE RECOMED ACCEPTINGE TESTS IS THE RESPONSIBILITY OF THE INSTRUCTING CONTRACTINE. ANY COSTS.	
C MORDAD PULIDES SHUL DE COMPETE LECTRON, PUL DIX WHY LD APPROPRIE FOR MOTALATION LOCATION. SEE PULIDE FOR MET RECORDERVIS.	C. WHERE LISTING RITURES AND OTHER ELECTRICLE TERES ARE SHOWN IN CONJUCT WITH LOCARIAS OF STRUCTURAL MEMORIES AND REDAVANCE OF OTHER COMPARIE, DAMAGE AND RETALL ALL RECORDS SUPPORTS AND READS TO LEAR THE ENDINANCE.	ADDIGARDU WAY WEAWLANDAS REZISSAWY TO OBIAN COMPLANCE, AND RE-RISTING OF SYSTAMS SHALL WE NOLADOD IN THE BASE BO OF THE PROJECT.	
 ALL BODS SHALL BE SUD FOR THE MANDER IND SUDS OF CONJUCTORS AND COMPARY INCOME THE BOX AND COMPARY WITH PLASTIC MINIS WITH INCOMENT. 2.06 JULY BODS 	RESINGER, DE OURE COMPARE, LARGER MO REVIL, RE INCOMENTA DE MINE TO CLAV DE COMPARADON. 8. GENY LOCARD OF EXCOMPANY, LARGE SOUL, ELEMENT, ALO ESCA LORDE REVIE MONTANO. RESURT NO CUTT PALEDON EN CAN DE MINE TO ANTA COMPANY, EN COMPANY, AND		
A. YOR PRIMESS BOOSTS SHILL BE DRIVANCEL ONE-PESS DAMAN STELL, NODODAT THE LOWPED WHI 1/0" TOTALE STEDS AND PLASEE BRUS MARK RECORDS AND MALE DRIVALS WHILL SHITCHS, OF OTHER BENESS, DURIT BRUSS SHILL DE - BRUMMESS (MC-PESS DAMAN STELL, NODODAT	E. ALL CONCUTE TO BE ONLY CONCUES OF DEPARTMENT NOTION, ALL CONDUCTS SHALL BE ROUTED DEFINED BY CEEPING SHALLS, NO CONCUTS SHALL BE FORMATION IN CONCUTE SHALL HOUSEN INTELLS UNLESS SPECIFICALLY TO INSCRIME TO ANY SHALL BE FRAN SO AS NOT TO INTERVIE WITH OPER FORMERS OF LODIENT.		
8. FOR COMMENDED COLLES, NUL SHICKES, OR CHER DENES, GUILET BORS SHILL DE GRUNNESS DRE-HEIZ DRIVER STELL, DODOLOF THE 47077-1/2" MINIMUM.	E. WHERE ALLOWED, DATORED CONDUCT REAS DAVID, DE INSTALLED PARALLE OF FORMORICA.AF TO WALLS, STRUCTURAL WERKBES, OR MERESENDA OF VERTICAL RUNGS AND SERVISS.		
C. FOR LIGENTING WEINE STIMUND BORTS WE NOT SUTHEL, SPECINE BORTS SWEL & DESIGNED TO ITS SPINT OF WEIT OTHER REQUESTIONTS AND SUBMETED FOR IMPROVE.	A LI CECTERE COMMENT AND A LINE ALTHOUGH ALCHIS ANSING PRACH PRE AND DEMOG AND CHEE THIS MULT AND ANIMOLOGY AND A REVENT TO PREVENT OF SHOLD OF RES, DARKS, AND DESISS SEE A LI SETU AN AMPRICATION FROM MURINE, CARD D ANNA D A HALL D A FROM TO A SHOLD OF RES, DARKS, AND DESISS SEE A LI SETU AND AMPRICATION FROM THE ADMIN D ANNA D A HALL D A FROM TO A SHOLD OF RES, DARKS, AND DESISS SEE A LI SETU AND AMPRICATION FROM THE CARD D ANNA D A HALL D A FROM TO A SHOLD OF RES. DARKS, AND DESISS SEE A LI SETU AND AMPRICATION FROM THE CARD D ANNA D A HALL D A FROM TO AND D AND AMPRICATION FROM THE AND AMPRICATION FROM THE AND AMPRICATION FROM THE ADMINISTRATION FROM THE ADMINISTRATION FROM THE ADMINISTRATION AND AMPRICATION FROM THE ADMINISTRATION FROM THE ADMINISTRATION FROM THE ADMINISTRATION AMPRICATION FROM THE ADMINISTRATION FROM THE ADMINISTRATION FROM THE ADMINISTRATION FROM THE ADMINISTRATION AMPRICATION FROM THE ADMINISTRATION FROM THE ADMINISTRATION FROM THE ADMINISTRATION AMPRICATION FROM THE ADMINISTRATION FROM THE ADMIN		
2.05 SWTCHES N/A 2.08 WECKPONTLS			
	n. Unless matten permession is gravited by the abovect, no mattend, shall be admited on the extender while or provident for or The balance		
A UNITY RESPECTIVE WALL BESTERVISE OF UNITY BESTERVISE OF UNITY BESTERVISE RESPECTIVE			
8. Other reconcers our a properties and an and a second and a secon	 AL RETAINS LICENCE SERVICE SERVICES WILL BE SERVICE WILL A LICENEL, LIGHT- HOIT CONDUT WILL APPROPRIATE SLACE AND SHELL NOT OTHER WINN SHELL BE RETAILED IN CONDUCT. AL PORE WINN SHELL BE RETAILED IN CONDUCT. 		
	2 AL PORER WING SHALL BE PETIALED IN CONCULT. IN TELEPHONE WIRS SHALL BE PETIALED IN CONCULT OR MOUNTION IN LEDING SPACES MEMOUT CONCULT UNLESS. OTHERWSE NOTED		
ZOR GENCE PLACES 1. MONKE PLACES FOR ALL SURFICES, RESERVALES, JOICTION BOIES, TELEMONE AND OTHER OUTLETS	L. ALL WRES FOR ALL SISTEMS SHALL BE CONTINUOUS FOOD SWITCH TO EXTINUES BEFORE COLLET. NO ADVITS SHALL BE WAVE EXCEPT IN FULL, LANCING OR DULLY TORES ON IN HAVE DE SWITCHED DUTTIES.		
 PROVIDE HARDS FOR ALL SWICKES, RELEVINEEDS, JOHENNA BUIES, PLEIMENE AND DIREN WORLEIS. PROVIDE ENDAVIED OR EIDHED PLATES FOR ALL LOOK SWICHES, PLEIT SWICHES, SWICHES FORM WICH EQUIVERT OR ORDAT CONTROLLED. 	in fall, lanctan an autli baes, an in finne de switsbord auturs. In: All Recommand, contro, and switch noondhig hearts shill be coordinated with adorectanal, illivitidhs from to		



INDEX TWICE

ELECTRICAL SPECIFICATIONS

DESIGN WEST ENGINEERING

Figure B-2: Los Angeles Department of Building and Safety Application for Building Permit and Certificate of Occupancy

9400 S La Tijera Blvd

	LA (<u>D</u>			k X19LA		9044 - 10000 - 15652 Printed: 12/20/19 10:23 AM
	LA Department of Bu		1140 5741	211	Safety	Issued On:	12/20/2019
	LA 104	4172449 12/20/2019	10:23:22	AM		Last Status:	Issued
	Htg/REY PMT cota DEV CENTE SYSTEMS	R SURCH	DEVT	490. 00 *2. 70		Status Date:	12/20/2019
	FEE HTG/REF PMT COb4 HTG/BDF PMT cow:	\$5.40	\$0. 00	0.00	GO IL 60	680	
		sub Total:		\$98.10			
	Permit # : 190441 Reoe±pt # ; 0104						(714)256- 2136
L.FSCRIPTIONOF WORK INSTALL 2 EXHAUST FANS I	N OARAGE						
COUNCW PISTRJCT: I I							
9. PPLICATIONPROCESSING INFORMATIO By: OK for Cashier: Nicole Lt		Date: 12/20/2	2019				
NOTICE. The work included in this permit sh dwelling units or guest rooms, That n of Occupancy. In the event that any additional information has been capt restrictions. Nevertheless, the inform the Health and Safety Code of the St	number is established by a box (i.e. I- 10) is filled to tured electronically and co nation printed exceeds that	Building Permit or a Ce o its capacity, it is possi ould not be printed due t	ertificate ible that to space				




Permit #: Receipt #:

C20 967408 (714)256- 2136 EMVReaeipt Section) S La Tijera Blvd		(92821	CLASS <u>LIC</u>	ENSE # PHONE	
EMVReacipt Section 'Cashier's Use Only V Application Label: CAPITAL ONE VISA TC: PD861229DD943547 'na: 0080000000000000000000000000000000000	-	Reference No: 14106			C20 96	· · · ·	
Application Label: CAPITAL ONE VISA TC: FD861229DD43537 /va: 0000000001 HVAC Apartment Express Permit No Plan Check LPROPERTY OWNER FUE BETMAY VILLAGE VI <u>APPLEANT</u> WILLIAM BEESON - LTRANTINGEMATION MILLIAM BEESON - MILLIAM BEESON - M	B	MVReaeipt Section					
HVAC ADD ADD ADD ADD ADD ADD ADD ADD ADD A					Cashier's Use Onl	ly	W/O 9441
Express Permit No Plan Check			0080008000				
No Plan Check L.PROPERTY OWNER FGG BETHANY VILAGE VI APPLEANT WEILLIAM BEESON - J.TEMATIBORMATEX (C) ENETECH INCO (C) ENETES URCH SENSING BOMATICH.**Ima Chesk (C) INTER SURCH SENSING DEVENTION OF VOISS (C) INTER SURCH SENSING DEVENTION OF VOISS (C) INTER SURCH SENSING DEVENTION OF VOISS 00.00 DEV SERV (C) CENTER SURCH SENSING DEVENTION OF VOISS 00.00 DEV SERV (C) ENTER SURCH SENSING DEVENTION OF VOISS 00.00 DEV SERV (C) INTER SURCH SENSING DEVENTION OF VOISS 00.00 DEV SERV (C) INTER SURCH SENSING DEVENTION OF VOISS 00.00 DEV SERV (C) INTER SURCH SENSING DEVENTION (C) INTER SURCH S	partment						
L PROPERTY OWNER L PROPERTY OWNER POR BETLANY VILLAGE VI <u>APPLCANT</u> WUEUMATIDD WILLIJAM BEESON - LIENNYLINGEMATIDN (C) ENETECH INCO C)	xpress Permit						
I_PROPERTY OWNER INSTALL 2 EXHAUST FANS IN GARAGE UNIT LIAM BEESON - INSTALL 2 EXHAUST FANS IN GARAGE I_PROPERTY OWNER INSTALL 2 EXHAUST FANS IN GARAGE III I I III I III I III I III III III III IIII IIII IIIIIII	o Plan Check	1					
FOR BETHANY VILLAGE VI APPLICANT. WIELLIAM DEESON - 3. TENANT INFORMATION (C) ENETECH INCO BAPTICATION COMMERTS Structural plan check is requised by a building weight offhe old y a building weight officiate of Occupancy. In the event that any box (i.e. 1-10) is filled to its capacity, it is capacity, it is capacity, it is space settictions. Nevertheless, the information printed exceeds that required by Section 19825 of the Health and Safety Code ofthe State of California. ITUALIZEN PMT COMMENT Systems DEVT FER ITUALIZEN PMT COMMENT Systems DEVT FE			6. DESCRIPTION OF WORK				
SUBJECTION ORderingender SUBJECTION ORDERATION SUBJECTION ORDERATION SUBJECTION ORDERATION CC) ENETECH INCO SUBJECTION ORDERATION SUBJECTION ORDERATION ORDERATION SUBJECTION ORDERATION SUBJECTION ORDERATION ORDERATI			INSTALL 2 EXHAUST F	ANS IN GARA	GE		
WILLIAM BEESON - LIENANT INFORMATION INFORMATION <td>· · · · · · · · · · · · · · · · · · ·</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td>	· · · · · · · · · · · · · · · · · · ·						
3_TENANTINKORMATION SATELICATION COMMENTS (C) ENETECH INCO Image: Structural plan check is required by a building weight ofthe old building weight ofthe old building weight ofthe old center structures 2/20/2019 STICE: 11 Image: Structural plan check is required by a building weight ofthe old building weight ofthe old center structures Date: 2/20/2019 NOTICE: The work included in this permit shall not be construed as establishing the legal number of dwelling units or guest rooms. That number is establishing the legal number of dwelling units or guest rooms. That number is establishing the legal number of dwelling units or guest rooms. That number is establishing the legal number of dwelling units or guest rooms. That number is establishing the legal number of dwelling units or guest rooms. That number is establishing the legal number of dwelling units or guest rooms. The worth that any box (i.e. 1-10) is filled to its capacity, it is possible that any box (i.e. 1-10) is filled to its capacity, it is considered by SYSTEMS DEVT FEE HTG/REF PMT COMM. HTG/REF PME COMMENT For inspection requests, call toll-free (888) LA4BUILD (524-2845), or request inspections via www. ladbs.org. To speak to a Call Center agent, call 311. Outside LA County, call (13) 473-3231. 190441000015652 0104132547 Permit #: Import Codm. 190411 - 10000 Import of dwe							
(C) ENETECH INCO SATELICATION COMMENTS Structural plan check is requi when supported by a building weight ofthe old 2/20/2019109254225AM HTG/REF PMTCOMM\$90.00 DEV SERV CENTER SURCH \$2.70 SYSTEMS DEVT FEE HTG/REF PMT COMM		ŀ]
(C) ENETECH INCO (C) ENETECH			E KLIST ITE				
SAPPLICATION COMMENTS Surctural plan check is requived by a building weight ofthe old 12/20/20 1910*252222AM HTG/REF PMTCOMM\$90.00 DEV SERV CENTER SURCH \$2.75 SYSTEMS DEVT FEE HTG/REF PMT COMM HTG/REF PME COMM HTG/REF PME COMMENT * P 1 9 0 4 4 1 0 0 0 0 1 5 6 5 2 1 N * * P 1 9 0 4 4 1 0 0 0 0 1 5 6 5 2 1 N * * P 1 9 0 4 4 1 0 0 0 0 1 5 6 5 2 1 N *			<u>PISTRICT:</u> I I				
SAPELICATION COMMENTS Structural plan check is requived by a building weight ofthe old 2/20/20 1910*25422AM HTG/REF PMT COMM\$90.00 DEV SERV. CENTER SURCH \$2.70 SYSTEMS DEVT FEE HTG/REF PMT COMM\$90.00 DEV SERV. CENTER SURCH \$2.70 HTG/REF PMT COMM Intel Stattatatatatatatatatatatatatatatatatat		(C) ENETECH INCO		MATION -Plan Check			
SAPPLICATION COMMENTS Structural plan check is requi when supported by a building weight offle old 12/20/2019 1910923423AM HTG/REF PMTCOMM\$90.00 DEV SERV CENTER SURCH \$2.70 SYSTEMS DEVT FEE HTG/REF PMT COMM HTG/REF PMT COMM HTG/REF PMT COMM Image: the state of the st				ole L•aface			
2/20/20 1910725425425AM HTG/REF PMTCOMM\$90.00 DEV SERVI CENTER SURCH \$2.70 SYSTEMS DEVT FEE HTG/REF PMT COMM HTG/REF PMT COMM HTG/REF PMT COMM HTG/REF PME COMM HTG/RE	88						
2/20/20 910725425425AM HTG/REF PMTCOMM\$90.00 DEV SERV CENTER SURCH \$2.70 SYSTEMS DEVT FEE HTG/REF PMT COMM HTG/REF PMT COMM HTG/REF PMT COMM HTG/REF PME COMM HTG/REF	5. APPLICATION COMMENTS					Date:	
2/20/20 910725425425AM HTG/REF PMTCOMM\$90.00 DEV SERV CENTER SURCH \$2.70 SYSTEMS DEVT FEE HTG/REF PMT COMM HTG/REF PMT COMM HTG/REF PMT COMM HTG/REF PME COMM HTG/REF	Structural plan check is requi when supported by a	-					
CENTER SURCH \$2.70 SYSTEMS DEVT FEE HTG/REF PMT COMM HTG/REF PM'E COMM +TG/REF PM'E COMM +TG/REF PM'E COMM +TG/REF PM'E COMM HTG/REF PM'E COMM +TG/REF PM'E			The work included in this per	rmit shall not be	construed as establish	ing the legal number of	
Image: Stratewise beven price Stratewise beven price HTG/REF PMT COMM HTG/REF PMT COMM HTG/REF PMT COMM HTG/REF PMT COMM Image: Stratewise price For inspection requests, call toll-free (888) LA4BUILD (524-2845), or request inspections via www.ladbs.org. To speak to a Call Center agent, call 311. Outside LA County, call (213) 473-3231. Image: Stratewise price \$98.10 Image: Stratewise price \$90.44.1.0000 Image: Stratewise price \$90.41.1.0000 Image: Stratewise price Image: Stratewise price Image: Stratewise price Image: Stratewise price			Certificate of Occupancy. In	the event that ar	ny box (i.e. 1-10) is fill	ed to its capacity, it is	
HTG/REF PM'E COM + P 1 9 0 4 4 1 0 0 0 0 1 5 6 5 2 1 N * * P 1 9 0 4 4 1 0 0 0 0 0 1 5 6 5 2 1 N * \$98.10 190441000015652 0104132547 Permit #: Print #: Print #: Print Code Plan 4: X19LA09099 Furnt Code Plan 4: X19LA09099 Furnt Code Plan 4: X19LA09099 Plan 4: X19LA09099			due to space restrictions. New	ertheless, the in	formation printed exce	eds that required by	
For inspection requests, call toll-free (888) LA4BUILD (524-2845), or request inspections via www.ladbs.org. To speak to a Call Center agent, call 311. Outside LA County, call (213) 473-3231. \$98.10 190441000015652 0104132547 Permit #: Permit #: Plan 4: X19LA09099 Fuert Code			Section 19825 of the Health	and Safety Code	e of the State of Californ	nia.	\$ 0
(213) 473-3231. * P 1 9 0 4 4 1 0 0 0 0 1 5 6 5 2 1 N * \$98.10 190441000015652 0104132547 Permit #: Plan 4: X19LA09099 Fuert Code	ł	TTG/REF PM'E COMM					\$0.
* P 1 9 0 4 4 1 0 0 0 0 1 5 6 5 2 1 N * * P 1 9 0 4 4 1 0 0 0 0 1 5 6 5 2 1 N * 190441000015652 0104132547 Permit #: Permit #: Plan 4: X19LA09099 Fuent Code	I (RAMARAM INT AND A AND AND AND AND AND AND AND AND A	n manafa kinaké mikina mikinak mikinaké mikinaké mikinaké mikinaké mikinaké		to a Call Cente	r agent, call 311. Outsi	de LA County, call	S
190441000015652 0104132547 Permit #: Plan 4: X19LA09099 Fuert Code							То
Permit #: 0104132547 Plan 4: X19LA09099 Funct Code 19041 - 10000	* 7 1 9 0 4 4 1 0 0 0	01505218*	190///1	000015652	\$98.10		
Plan 4: X19LA09099 19041 - 10000			170441		04132547		
Event Code		, F	Permit #:				
Event Code				Plan	1. X191 A09099	Canada	
Event Code; Printed: 05/23/1			A DE LE CONTRACTOR			19041 - 10	000 - 1955
				Event C	ode;	- Printed: 05/	23/19 09:30 A
							· *
Electrical City of Los Angeles Department of Building and Spfety Issued On: 05/23/2019 Apartment 05/23/2019 05/23/2019 05/23/2019		City of Lo	os Angeles Department of I	Building and S	Spfety Issu	ied On: 05/23/2019	
ADDI ICATION EOD ELECTRICAL Lost Status: Logad		APPL	LICATION FOR EI	LECTRICA	AL Last	Status: Issued	
Express Permit	Express Permit						
APPLICATION FOR ELECTRICAL Last Status. Issued o Plan Check PLAN CHECK AND INSPECTION Status Date: 05/23/2019 10001	o Plan Check]	PLAN CHECK AND INS	PECTION	Sta	ntus Date: 05/23/2019	

9400 S La Tijera Blvd

PARTIAL VULLAGE VISTAS INCO PO BOX 87407 ABUULAH AHMED -051708-0719 TOWNATURAL MARKED -051708-0719	PROPE	RTY O PR			
ABUULLAH AHMED (301)768 0719 TENANTIEN CONTINUENDALATEE CONTINUENCE CONTINUEN				- * - * - *	
INTERPRETATION OF CONTROL OF A DECOMPOSATE	ABI	DULLAH AHMED -(951)768-0719		un Jéph	
OVERATIONALITY & REINSTER MARE OVERATION OVERATION OF CONSTRAINTS OVERATION OF CONSTRA	TENA	NTINFORMATION	2		
CONSTRUCTION OF CONTROL OF PRINTY ADVANCED DOMESTIC WATER HEATING SYSTEM CONSTRUCTION OF WORK SECURICAL, FOR PRINTY ADVANCED DOMESTIC WATER HEATING SYSTEM CONSTRUCTION SECURICAL, FOR PRINTY ADVANCED DOMESTIC WATER HEATING SYSTEM CONSTRUCTION SECURICAL, FOR PRINTY ADVANCED DOMESTIC WATER HEATING SYSTEM CONSTRUCTION SECURICAL FOR PRINTY ADVANCED DOMESTIC WATER HEATING SYSTEM CONSTRUCTION SECURICAL FOR PRINTY ADVANCED DOMESTIC WATER HEATING SYSTEM CONSTRUCTION SECURICAL FOR PRINTY ADVANCED DOMESTIC WATER HEATING SYSTEM CONSTRUCTION SECURICAL FOR PRINTY ADVANCED DOMESTIC WATER HEATING SYSTEM CONSTRUCTION SECURICAL FOR PRINTY ADVANCED DOMESTIC WATER HEATING SYSTEM POINT CONSTRUCTION SECURICAL FOR PRINTY ADVANCED DOMESTIC WATER HEATING SYSTEM POINT CONSTRUCTION SECURICAL FORMULA PRINTY ADVANCED DOMESTIC WATER HEATING SYSTEM POINT CONSTRUCTION SECURICAL FORMULA PRINTY ADVANCED DOMESTIC WATER HEATING SYSTEM POINT CONSTRUCTION SECURICAL FORMULA PRINTY ADVANCED DOMESTIC WATER HEATING SYSTEM POINT CONSTRUCTION SECURICAL FORMULA PRINTY ADVANCED DOMESTIC WATER HEATING SYSTEM POINT CONSTRUCTION SECURICAL FORMULA PRINTY ADVANCED DOMESTIC WATER POINT CONSTRUCTION SECURICAL FORMULA PRINTY ADVANCED DOMESTIC WATER HEATING SYSTEM SECURICAL FORMULA PRINTY ADVANCED DOMESTIC WATER HEATING SYSTEM SECURICAL FORMULA PRINTY ADVANCED DOMESTIC WATER HEATING SYSTEM POINT CONSTRUCTION SECURICAL FORMULA PRINTY ADVANCED DOMESTIC WATER POINT CONSTRUCTION SECURICAL FORMULA PRINTY ADVANCED DOMESTIC WATER HEATING SYSTEM POINT CONSTRUCTION SECURATE PRINTY ADVANCED		CONTRACTOR ADDITITION & ENCINEER NAME ADDRESS			
92221 For CRANNER'S Ge Only W/O 94119552 PERCENTION OF WORK ELECTRICAL, FOR PUMPS ADVANCED DOMESTIC WATER HEATING SYSTEM The CRANNER'S Ge Only W/O 94119552 Image: Construction of Work ELECTRICAL, FOR PUMPS ADVANCED DOMESTIC WATER HEATING SYSTEM The CRANNER'S Ge Only W/O 94119552 Image: Construction of Work ELECTRICAL, FOR PUMPS ADVANCED DOMESTIC WATER HEATING SYSTEM The CRANNER'S Ge Only The WORK INFORMATION Image: Construction of Work ELECTRICAL, FOR PUMPS ADVANCED DOMESTIC WATER HEATING SYSTEM The Work Included in this permit shall not be constructed as establishing the legal number of the construction be been cargination of the construction of the constructing the construction of the construction of the construc	9L	CONTRACTOR, ARCHITZCT & ENGINEER NAME ADDRESS		CLASS LICEN	SE# PHONE#
Intercent Press: For Cashier's Use Only W/O 94119552 Intercent Press: Builden Control Cashier's Use Only W/O 9411952 Intercent Press: Builden Control Cashier's Use Only W/O 9411952 Intercent Press: Builden Control Cashier's Use Only W/O 9411952 Intercent Press: Builden Control Cashier's Use Only W/O 9411952 Intercent Press: Builden Control Cashier's Use Only W/O 9411952 Intercent Press: Builden Control Cashier's Use Only W/O 9411952 Intercent Press: Builden Control Cashier's Use Only W/O 9411952 Intercent Press: Builden Control Cashier's Use Only W/O 9411952 Intercent Press: Builden Control Cashier's Use Only W/O 9411952 Intercent Press: Builden Control Cashier's Use Only W/O 9411952 Intercent Press: Builden Control Cashier's Use Only W/O 9411952 Intercent Press: Builden Control Cashier's Use Only W/O 9411952 Intercent Press: Builden Control Cashier's Use Only W/O 9411952 Intercent Press: Builden Control Cashier's Use Only Store Cashier's Use Only Intercent Press: Builden Control Cashier's Use Only Store Cashi			, CA 192821	B 9674	08 (951)768-0719
Inscretation of the second procession of the same of california and states (California and States) and States (California and States) and States (California and States) and States). Image: State States (California and States) and States (California and States) and States). Image: States (California and States) (California and States		92021		-8 -	- 12 13
Inscretation of the second procession of the same of california and states (California and States) and States (California and States) and States (California and States) and States). Image: State States (California and States) and States (California and States) and States). Image: States (California and States) (California and States					W/O 9/119552
Image: Construct of the print of the print shall not be construct as establishing the legal number of dwelling units or guest rooms. That number is establishing the legal number of dwelling units or guest rooms. That number is establishing the legal number of dwelling units or guest rooms. That number is establishing the legal number of dwelling units or guest rooms. That number is establishing the legal number of dwelling units or guest rooms. That number is establishing the legal number of critificae of Occupancy. In the event that any box (i.t10) filled to its capacity it is possible that additional informations have captured decronically and could not be printed due to space restructions. Nevertheless, the information printed exceeds that required by Section (1982) of _the event and any box (i.t10) (242-245), request inspections, via www.ladits.org. To k ton Call Cente a nt, call 3°. Outside LA County cart (213) 413- 233. AM LA HENR 106/1236/19 5/23/2019 ElecTRICAL PERMIT-COM ElecTRICAL PERMIT-COM Event of the construct as the capture of printed exceeds that required by Section (1982) of _the Health and Safety County cart (213) 413- 233.		<u>SPPLICATION CC_COMMENTS</u>	For Cashier's Use On	ly State	W/O)411)332
Image: Construct of the print of the print shall not be construct as establishing the legal number of dwelling units or guest rooms. That number is establishing the legal number of dwelling units or guest rooms. That number is establishing the legal number of dwelling units or guest rooms. That number is establishing the legal number of dwelling units or guest rooms. That number is establishing the legal number of dwelling units or guest rooms. That number is establishing the legal number of critificae of Occupancy. In the event that any box (i.t10) filled to its capacity it is possible that additional informations have captured decronically and could not be printed due to space restructions. Nevertheless, the information printed exceeds that required by Section (1982) of _the event and any box (i.t10) (242-245), request inspections, via www.ladits.org. To k ton Call Cente a nt, call 3°. Outside LA County cart (213) 413- 233. AM LA HENR 106/1236/19 5/23/2019 ElecTRICAL PERMIT-COM ElecTRICAL PERMIT-COM Event of the construct as the capture of printed exceeds that required by Section (1982) of _the Health and Safety County cart (213) 413- 233.					
Image: Construct of the print of the print shall not be construct as establishing the legal number of dwelling units or guest rooms. That number is establishing the legal number of dwelling units or guest rooms. That number is establishing the legal number of dwelling units or guest rooms. That number is establishing the legal number of dwelling units or guest rooms. That number is establishing the legal number of dwelling units or guest rooms. That number is establishing the legal number of critificae of Occupancy. In the event that any box (i.t10) filled to its capacity it is possible that additional informations have captured decronically and could not be printed due to space restructions. Nevertheless, the information printed exceeds that required by Section (1982) of _the event and any box (i.t10) (242-245), request inspections, via www.ladits.org. To k ton Call Cente a nt, call 3°. Outside LA County cart (213) 413- 233. AM LA HENR 106/1236/19 5/23/2019 ElecTRICAL PERMIT-COM ElecTRICAL PERMIT-COM Event of the construct as the capture of printed exceeds that required by Section (1982) of _the Health and Safety County cart (213) 413- 233.				1	
Image: Construct of the print of the print shall not be construct as establishing the legal number of dwelling units or guest rooms. That number is establishing the legal number of dwelling units or guest rooms. That number is establishing the legal number of dwelling units or guest rooms. That number is establishing the legal number of dwelling units or guest rooms. That number is establishing the legal number of dwelling units or guest rooms. That number is establishing the legal number of critificae of Occupancy. In the event that any box (i.t10) filled to its capacity it is possible that additional informations have captured decronically and could not be printed due to space restructions. Nevertheless, the information printed exceeds that required by Section (1982) of _the event and any box (i.t10) (242-245), request inspections, via www.ladits.org. To k ton Call Cente a nt, call 3°. Outside LA County cart (213) 413- 233. AM LA HENR 106/1236/19 5/23/2019 ElecTRICAL PERMIT-COM ElecTRICAL PERMIT-COM Event of the construct as the capture of printed exceeds that required by Section (1982) of _the Health and Safety County cart (213) 413- 233.			e* 1***	k.	
Image: Construct of the print of the print shall not be construct as establishing the legal number of dwelling units or guest rooms. That number is establishing the legal number of dwelling units or guest rooms. That number is establishing the legal number of dwelling units or guest rooms. That number is establishing the legal number of dwelling units or guest rooms. That number is establishing the legal number of dwelling units or guest rooms. That number is establishing the legal number of critificae of Occupancy. In the event that any box (i.t10) filled to its capacity it is possible that additional informations have captured decronically and could not be printed due to space restructions. Nevertheless, the information printed exceeds that required by Section (1982) of _the event and any box (i.t10) (242-245), request inspections, via www.ladits.org. To k ton Call Cente a nt, call 3°. Outside LA County cart (213) 413- 233. AM LA HENR 106/1236/19 5/23/2019 ElecTRICAL PERMIT-COM ElecTRICAL PERMIT-COM Event of the construct as the capture of printed exceeds that required by Section (1982) of _the Health and Safety County cart (213) 413- 233.					
Image: Construct of the print of the print shall not be construct as establishing the legal number of dwelling units or guest rooms. That number is establishing the legal number of dwelling units or guest rooms. That number is establishing the legal number of dwelling units or guest rooms. That number is establishing the legal number of dwelling units or guest rooms. That number is establishing the legal number of dwelling units or guest rooms. That number is establishing the legal number of critificae of Occupancy. In the event that any box (i.t10) filled to its capacity it is possible that additional informations have captured decronically and could not be printed due to space restructions. Nevertheless, the information printed exceeds that required by Section (1982) of _the event and any box (i.t10) (242-245), request inspections, via www.ladits.org. To k ton Call Cente a nt, call 3°. Outside LA County cart (213) 413- 233. AM LA HENR 106/1236/19 5/23/2019 ElecTRICAL PERMIT-COM ElecTRICAL PERMIT-COM Event of the construct as the capture of printed exceeds that required by Section (1982) of _the Health and Safety County cart (213) 413- 233.				~× ·	
Image: control motion of the second secon			4	C	
ACURCLEMETRICE: AMPLACATION REDGESSING INFORMATION Plan Check By: OK for Cashier: Monique Perez Signature: net work included in this permit shall not be construed as establishing the legal number of dwelling units or guest rooms. That number is established by a Building Permit or a Certificate of Occupancy. In the event that any box (i.e. 1-10) is filled to its capacity. It is possible that additional information has been captured electronically and could not be printed due to space restrictions. Nevertheless, the information printed exceeds that requited by Section [9825 of_the Health and Safety Code of the State of California. For inspection requests, cal 4BUILD (524-2845), request inspections via www.ladbs.org. To k toa Call Cente a nt, call 3". Outside LA County catt (213) 413-3231. LA HENR 106123619 5/23/2019 ELECTRICAL PERMIT-COMM DEV SERV CENTER SURCH SYSTm4S DEVT FEE ELECTRICAL PERMIT-COMM DEV SERV CENTER SURCH SYSTm4S DEVT FEE ELECTRICAL PERMIT-COMM DEV SERV CENTER SURCH			$n \vee$	₽	
ACURCLEMETRICE: AMPLACATION REDGESSING INFORMATION Plan Check By: OK for Cashier: Monique Perez Signature: net work included in this permit shall not be construed as establishing the legal number of dwelling units or guest rooms. That number is established by a Building Permit or a Certificate of Occupancy. In the event that any box (i.e. 1-10) is filled to its capacity. It is possible that additional information has been captured electronically and could not be printed due to space restrictions. Nevertheless, the information printed exceeds that requited by Section [9825 of_the Health and Safety Code of the State of California. For inspection requests, cal 4BUILD (524-2845), request inspections via www.ladbs.org. To k toa Call Cente a nt, call 3". Outside LA County catt (213) 413-3231. LA HENR 106123619 5/23/2019 ELECTRICAL PERMIT-COMM DEV SERV CENTER SURCH SYSTm4S DEVT FEE ELECTRICAL PERMIT-COMM DEV SERV CENTER SURCH SYSTm4S DEVT FEE ELECTRICAL PERMIT-COMM DEV SERV CENTER SURCH			7		
ACURCLEMETRICE: AMPLACATION REDGESSING INFORMATION Plan Check By: OK for Cashier: Monique Perez Signature: net work included in this permit shall not be construed as establishing the legal number of dwelling units or guest rooms. That number is established by a Building Permit or a Certificate of Occupancy. In the event that any box (i.e. 1-10) is filled to its capacity. It is possible that additional information has been captured electronically and could not be printed due to space restrictions. Nevertheless, the information printed exceeds that requited by Section [9825 of_the Health and Safety Code of the State of California. For inspection requests, cal 4BUILD (524-2845), request inspections via www.ladbs.org. To k toa Call Cente a nt, call 3". Outside LA County catt (213) 413-3231. LA HENR 106123619 5/23/2019 ELECTRICAL PERMIT-COMM DEV SERV CENTER SURCH SYSTm4S DEVT FEE ELECTRICAL PERMIT-COMM DEV SERV CENTER SURCH SYSTm4S DEVT FEE ELECTRICAL PERMIT-COMM DEV SERV CENTER SURCH			\mathcal{U}		
ACURCLEMETRICE: AMPLACATION REDGESSING INFORMATION Plan Check By: OK for Cashier: Monique Perez Signature: net work included in this permit shall not be construed as establishing the legal number of dwelling units or guest rooms. That number is established by a Building Permit or a Certificate of Occupancy. In the event that any box (i.e. 1-10) is filled to its capacity. It is possible that additional information has been captured electronically and could not be printed due to space restrictions. Nevertheless, the information printed exceeds that requited by Section [9825 of_the Health and Safety Code of the State of California. For inspection requests, cal 4BUILD (524-2845), request inspections via www.ladbs.org. To k toa Call Cente a nt, call 3". Outside LA County catt (213) 413-3231. LA HENR 106123619 5/23/2019 ELECTRICAL PERMIT-COMM DEV SERV CENTER SURCH SYSTm4S DEVT FEE ELECTRICAL PERMIT-COMM DEV SERV CENTER SURCH SYSTm4S DEVT FEE ELECTRICAL PERMIT-COMM DEV SERV CENTER SURCH				2	
ACURCLEMETRICE: AMPLACATION REDGESSING INFORMATION Plan Check By: OK for Cashier: Monique Perez Signature: net work included in this permit shall not be construed as establishing the legal number of dwelling units or guest rooms. That number is established by a Building Permit or a Certificate of Occupancy. In the event that any box (i.e. 1-10) is filled to its capacity. It is possible that additional information has been captured electronically and could not be printed due to space restrictions. Nevertheless, the information printed exceeds that requited by Section [9825 of_the Health and Safety Code of the State of California. For inspection requests, cal 4BUILD (524-2845), request inspections via www.ladbs.org. To k toa Call Cente a nt, call 3". Outside LA County catt (213) 413-3231. LA HENR 106123619 5/23/2019 ELECTRICAL PERMIT-COMM DEV SERV CENTER SURCH SYSTm4S DEVT FEE ELECTRICAL PERMIT-COMM DEV SERV CENTER SURCH SYSTm4S DEVT FEE ELECTRICAL PERMIT-COMM DEV SERV CENTER SURCH		2. CHECKLIST ITEMS:	- 82 - 68s	.4	
AMPLICATION FUNCTIONATION Plan Check By: OK for Cashier: Monique Perez Signature: ne work included in this permit shall not be construed as establishing the legal number of dwelling units or guest nooms. That number is established by a Bailding Permit or a Certificate of Occupancy. In the event that any box (i.e. 1-10) is filled to its capacity. it is possible that additional information has been captured electronically and could not be printed due to space restrictions. Nevertheless, the information printed exceeds that required by Section 19825 of the Heath and Safet OC doal formation. For inspection requests, cal 4BUILD (524-2845), request inspections via www.ladbs.org. To k toa Call Cente a nt, call 3". Outside LA County catt (213) 413-3231. \$13.14. LA HENR 106123619 5/23/2019 \$12.CERTRICAL PERMIT=-COMM ELECTRICAL PERMIT=-COMM SYSTm4S DEVT FEE ELECTRICAL PERMIT-COMM SYSTm4S DEVT FEE ELECTRICAL PERMIT-COMM <td< td=""><td></td><td></td><td></td><td>-</td><td></td></td<>				-	
Plan Check By: OK for Cashier: Monique Perez Signature: Date: 05/23/2019 MOTICE: net work included in this permit shall not be construed as establishing the legal number of dwelling units or guest rooms. That number is established by a Building Permit or a Certificate of Occupancy. In the event that any box (i.e. 1-10) is filled to its capacity, it is possible that additional information printed electronically and could not be printed due to space restrictions. Nevertheless, the information printed exceeds that required by Section (9825 of the Hcalith and Safety Code of the State of California, For inspection requests, cal 4BUILD (524-2845), request inspections via www.ladbs.org. To k toa Call Cente a nt, call 3°. Outside LA County catt (213) 413- 3231. LA HEINR 106123619 5/23/2019 ELECTRICAL PERMIT-COM DEV SERV CENTER SURCH SYSTm45 DEVT FEE ELECTRICAL PERMIT-COM ELECTRICAL PERMIT-COM DEV SERV CONTER SURCH SYSTm45 DEVT FEE ELECTRICAL PERMIT-COM ELECTRICAL PERMIT-COM DEV SERV CONTER SURCH SYSTm45 DEVT FEE ELECTRICAL PERMIT-COM ELECTRICAL PERMIT-COM ELECTRICAL PERMIT-COM ELECTRICAL PERMIT-COM SIGNATION COM SYSTm45 DEVT FEE ELECTRICAL PERMIT-COM ELECTRICAL PERMIT-COM ELECTRICAL PERMIT-COM SYSTm45 DEVT FEE ELECTRICAL PERMIT-COM SYSTm45 DEVT FEE ELECTRICAL PERMIT-COM SYSTm45 DEVT FEE ELECTRICAL PERMIT-COM SYSTm45 DEVT FEE ELECTRICAL PERMIT-COM SYSTMAS DEVT FEE SUCH SYSTMAS DEVT FEE SUCH SYSTM			_		
r AM required of Occupancy. In the event that any box (i.e. 1-10) is filled to its capacity, it is possible that additional information has been captured electronically and could not be printed due to space restrictions. Nevertheless, the information printed exceeds that required by Section 19825 of the Hcalth and Safety Code of the State of California, AM For inspection requests, cal 4BUILD (524-2845), request inspections via www.ladbs.org. To k toa Call Cente a nt, call 3". Outside LA County catt (213) 413-3231. \$13.14. LA HENR 106123619 5/23/2019 \$23.00. LeterTRICAL PERMIT-COMM SYSTm4S DEVT FEE ELECTRICAL PERMIT-COMM SUBLECTRICAL PERMIT-COMM	vd S2	Constant of the second s			
r AM required of Occupancy. In the event that any box (i.e. 1-10) is filled to its capacity, it is possible that additional information has been captured electronically and could not be printed due to space restrictions. Nevertheless, the information printed exceeds that required by Section 19825 of the Hcalth and Safety Code of the State of California, AM For inspection requests, cal 4BUILD (524-2845), request inspections via www.ladbs.org. To k toa Call Cente a nt, call 3". Outside LA County catt (213) 413-3231. \$13.14. LA HENR 106123619 5/23/2019 \$23.00. LeterTRICAL PERMIT-COMM SYSTm4S DEVT FEE ELECTRICAL PERMIT-COMM SUBLECTRICAL PERMIT-COMM	a Bl		1. 1 . 0. 100	Sau-S	
r AM required of Occupancy. In the event that any box (i.e. 1-10) is filled to its capacity, it is possible that additional information has been captured electronically and could not be printed due to space restrictions. Nevertheless, the information printed exceeds that required by Section 19825 of the Hcalth and Safety Code of the State of California, AM For inspection requests, cal 4BUILD (524-2845), request inspections via www.ladbs.org. To k toa Call Cente a nt, call 3". Outside LA County catt (213) 413-3231. \$13.14. LA HENR 106123619 5/23/2019 \$23.00. LeterTRICAL PERMIT-COMM SYSTm4S DEVT FEE ELECTRICAL PERMIT-COMM SUBLECTRICAL PERMIT-COMM	l'ijer 00-	OK for Cashier: Monique Perez	10 5.5 ku 4.000		
r AM required of Occupancy. In the event that any box (i.e. 1-10) is filled to its capacity, it is possible that additional information has been captured electronically and could not be printed due to space restrictions. Nevertheless, the information printed exceeds that required by Section 19825 of the Hcalth and Safety Code of the State of California, AM For inspection requests, cal 4BUILD (524-2845), request inspections via www.ladbs.org. To k toa Call Cente a nt, call 3". Outside LA County catt (213) 413-3231. \$13.14. LA HENR 106123619 5/23/2019 \$23.00. LeterTRICAL PERMIT-COMM SYSTm4S DEVT FEE ELECTRICAL PERMIT-COMM SUBLECTRICAL PERMIT-COMM	La 100	Signature			
of dwelling units or guest rooms. That number is established by a Building Permit or a Certificate of Occupancy. In the event that any box (i.e. 1-10) is filled to its capacity. it is possible that additional information has been captured electronically and could not be printed due to space restrictions. Nevertheless, the information printed exceeds that required by Section (9825 of_the Health and Safety Code of the State of California, For inspection requests, cal 4BUILD (524-2845), request inspections via www.ladbs.org. To k toa Call Cente a nt, call 3". Outside LA County catt (213) 413- 3231. LA HENR 106123619 5/23/2019 ELECTRICAL PERMIT-COMM DEV SERV CENTER SURCH SYSTm4S DEVT FEE ELECTRICAL PERMIT-COMM	0 S 0		-	-, , (1)	
of dwelling units or guest rooms. That number is established by a Building Permit or a Certificate of Occupancy. In the event that any box (i.e. 1-10) is filled to its capacity. it is possible that additional information has been captured electronically and could not be printed due to space restrictions. Nevertheless, the information printed exceeds that required by Section (9825 of_the Health and Safety Code of the State of California, For inspection requests, cal 4BUILD (524-2845), request inspections via www.ladbs.org. To k toa Call Cente a nt, call 3". Outside LA County catt (213) 413- 3231. LA HENR 106123619 5/23/2019 ELECTRICAL PERMIT-COMM DEV SERV CENTER SURCH SYSTm4S DEVT FEE ELECTRICAL PERMIT-COMM		e nte work included in this permit shall not be construed as establishing the legal number	4 	· • • •	
is possible that additional information has been captured electronically and could not be printed due to space restrictions. Nevertheless, the information printed exceeds that required by Section [9825 of_ the Health and Safety Code of the State of California, For inspection requests, cal 4BUILD (524-2845), request inspections via www.ladbs.org. To k toa Call Cente a nt, call 3". Outside LA County catt (213) 413- 3231. LA HENR 106123619 5/23/2019 ELECTRICAL PERMIT-COMM DEV SERV CENTER SURCH SYSTm4S DEVT FEE ELECTRICAL PERMITI-COMM DEV SERV CENTER SURCH SYSTm4S DEVT FEE ELECTRICAL PERMITI-COMM DEV SERV CENTER SURCH SYSTm4S DEVT FEE ELECTRICAL PERMITI-COMM DEV SERV CENTER SURCH SYSTm4S DEVT FEE		of dwelling units or guest rooms. That number is established by a Building Permit or a		-5	AM
requited by Section [9825 of_ the Hcalth and Safety Code of the State of California, \$6.57 For inspection requests, cal 4BUILD (524-2845), request inspections via www.ladbs.org. To k toa Call Cente a nt, call 3". Outside LA County catt (213) 413-3231. \$13.14. LA HENR 106123619 5/23/2019 \$23.00. ELECTRICAL PERMIT-COMM DEV SERV CENTER SURCH SYSTm4S DEVT FEE ELECTRICAL PERMIT-COMM DEV SERV CENTER SURCH SYSTm4S DEVT FEE ELECTRICAL PERMIT-COM ELECTRICAL PERMIT-COM		is possible that additional information has been captured electronically and could not be		,	\$196.00
In the inplotent of the inplotent inplotent inplotent in the inplotent inplotent in the inplotent inplotent in the inplotent inplotent in the inplotent inplotent in the inplotent inplotent in the inplotent inplotent inplotent inplotent inplotent inplotent inplotent inplotent inplotent in the inplotent inplo					\$6.57
www.ladbs.org. To k toa Call Cente a nt, call 3". Outside LA County catt (213) 413- 3231. LA HENR 106123619 5/23/2019 ELECTRICAL PERMIT-COM DEV SERV CENTER SURCH SYSTM4S DEVT FEE ELECTRICAL PERMIT-COM ELECTRICAL PERMIT-COM DEV SERV CENTER SURCH SYSTM4S DEVT FEE ELECTRICAL PERMIT-COM ELECTRICAL PERMIT-COM DEV SERV CENTER SURCH SYSTM4S DEVT FEE ELECTRICAL PERMIT-COM DEV SERV CENTER SURCH			an linear a	. <u>'</u> 4 '	\$13.14
LA HENR 106123619 5/23/2019 ELECTRICAL PERMIT-COMM DEV SERV CENTER SURCH SYSTm4S DEVT FEE ELECTRICAL PERMITI-CObBf ELECTRICAL PERMIT-CON		www.ladbs.org. To k toa Call Cente a nt, call 3". Outside LA County catt (213) 413-			\$23.00.
ELECTRICAL PERMIT-COMM DEV SERV CENTER SURCH SYSTm4S DEVT FEE ELECTRICAL PERMIT-COb BF ELECTRICAL PERMIT-CON * P 1 9 0 4 1 I IIII IIII IIII IIIII IIIII IIIII IIII		3231.	23.34.54	ur.	
ELECTRICAL PERMIT-COMM DEV SERV CENTER SURCH SYSTm4S DEVT FEE ELECTRICAL PERMIT-COb BF ELECTRICAL PERMIT-CON * P 1 9 0 4 1 I IIII IIII IIII IIIII IIIII IIIII IIII					
ELECTRICAL PERMIT-COMM DEV SERV CENTER SURCH SYSTm4S DEVT FEE ELECTRICAL PERMIT-COb BF ELECTRICAL PERMIT-CON * P 1 9 0 4 1 I IIII IIII IIII IIIII IIIII IIIII IIII					
DEV SERV CENTER SURCH SYSTm4S DEVT FEE SYSTm4S DEVT FEE ELECTRICAL PERMIT-CODBF ELECTRICAL PERMIT-CQN * P 1 9 0 4 11 IIIII IIIII IIIII IIIII IIIII IIIII IIII					
SYSTM4S DEVT FEE ELECTRICAL PERMITI-CODBF ELECTRICAL PERMIT-CQN * P 1 9 0 4 11 11111 11111 11111 11111 11111 11111 1111					
ELECTRICAL PERMI'I'-CObbf ELECTRICAL PERMIT-CQN * P 1 9 0 4 1 IIIII IIII IIII IIIII IIIII IIIII IIIII					
			ELECTRICAL PERMI		ICAL
			PERMIT-CQN		
			· • • • • • • • • • • • • • • • • • • •	T T1TTT T1T1	
190411000019552Sub Total : \$238.71					1 111 11 11 11
		190411000019552Sub Total :			\$238.71

9400 S La Tijera Blvd



4110000

9400 S La Tijera Blvd

19016 10000 - 11459

	SE SE		-	:k #:		
		E DR	2	le:		
Bldg-Alter/Repair GREEN .NONE Apartment				Safety	Issued on:	05/10/2019
Plan Check at Counter Pian Check	B19LA07875	Printed: 05/10/19		RM1f	Last Statu	s: Issued
Check	DEPARTME	ENT OF BUILDI		NCY	Status Dat	e: 05/10/2019
	TRACI	SAFET		44/87	096B161 83	2. ASSESSOR PARC 4119 - 039 - 00
LA Department: of	TR 19445	Building a LA	nd Safety 104156122			4119 - 039 - 00
5/10/2019 : 27 :AM						
BUILDING			COMM*920.00			
Airport Hazard Area i 50' Height Lin Abi Airpoit Hazard Area - Transitior Surface Area Planning Commiqgion West Los Ang ADBS Blanch Office WLA Council District - Il		\$0.00. \$42.00 DEV SERV DEVT PLANNING SURCH! MISCELLANEOUS	\$57.72 CITY	CH Energy Fire Dis Hiflside	Map - 096B Zone - 6 strict 2 c Grading Area - YES surce Zone Distance -	6.3
ZONES(S): [QIC4-1-CDO	-		BL			
ZI - ZI-2374 LOS ANGELES STAT ZI - ZI-2404 Loyola Village ZI - ZI-2402 Transit Priority Area in ZA ₃₄ ZA-1987-1490-SM	Permit #: 190	#: 2019LA24574	\$1,1 STI	D	ORD - ORD-18079 CPC CPC-i956 CPC • CPC.1984-226 CPC - CPC-1986-292-	5-70S8 5-SP
5. CHECKLIST ITEMS Special Inspect - Anchor Bolts Special Inspect - Concrete>2.5ksi Special Inspect - Epoxy Bolts			¥.			
5. PROPERTY OWNER, TENANT. APPLIC Owner(s): EQR BETHANY VILLAGE VISTA 0 PO BOX 87407, CHICAGO IL 60 Tenant:	AID: A000000	0041010		r's Use Only t'NISSION SUR ECK 90.00		W/O #: 91 00 BUILDING PLAN
	•		្ទព	ub	Tota	ıl: \$1,184.18
Applicant: (Relationship: Other) WILLIAM B ENETECH 920 W. LAMBERT RD. SUITE J, E	BREA, CA 92821 (714) 255-2	2939]	ub	vv	
2. EXISTING USE (05) Apartment	PROPOSED	USE		5		
		1				

190161000011459. Permit

8. DESCRIPTION OF WORK New concrete pad and anchorages for (N) solar water heating and GEHP storage tanks on ground level.		
9. #Bidez on Site & Use:		
go. PROCESSING BLDG. pc By: Nguyen DAS pc By: OK ti)r Cashier: Michael Lopez Coord. OK; Signature: Date: 05/10/2019	LA ESTE 104156122 5/10/2019 9:27:38 AM BUILDING PERMIT cowna BUILDING PIAN CEECK EI RESIDENTIAL	\$920.00 \$42.00
11. PROJECT VALUATION Final Fee Period Permit Valuation: \$150,000 PC Valuation:	DEV SERV CENTER SURCH \$28.8	
Sewer Cap ID: Total Bond(s). Due: 12. ATTACHMENTS	DEVE FEE \$57.72 CITY PLANNING S MISCELL4	URCH \$55.20
Plot Plan For inspection requests. call toil-free (888) LA4BUILD (524-2845), or request inspections via www.ladbs.org. To speak to a Call Center agent, cau 311. Oatside LA County, (2*3) 473-3231.	PLANNING	64.40 ca BLDG s'iD
* P 1 9 0 1 6 1 0 0 0 0 1 1 4 5 9 F N *	Tot-al: Permit #: 19935630099459 Building Card #: 2019 Receipt #: 0104038465 2019LA24574	\$1,184.18

А

p p

1 i

с

а t

i

0 n

Р

1

а

n

С

h

e

		-

с

k В

1

9

1

.

А

0

7

8

7

S

Е

v

		e		
		n		
		t		
		19016 10000 1145 °		d: 04/19/19 10:18 AM
.Bldg.A1ter/Repair GREEN NONE	City of Los Angei	es• Depattntentof Building and Safety	Plinte	d: 04/19/19 10:18 AM
Apartment				
Ptan Check at Counter Plan Check		FOR BUILDING PERMIT	Last Status: PC in	Progrßs
	bOT(si		Status Date: 04/19	/2019 4119 039 — 004
TR 19445	10	3 M B 628-84/87	096B161 01	
Airport Hazard Area 150' Elcight Limit Above E Airport Hazard Area - fransitional Surface Area		verlay District - Loyola Village d Council Westchester/Ptaya dc! Rey Energy	096B 16 t Zone -6	
Ätea Planning Cotnmission - West Los Angeles LADBS Branch Office - WI,A Coundil District-	Community Noise Equ	uiv, Level - 65 db < dB Fire Di a - Westchester Playa def Rey Hillside		
IQ]C4-1-CDO				
	a in Cit ORD ^A IOt823	ORD - ORD. 129279 ORD - ORD- 161650 ORD - 00-168999 ORD - 00-168999	ORD ORD. t*0797 CPC - CPC-19S6-fi058 CPC 984-226-SP	
- ZA-i987- t490-SM	ORD ORO-I t 006	ORD ORD.J759S1-SA500	CPC CPC-1986-292-ZC	
EQR BETHANY VILLAGE VSTAS IN PO BOX CHICAGO IL 60680 Tena		For Cashier's Use Or	nly	W/0 4: 91611459.
App%canc (Relationship: Other) WILLIAM 920 W. LAMBERTRD, SUITE J, BREA				
SOLAR WATER HEATING & GEMP STO CONCRETE INSPECTION.	ORAGE TANK & GEHPANCHOR& CONC	RETE.		
?.ROCESSING				
BLDG. pc By: OK Cashier:	DAS PC. By: Coord. OK:			
Signature:	Date:			
it. Submittal ftePeriod <u>M5</u> Sewer Cap ID:	0.000 Total Bond(s) Due:	BUILDING H DEV SER SURCH SYS PEE ctTY	TEMS DEVT PLANNING	\$828.00 \$24.84 \$49.68 \$49.68
		SURCH MISC PLANNING	ELLANEOtJS MAINT St.JRCX	\$10.00

d

e :

DAVI 307033750 1/31/2019\$1.65LUbBJNGPbRMIT,,.CüMM\$3.30DEV SERV CENTER SURCH\$0,00SYSTEMS DEVIS\$0,00AN CHECK AND INSPECTIONDate: 01/31/2019	Fnrinspaction requests, can (888) LA4BiJILD (524- request inspections via To gpeak to a Call Center age	2845). Outside LA nt, can 311. Outside	County, cali (213) 482-0000 or LA County, (213) *73-3231.			\$57 96	
@DBS Pennit Y: k Plan Check X19LA01839 19042 10000 0246 Printed: 01/3 i/19 09:16 A DEPARTMENT OF BUILDING AND SAFETY Event Code: A Department of Building and Safety Issued On: 01131/2019 S1.65 S1.65 DEW SRV CENTRE SURCH 'NUMBINGPERMIT-COAM \$0,00 SV SRV CENTRE SURCH 'STEMD EPEY' 'LUMBINGPERMIT-COAM \$0,00 gub (951)768-0719 190421000002461 (951)768-0719 (C) ENETECHINCORPORATED 420 W LAMBERT RD BREA, CA 92821 C33 967408 (950768-071) solar wattre Heating system 420 W LAMBERT RD BREA, CA 92821 C33 967408 (950768-071) Image: Solar wattre Heating system Image: Solar wattre Heating system Image: Solar wattre Heating system Image: Solar wattre Heating system Image: Solar wattre Heating system Image: Solar wattre Heating system Image: Solar wattre Heating system Image: Solar wattre Heating system Image: Solar wattre Heating system Image: Solar wattre Heating system Image: Solar wattre Heating system Image: Solar wattre Heating system Image: Solar wattre Heating system Image: Solar wattre Heating system Image:) 0 -O		Permit	19016100	0011459	
Plan Check X191A01839 Printed: 01/3 i/19 09:16 A DEPARTMENT OF BUILDING AND SAFETY Event Code: A Department of Building and Safety Issued On: 01131/2019 DAVI 307033750 1/31/2019 \$1.65 IDBINGPERMIT-COEN \$0,00 AN CHECK AND INSPECTION Date: 01/31/2019 UMBINGPERMIT-COEN \$0,00 AN CHECK AND INSPECTION COMPORATED \$190421000002461 UMBINGPERMIT-COEN \$100 AN CHECK AND BREA.CA 92821 C33 967408 (950768-071 DOT \$100 AN CHECK BUILD \$100 AN CHECK AND BREA.CA 92821 C33 967408 (950768-071 DOT \$100 AN CHECK BUILD \$100 AN CHECK BUIL	19G						
A DeparEment of But-Iding and DAVI 307033750 1731/2019 DAVI 307033750 1731/2019 S1.65 SVERKE SURCH YSTEMS DEV!S UMBINOPERMIT-COEN gub 190421000002461 (C) ENETECHINCORPORATED 420 W LAMBERT RD BREA, CA 92821 (C) ENETECHINCORPORATED 420 W LAMBERT RD BREA, CA 92821 SOLAR WATER HEATING SYSTEM SOLAR WATER HEATING SYSTEM Plin Check By: OK for Cashier: Trevia Hodge	@ <u>DBS</u>				A01839		
DAVI 307033750 1/31/2019 LUBINOPRRMT_COMM EVS SERV CENTER SURCH VYSTEMS DEVIP LUMBINGPERMIT-COEN gub 190421000002461 (C) ENETECHINCORPORATED 420 W LAMBERT RD SOLAR WATER HEATING SYSTEM II Plan Check By: OK for Cashier: Trevia Hodge	DEPARTMENT OF BU	JILDING A	AND SAFETY	Event Code:			
LUBBINGPERMIT_CBAM S3.30 PPLICATION FOR PLUMBING L5 Status Essed STATES SURCH INSTERS SURCES IN			Angeles Department	of Building and Safety	Issued O	n: 01131/2019	
XYSTEMS DEVI ^S SV, OU AN CHECK AND INSPECTION UMBINGPERMIT-COEN 95 87407 CHICAGO IL 60680 (951)768-0719 190421000002461 (C) ENETECHINCORPORATED 420 W LAMBERT RD BREA. CA 92821 C33 967408 (950768-071 C34 97 C44 C44 C44 C44 C44 C44 C44 C44 C44 C4		\$3.30					
gub (931)768-0719 190421000002461 C33 907408 (950768-071 (C) ENETECHINCORPORATED 420 W LAMBERT RD BREA, CA 92821 C33 907408 (950768-071 SOLAR WATER HEATING SYSTEM	YSTEMS DEVI ^S					ate: 01/31/2019	
I DOUZIONO DOUZIA DI DE LA CA 92821 C33 967408 (950768-071 C33 967408 (950768-071 C34 Carbon Carbo		95	87407	CHICAGO IL 6	0680		
SOLAR WATER HEATING SYSTEM II Plan Check By: OK for Cashier: Trevia Hodge						(951)768-0719)
Il Plan Check By: OK for Cashier: Trevia Hodge	(C) ENETECHINCORPORA	TED 420	W LAMBERT RD	BREA, CA 92821		C33 967408 (950768-07	19
Plan Check By: OK for Cashier: Trevia Hodge	SOLAR WATER HEATING SYSTEM						
OK for Cashier: Trevia Hodge	11						
Signature: Date: <u>01/31/</u> 2019							
	Signature:		Date: 01/31/2019				

	For Cashier's Use Only	W/O 94202461
The work included in this permit Shau not be construed as establishing the. legal number of dwelling units or guest rooms, That number is established by a Building Permit Of a Certificate ofOeeupancy. Intheeventthat any box (i.e. ("10) -is lilied to itscgpaeitY* itis possible {hat additional information has been captured electronically md could not be printed due swaee Nevertheless, the: information printed-exceeds that required by Section 19825 of the Code Of the State ofCalifornia.		
For inspeeåon requestss cali ton-free 4BULLD (514-2845). Outside LA COImty, (213) 482-0000 or requestius ns Via b org, To speak to Catt Center agent, OuGideLACounty.		
	rA bÄVt 107033750 1/31/2019 DEV SERV CENTER SURCE DEV'? FEE	\$55.00 65
	BEV??FEE sub 190421000002461 Receipt 0107996927	\$\$9,95

11/15/18 Supervision Sameti 1000000 213 482-6524

9400 S La Tijera Blvd

G

Application #: Plan Check #: M181 Event Code: 18042 - 10000 - 25924 **T** 7 Printed: 10/25/18 03:33 PM

		City of Los Angeles - Department of	Building and Safety		
Apartn	nent	APPLICATION FOR PLU	JMBING	Last Status: Submitted	
Regula	r Plan Check				
Plan Ch	eck	PLAN CHECK AND INSP	PECTION	StatusDate•. 10/25/2018	3
L PROPI	ERTY				
	R BETHANY VILLAGE VISTAS INC OP <u>ANT INFORMATION</u> (Relationship: Engineer)	O BOX 87407	CHICAGO IL 60680		
AB	BDULLAH YACOB AHMED OCCIDEh 48	62 GRAPHITE CREEK RD	JURUPA VALLEY, C	A 91752	(951)768-0719
3. TENAN	T INFORMATION				
FO	4. CONTRACTOR. ARCHITECT & ENGINEER NAME	D		LICENSE #	PHONE #
M18LA06406FO	(E) ,	4862 GRAPHITE CREEK RD	, JURUPA VALLEY, CA 917	752 M2354	
M18L	5. APPLICATION COMMENTS		For Cashier ^t s Use (Only	W/O 84225924
					9
	4. DESCRIPTION OF WORK			(nit	T
	ADDITION OF SUPPLEMTAL WA		/	20 000	X.
	(EVACUATED TUBE SOLAR SYS1E PUMP) ON EXISTING DOMESTIC H		. ((u)	
	APPARTMENT BUILDING.			Autobia	
				`//	
	1. CHECKLIST TTEMS			2	
	COUNCW 11				
	2. APPLICATION PROCESSING INFORMATION				
vd 42	man Check By: OK for Cashier:				
era Blvd					
- 10000	Signature: NOTICE; work included in this permit shall no	t be construed as establishing the legai	Producted		
S La	number of dwelling units or guest rooms. The Permit or a Certificate ofOccupancy. In the even	t number is established by a Building			
9400 S La Tijera Blvd 18042 - 10000 - 25924	eapaeity. it is possible that additional informatic conid not be printed due to space restrictions	on has been captured electronically and	LA ESTE 104144	314 10/25/2018 3:33:06	PM
5 4	exoeedS that required by Section 19825 of the California.		MECHANICAL pc	\$99* 00.	



For inspection requests, call toll- (524-2845). Outside LA County, call (213) 482-0000 ortequostins tions via www. adbs rg. Tospeaktoa Call Center agent; 311. OutsideLACo . (213>473-323.1.

DEV SERV CENTER SURCH	
SYSTEMS bEVT	
BECEANICAL\$ PC	

Sub Total :

\$49.50 \$161.87

\$4.46

\$8.91

Permit #: 180421000025924

Receipt #: 0104960576

INSPECTION RECORD

Your feedback is important, please visit our website to convtete customer

survey at www.iadbs.oqlLADBSWeblcustométsurvey.isf

If you would like to provide additional' feedback' need clarification, or have any question regarding plan check or inspectiori matters, please Gall our Customer Hotline at (213) 482-0056

2019LA24574 5/10/2019

LA ESTE 0104038465 19016-10000-11459 F

PERMIT NO : 19016-10000-11459 ADDRESS : 9400 S LA TIJERA BLVD WORK DESC : NEW CONCRETE PAD AND ANCHORAGES FOR (N) SOLAR STORAGE TANKS ON GROUND LEVEL. INSPECTION RECORDS AND. PLANS MUST BE AVAILABLE DURING

INSPECTION

DATEINSPECTOR initial

Grading

Toe or Bottom Soils Report Approved

DO NOT PLACE FILL UNTIL ABOVE IS SIGNED

Backfill

Excavation

Drainage Devices Rough Grading Approved Compaction Repott

Footin Excavation Forms Reinforcing Steel OK to place concrete

> Electrical Plumbing Plumbing N'Ethane Gas Piping Heating & Refrigeration

Fire Sprinklers Disabted Access Methane OK to Place Floor DO NOT PLACE FLOOR UNTIL ABOVE IS SIGNED

Green Code Electrical Plumbing Fire Sprinkler Heating & Refrigeration Roof Sheathing Disabled Access Framing Insulation Suspended Ceiling OK to Cover

FOR INSPECTION REQUESTS, PLEASE CALL 3-1-1 OR OUTSIDE CITY OF LOS ANGELES 888-LA4-BUtLD (888)524-2845 or

B-B Card rev. 411811

TYPE DATE INSPECTOR **Exterior Lathing** Interior Lathing Drywall DO NOT COVER UNTIL ABOVE ts SIGNED **Electrical Underground** Gas H6ating & Refrigeration Sewer **Disabled Access** Excavation **Reinforcing Steel** Bonding Pre-Gunite Deck Enclosure/Fence PooVSpa Cover DO NOT FILL POOL UNTIL ABOVE IS SIGNED Grading Etectricai Plumbing Gas Test Gas Heating & Refrigeration Pressure Vessels Elevator Fire Sprinkler Disabled Access Green Building I-AFD (Title 19 only) LAFD Fire Life safety **Pool Final** AQM'sign-off provided Public Works Building Certificate of Occupancy Required YES NO

SUPPLEMENTAL NOTES 16/19-

IMPORTANT NOTICE

Prior to the start of any construction work adjacent to any public way, pedestrian protection shall be provided. (Sec. 91.3303 L.A.M.C.).

- * Inspections may be requested Monday through Friday by calling 1-888-LA4-BUILD, When requesting an inspection, the following information is required: (1) The job address, (2) Type of inspection, (3) use of Building, (4) Permit number, (5) Phone number of a contact person should the department need to reach someone.
- * Inspection requests received before 4:00 p.m. Monday through Friday (excluding holidays) witl normally be made the next business day, Requests received after 4:00 p.m. will be made following the next business day. The Automated Inspection Call Back System (AICBS) will phone the contact person to confirm the inspection.

Permit fees provide for a limited number of inspections. A reinspection fee may be assessed when the work for which an inspection was requested is not complete, when the inspection record or plans are not available, or when here is failure to provide site access to department staff.

No person shall perform any construction or repair work between the hours of 9:00 p.m. (6:00 p.m. grading) and 7:00 a.m. the following day which results in loud noises to the disturbance of persons occupying sleeping quarters in any dwelling, hotel, motel, apartment, or other place of residence(Sec. 41.40 L.A.M.C.).

No person, other than an individual homeowner engaged in the repair or construction of his/her single-family dwelling, shall perform any construction or repair work of any kind upon any building or structure located on land developed with residential buildings or perform work within 500 feet of land so occupied, before 8:00 a.m. or after 6:00 p.m. on any Saturday or at any time on Sunday (Sec. 41.40 L.A.M.C.).

Dust control measures to prevent dust from being blown or deposited over or upon any private property in any residential area must be implemented during any excavation or earth-moving phase of construction, sand blasting, or demolition.

A separate permit from the State of California Division of Industrial Safety is required prior to starting certain work involving substantial risk to workers such as: construction or demolition exceeding 3 stories or 36 feet in height, or excavations or trenches over 5 feet in depth involving entry by workers.

Building permits are valid for Wvo years or expire on the 180th day from the date of issuance if the work permitted has not commenced. The department reserves the right to expire any permit where work has been suspended for a period of 180 days or more.

* Inspection services will not be provided when there is an unleashed dog on the premises.

BUILDING AND SAFETY PERMIT AND PLAN CHECK OFFICE LOCATIONS

Downtown Los Angeles

201 N. Figueroa st., 4th Fl. Los Angeles, CA

90012 Van Nuys West Los Angeles

San Pedro 638 S. Beacon St., 2nd Fl. San Pedro, CA 90731 South Los Angeles 8475 S. Vermont Aver, 2nd Fl. Los Angeles, CA 90044 6262 Van Nuys Blvd., 2nd Fl. Van Nuys, CA 91401 1828 Sawtelle Blvd., 2nd Fl. Los Angeles, CA 90025

Your feedback is important, paese visit for work of the power and ADERWINGTON of the power and ADERWINGTON for the matteries of the power and ader and the power and address of the power address of t			I our website to complete customer astisementaryex.all disade, meet claimfoulion, or have any on metters, please call our Customer	6/10	2019LA24574 5/10/2019 9:27:42AM LA ESTE 0104035465		
PERMIT NO : 19					6-10000-11459 F		
				1.000			
ADDRESS : 94	00 S LA TIJ	ERA BLVD			and the second second		
		ETE PAD AND ANCH NKS ON GROUND L	FORAGES FOR (N) SOLAR	WATER F	EATING AND GEHP		
INSPECTIO	NRECOR	DS AND PLANS	MUST BE AVAILABL		ING INSPECTION		
	NG INSPECT				PREVIOUS IS SIGNED		
TYPE	DATE	INSPECTOR	TYPE	DATE	INSPECTOR		
Initial Grading	Tour IE	Mareuron	Exterior Lathing	LWATE.	INGPECTOR		
Toe or Bottom			Interior Lething				
Solis Report Approved			Orwell	-			
DO NOT PLACE FI	LI UNTE AF	OVE IS SIGNED		VED UNTE	ABOVE IS SIGNED		
Backfill	ALL OPTING ALL	OTE IS BIUMED			F THE BUILDING		
Fil			Electrical Underground	ALC: NO.	1116 0000000000		
Excavation			Gas	-			
Drainage Devices			Hiteting & Refrigeration	-			
Rough Greding			Sever				
oproved Compaction Report			Disabled Access				
	AG INSPECT	ONS		OOL INSP	FOTIONS		
Footing Excevation			Excavation		and the second se		
Forms		/	Reinforcing Steel	-			
Reinforcing Steel	111		Bonding				
K to place concrete	HIMA /	Dur 7	Piping				
GROUND	VORK MASPE	CTONS	Pre-Gunite				
Electricel	4	//	Deck.				
Plumbing			Enclosure/Fence				
Plumbing Melhane			Pool/Spa Cover		Concern Concerns		
Gas Piping					TIL ABOVE IS SIGNED		
Heating & Refrigeration				INAL INSP	ECTIONS		
Fire Sprinklers			Grisding		Rese		
Disabled Access			Electrical	app	20 Jalina		
Mathane			Plumbing	1/30/20	Mar 4 1		
OK to Place Floor		and the second s	Gass Text	111	P		
DO NOT PLACE FLO			Geo	1/2	LAA.		
	H INSPECTIO	DNS	Heating & Refrigeration	19120	VIN		
Green Coda			Pressure Vessele		1 201		
Electrical	11		Elevator	1	1		
Plumbing	1/30/20		Fire Sprinkler		. \		
Fire Sprinkler	1 1		Disabled Access				
Heating & Refrigeration			Green Building	-	w		
Roof Sheathing			LAFD (Title 19 only)				
Disabled Access			LAFD Fire Life Safety				
Framing			Pool Final				
Insulation			AQMD sign-off provided		•		
Buspended Ceiling			Public Works				
OK to Cover			Building				
FOR INSPECTION RE	QUESTS. PL	EASE CALL 3-1-1	PROJECT PINAL	Sugar State			
OR OUTSIDE CITY OF LOS ANGELES 888-LA4-BUILD (888)524-2845 or www.ladbs.org			Certificate of Occupancy Required YES NC				





ENERGY RESEARCH AND DEVELOPMENT DIVISION

Appendix C: Measurement and Verification (M&V) Report

June 2024 | CEC-500-2024-054-AP



APPENDIX C: Measurement and Verification (M&V) Report

Overall Measurement & Verification Approach

The goal of this measurement and verification (M&V) project is to assess the overall energy savings potential of the retrofitted equipment, controls hardware, and controls strategies as compared to the baseline domestic hot water (DHW) system at the test site.

The existing DHW system that was retrofitted serves 148 residential units across four stories of the building and is located on the roof. It consists of two central gas-fired boilers (one of which is redundant) with an integral pump each, a storage tank, and two return water pumps in series in the recirculation loop. The make-up water feeds into the storage tank. The boilers are controlled by one aquastat set to approximately 130 degrees Fahrenheit (°F) (54 degrees Celsius [°C]) whose thermowell is mounted in the bottom half of the storage tank. One boiler and at least one return water pump occasionally failed or were disabled intentionally by the facility staff.

The retrofit equipment consists of a gas-engine heat pump (GEHP) plant located in the firstfloor parking lot and a solar thermal system located on the roof. Both systems intercept and preheat the make-up water to the existing DHW system, and the existing system is otherwise left intact and not modified by the project team.

The gas into the existing boilers and new GEHP were measured by diaphragm gas meters with pulse output. Pump power for the new pumps was measured with three-phase power meters. Heat energy into and out of the existing storage tank and out of the GEHP was measured with British thermal unit (Btu) meters. Data was typically sampled at 1-second intervals and saved at 1-minute intervals.

The two boiler gas meters and the one Btu meter between the boilers and the existing storage tank were used to estimate the coefficient of performance (COP) of the pair of existing boilers at an hourly interval for time periods of consistent data. The GEHP gas meter and Btu meter were used to estimate the COP of the GEHP at hourly intervals for time periods of consistent data.

For each measurement period, gas usage was aggregated to daily intervals and scatter plotted versus daily National Oceanic and Atmospheric Administration (NOAA) weather station dry bulb temperature to search for linear correlation. Normalization for other factors such as occupancy was not conducted, and pump energy was not scatter plotted against any factors.

Correlation was not great for either period, but both gas versus dry bulb temperature trendline equation were nevertheless applied to California Climate Zone typical weather data. This yielded estimated annual energy usage for the baseline and retrofit periods as well as estimated annual savings.

Data Points

Data points are shown in Table C-1 below.

Data Sampling, Recording, and Collection Intervals

Data point information is also shown in Table C-2 below.

Data Point	Qty.	Units	Recording Interval	Resolution
Boiler Gas Usage	2	ft³	1 min.	1 pulse = 1 ft ³
GEHP Gas Usage	1	kBtu/hr	1 min.	1 Btu/hr
Boiler Pump Power	2	kW (via kVA)	1 min.	~0.01 kW
GEHP Pump Power	2	kW	1 min.	0.001 kW
GEHP Other Power	1	kW	1 min.	0.001 kW
Solar Thermal Pump Power	1	kW	1 min.	0.001 kW
Boiler Supply Water Temp.	1	°F	1 min.	0.018°F
Boiler Return Water Temp.	1	°F	1 min.	0.018°F
Hot Water Supply Temp.	2	°F	1 min.	0.018°F
Hot Water Return Temp.	1	°F	1 min.	0.018°F
Make-up Cold & Pre-heated Water Temp.	2	°F	1 min.	0.018°F
GEHP Outlet Temp.	1	°F	1 min.	0.01°F
GEHP Inlet Temp.	1	°F	1 min.	0.01°F
Outside Air Dry Bulb Temperature	1	°C	~ 1hr.	0.1°C
Boiler Water Flow Rate	1	gpm	1 min.	0.001 gpm
Hot Water Return Flow Rate	1	gpm	1 min.	0.001 gpm
Hot Water Supply Flow Rate	1	gpm	1 min.	0.001 gpm
Make-up Water Flow Rate	1	gpm (via (2) gpm)	1 min.	0.001 gpm
GEHP Water Flow Rate	1	gpm	1 min.	0.01 gpm
Boiler Heat Rate	1	Btu/min	1 min.	0.001 Btu/min
Hot Water Return Heat Rate (against Hot Supply Temp.)	1	Btu/min	1 min.	0.001 Btu/min
Make-up Water Heat Rate (against Hot Supply Temp.)	1	Btu/min (via (2) gpm & (2) °F)	1 min.	0.001 Btu/min
GEHP Heat Rate	1	kBtu/hr	1 min.	1 Btu/hr

 Table C-1: Data Points, Intervals, Resolution, and Accuracy

Source: NegaWatt Consulting

Instrumentation

M&V instrumentation is shown in Table C-2 below.

Make, Model, Name, URL	odel, Name, URL Specifications	
MultiTech Cellular Modem MTR- LAT1. <u>https://www.multitech.com/</u> <u>models/92507399LF</u> .	LTE Cat 3 Router with Fallback, w/o Accessories (AT&T). Operating Temp.: -40°F (-40°C) to 176°F (80°C)	Purchased new in 2018.
T-Mobile Unlimited data plan for 2 years. <u>http://www.egauge.net/eos/accessories/CR100MT</u> .	Network Speed: 3G.	Purchased new in 2018.
RS-485 to Ethernet converter. http://www.egauge.net/eos/ accessories/bf430.	Operating Temp.: -17°F (0°C) ~ 131°F (55°C).	Purchased new in 2018.
RS485-USB Converter. <u>http://www.</u> egauge.net/eos/accessories/usb485.	Operating Temp.: -34°F (-30°C) to 140°F (60°C).	Purchased new in 2018. Quantity: 2.
ControlByWeb X-420 Web-Enabled Data Acquisition. <u>https://www.</u> <u>controlbyweb.com/x420/</u> .	Digital Inputs Number of Inputs: 2 (configurable). Analog Inputs Number of Inputs: 4. Resolution: 16-bit, SAR. Temperature Sensors Maximum Number of Sensors: 16. Type: Dallas Semiconductor DS18B20. Temp. Range: -67°F to 257°F (-55°C to 125°C). Accuracy: ±32.9°F (0.5°C) (from -18°F [-10°C] to 185°F [85°C]).	Purchased new in 2018. Quantity: 2
ControlByWeb X-WR-1R12-1I-I WebRelay. <u>https://www.controlby</u> web.com/webrelay/partnumbers. <u>html</u>	Outputs Relays: 1. Current: 12A 240VAC, 30VDC. Inputs Digital: 1. Range: 4-26 VDC.	Purchased new in 2018.
Elster American Meter AC-800 with PulseMaster Pulse Output Module. <u>https://mcsmeters.com/collections/</u> <u>diaphragm-gas-meters/products/</u> <u>american-meter-ac800-diaphragm-</u> <u>meter</u> .	Capacity: 800 SCFH (22.7 m ³ /h) (0.60 specific gravity gas) at 1/2-inch w.c. differential. Pulse Rate: 1 pulse/1 ft ³ . Performance: Meets ANSI B109.2.	Purchased new in 2018. Quantity: 2.
Pulse output gas meter (make/model TBD)	TBD	Provided by GEHP manufacturer

Table C-2: M&V Instrumentation

Make, Model, Name, URL	Specifications	Notes
Onset Temperature (6') Sensor TMC6-HE. <u>https://www.onsetcomp.</u> <u>com/products/sensors/tmc6-he</u> .	Measurement range: -40°F (-40°C) to 212°F (100°C). Drift: <32°F (0.1°C) (<0.2°F [-17°C]) per year.	Purchased new in ~ 2017. Quantity: 2
	Response time in air: 3 min. typical to 90% in air moving 1 m/sec (2.2 mph).	
Sierra Instruments Ultrasonic Liquid Flow Meter with Thermal Energy/Btu Capability, InnovaSonic®207i. <u>http://www.sierrainstruments.com/</u>	Performance Specifications Pipe Size: 2 to 236 inches (50 to 6000 mm). Accuracy: ± 0.5% of reading from 0.16	Purchased new in 2018. Quantity: 5 4.
products/207iprod.html	to 40 ft/s (0.05 to 12 m/s). Repeatability: ± 0.15% of reading >0.16 ft/s (0.05 m/s). Resolution: 0.01 ft/s (0.00025 m/s). Response Time: 150 m/s measuring	
	cycle. Operating Specifications	
	Flow Velocity Range	
	Bi-directional flows: 0.16 to 40 ft/s (0.05 to 12 m/s).	
	Note: 0.08 ft/s (0.025 m/s) is the default low flow cut-off.	
	Temperature	
	Ambient electronics: -4°F (-20°C) to 140°F (60°C).	
	Clamp-on transducer: 14°F (-10°C) to 176°F (80°C).	
	Clamp-On RTD Accuracy: ±0.12% at 32°F (0°C).	
Omega Flow Meter		Provided by GEHP manufacturer
Temperature sensors		Provided by GEHP manufacturer
eGauge Core Energy Meter. <u>http://</u> www.egauge.net/eos/energy-	Operating Temp.: -34°F (30°C) to 158°F (70°C).	Purchased new in 2018. Quantity: 2.
meters/EG4115.	Power Draw: 12W max, 2W typical. Measurement Voltage: Up to 277 Vrms per line. 3 lines.	
	Measurement Current: 15 sensor ports, 6900A max/ea.	
	Accuracy: ANSI C12.2 – 0.5% Compliant.	

Make, Model, Name, URL	Specifications	Notes	
	Register Count (data storage points): 64.		
	Granularity (duration/avg): 1 hour/1 second, 1 year/1 minute, 10 years/15 minutes, Device Lifetime/1 Day.		
	Data Communication: Modbus RTU, Modbus TCP, BACnet/IP, XML.		
Magnelab SCT-0400 Split-core AC Current Sensor, <u>https://www.</u> egauge.net/docs/sct_0400.pdf	Output: 0.333V at rated AC current. Accuracy: ±1%. Range: 10% to 130% of rated current. Frequency: 50Hz – 400Hz.	Purchased new in Fall 2013. Multiple sizes from 10 to 50 amps.	
Extech 380976 1-phase/3-phase 1000 Amp True RMS Power Clamp- On Meter, <u>http://www.extech.com/</u> instruments/product.asp?catid=27& prodid=705	Function: Max Range/Resolution, Basic Accuracy. True Power (W): 600kW/10W, ±5%. Apparent Power(kVA): 600kVA/100VA, ±2%.	Calibrated on 10/11/2012. Used for spot checking only as needed.	
	Reactive Power (kVAR): 600kVAR/10VAR, ±5%.		
	Phase Angle (f): -60 to +60° / 0.1°, $\pm 6^{\circ}$.		
	AC Current (Trms): 1000A/10mA, ±2%. μA Current (AC+DC) (Trms): 1000μA/10nA, ±1%.		
	AC/DC Voltage (Trms): $600V/0.1mV$, $\pm 1\%$.		
	Temperature (Type K): -58°F (-50°C), to 1000°F (538°C) / 0.1°F (-17°C), ±1%.		

Instrumentation Layout

Figure C-1 below shows the baseline instrumentation installation guidance diagram. The hexagons labeled "F" are flow meters, those with "T" are temperature sensors, and those with "G" are gas meters.




Figure C-1: Baseline M&V Instrumentation Installation Guidance Diagram

An instrumentation installation guidance diagram was not created for the retrofit equipment. However, Figure C-2 is a schematic M&V instrumentation diagram showing both the baseline and retrofit equipment.




Figure C-2: Baseline & Retrofit M&V Instrumentation Diagram

Data Analysis Procedures

Data analysis procedures are summarized in the following list:

- 1. Remotely download data from all sensors regularly and troubleshoot irregularities.
- 2. For the existing boilers in the baseline period and the GEHP in the retrofit period, aggregate the data to daily intervals and compare heat output to gas usage to calculate equipment efficiency or COP:

a. Q_{out}/E_{in}

- 3. For the baseline and retrofit periods at the daily interval only, look for correlation between E_{in} and daily NOAA weather station dry bulb.
- 4. If correlation is high enough for E_{in} for both baseline and retrofit, calculate annual savings against each of the California climate zone weather files first aggregated to daily intervals. If only one correlation is high enough, then only calculate adjusted savings for the respective measurement period (i.e. baseline adjusted to retrofit conditions or vice versa).
- 5. Calculate cost savings using blended electricity and gas rates.
- 6. Identify and discuss system loss mechanisms, and opportunities for optimization and improvements.
- 7. Data analysis will be performed periodically on an interim basis upon request by the PI, and for final reporting at project end.

Baseline System

Existing Domestic Hot Water Plant Conditions

The overall system are shown in Figure C-3 and C-4. The left photo in Figure C-4 shows the hot water supply line, hot water return line and two inline pumps mounted in series, and the make-up cold water line. The right photo shows the gas piping into the boilers and the integral boiler pumps. Figure C-5 shows the nameplate for one of the two identical boilers.



Figure C-3: Existing Boilers and Storage Tank

Figure C-4: Existing Storage Tank Water Piping and Boiler Gas Piping



Source: NegaWatt Consulting

Figure C-5: Boiler Nameplate

	stems Company : Oakville, Ontario, Canada:
Automatic Circulating Tank Water Heater	Recovery Rate (100'F Rise) 764 GPH
For Either Indoor or Outdoor Installation, Indoor Installation Either Direct Vent or Using Indoor Combustion Air. For Installation on Combustible Flooring, CATEGORY 1 & III. is Product Complex With ANSI 221(10) & 2004 : CSA 4.3b 2004 : CSA # F1031.15273674	FOR YOUR SAFETY Do not store or use gasoline or other flammable vapors and liquids in the vicinity of this or any other appliance.
Manufactured Date: Nov 01, 2005	FOR INSTALLATION ON COMBUSTIBLE FLOORIN
Model Number PNCV0750NACK2PXN	Minimum Clearances From Combustible Surfaces
Serial Number C05 159319 National Board 159319	Clearance Indoor Outdoor From (Inches) (Inches)
This Boiler Equipped to Burn NATURAL Gas	Top 1 Unobstructed
Input 749,970 Btu/hr	Side 1 6
Minimum Input Rate 249,990 Btu/hr	Front Alcove Unobstructed Rear 1 6
Output 630,000 Btu/hr	Vertical (Category 1) Vent* 6 * n/a
Maximum W.P. Water 160 P.S.I.	Horizontal (Category 3) Vent per UL1738 venting system supplier's instructions
Maximum Water Temperature 210 Deg. F	Service Clearance 24" at front of boiler *1" (2.5cm) when b-vent is used.
Minimum Relief Valve Capacity 720,000 Btu/hr	Electrical Characteristics
Heating Surface 72 sq. ft.	120 V - 60Hz - SINGLE PHASE - Less than 12 Amperes
Maximum Permissible 13 Inches W.C. Gas Supply Pressure 13	READ YOUR MANUAL THOROUGHLY
Minimum Permissible Gas Supply 4 Inches W.C.	This boiler must be installed in accordance with local codes for gas burning appliances, if any. If not, follow ANSI 2223.1
Manifold Pressure 2.5 in / W.C.	or, in Canada, CAN/CGA-B149.1 OR .2 installation codes.

Source: NegaWatt Consulting

Our various measurements gave us insight into plant operation. The integral boiler pumps run constantly at a steady combined flow rate of approximately 90 gallons per minute (gpm); the boiler supply to return water temperature difference is typically less than 6°F (-14°C); and the tank supply temperature setpoint is easily met. This indicates that cycling the pumps with a call for heat would be more efficient and that one boiler is redundant (i.e., one boiler has sufficient capacity to satisfy the load).

The hot water supply temperature is approximately 130°F (54°C) and the return water temperature is typically about 6°F (-14°C) colder. The return water pumps run constantly at a steady combined flow rate of approximately 19 gpm. The average minutely hot water draws are typically less than 10 gpm and often less than 5 gpm. This indicates that the return water pump flow rate could be reduced without impacting hot water wait time at the fixtures, and that the return water loop heat loss is a substantial portion of the current load.

Natural Gas Utility Data

We reviewed the natural gas utility data, but it is of limited value since one gas meter serves the whole building which includes three DHW plants, a pool, and other gas-fired equipment and appliances. See Figure C-6 for an excerpt of the October 2018 gas utility bill.

Account Activity				
Date of Bill	10/09/2018		Previous Balance	\$4813.8
			Total Amount of Payments	\$4813.89
			Balance Forward	\$0.00
			+ Current Bill	\$4665.29
			Current Balance	\$4665.2
Gas Service - Account	Summary			
Invoice Number			Customer Charge 30 Days X 0.16438	\$4.9
Premise Number		_	Baseline 4299 Therms X 0.88972	\$3824.9
Meter No.			Subtotal	\$3829.8
Rate	GM-E			
Current Reading	70484 Ac	ual 10/05/2018		
Previous Reading	67024 Ac	ual 09/05/2018		
Measured CCF Usage	3460			
Multiplier	1.0320			
Therm Factor	1.2040			
Therms	4299			
Summary Charges				
			Baseline 4299 Therms X 0.88972	\$7.1
			Baseline 4299 Therms X 0.88972	\$404.1
			Nat Gas Utility Tax	\$424.12
			Subtotal	\$835.4

Figure C-6: October 2018 Gas Utility Bill

Source: SoCalGas; obtained from building owner

During this bill period, the building used 3,460 centum cubic feet (CCF) (or, 346,000 cubic feet) of natural gas. The "multiplier" of 1.032 is used to convert to therms while accounting for the elevation of the site, which is approximately 150 feet, and the heat value of gas delivered that month to the given Btu district, which is 11 (SoCalGas 2018). The "Therm Factor" accounts for elevated delivery gas pressure using Boyle's Law as compared to atmospheric pressure (14.73 pounds per square inch absolute [psia]) (SoCalGas 2010). So, 1.204 equals delivery pressure divided by 14.73, giving a delivery pressure of 17.73 psia or 3 pounds per square inch gauge [psig]) (SoCalGas 2010).

There is a gas regulator in the garage that reduces the gas pressure in the line serving the boilers. We have not measured the pressure at our gas meters on the roof, but we know from the boiler nameplate that the acceptable pressure range is 4 inches water column (w.c.)

(0.144 psig) to 13 w.c. (0.469 psig). This gives a "Therm Factor" range of 1.0098 to 1.0318. We will use the midpoint of 1.02.

For the "multiplier," we will use the average of the most recent 11 months from January to November 2018 which gives 1.033.

Our diaphragm gas meters are not temperature compensating because such meters were not available from our distributor during M&V installation. We mounted a temperature sensor on the outside of the gas header pipe on the roof to attempt the temperature compensation calculation ourselves. For the time being, we will not attempt to correct for temperature since that data seems higher than expected.

The pulse rate of our gas meter is 1 cubic foot per pulse. Therefore, to convert our gas measurements at the boilers:

Gas Usage in therms = x pulses
$$\cdot \left(1 \frac{ft^3}{pulse}\right) \cdot (1.02 \cdot 1.033) \frac{therms}{100 ft^3}$$

To convert this to Btu, we multiply by 100,000 (U.S. EIA 2018).

Estimated Baseline Annual Domestic Hot Water Gas Usage & Emissions

The cumulative minutely gas pulse data was resampled to daily intervals and the above equation was used to convert to therms. The date range was June 8, 2018 to December 1, 2019, anomalous data was removed, and some days of data were missing. There were 485 usable observations. In Figure C-7 below, this data was scatter plotted against average daily dry bulb temperature from the NOAA weather station at Los Angeles International Airport and a linear trendline is shown. The coefficient of determination (R²) is not as high as we prefer, but our baseline measurement period was long.




Figure C-7: Gas Usage versus Dry Bulb Temperature

Source: NegaWatt Consulting

Applying the trendline equation to daily outside air temperature data for California Climate Zone 6, this yields 10,837 therms per year per Table C-3. Associated greenhouse gas (GHG) emissions are shown using the California Energy Commission's (CEC's) emissions factor of 11.7pounds (lbs.) of carbon dioxide equivalent (CO₂e). Gas cost is shown using CEC's statewide average residential rate of \$1/therm.

Baseline	Baseline	Baseline Annual	Baseline Annual	Date Range
Annual DHW	Annual DHW	DHW Gas Cost	CO2e from	
Gas Usage	Gas Usage	[\$, Statewide	DHW Gas	
[therms]	[MMBtu]	Average]	Usage [lbs.]	
10,837	1,084	\$10,837	126,792	6/8/18-12/1/19

Table C-3: Estimated Baseline Annual Values

Source: NegaWatt Consulting

Additional Baseline M&V Results

We measured, plotted, and analyzed numerous additional data points, both at the raw minutely interval and aggregated to daily intervals. Before aggregating to daily intervals, we removed anomalous spikes and corrected small issues such as energy measurements that were consistently negative instead of positive cumulative values. We also ignored days where 60 minutes or more of measurements (congruous or not) were missing. Below are some of our daily interval timeline plots for the full baseline measurement period, along with some observations.

Figure C-8 below shows *net* boiler output (i.e., "energy-boiler") and boiler gas input (i.e., "Gas Total [Btu]"), both in units of Btu. Figure C-9 shows average boiler efficiency, which is net boiler output divided by boiler gas input. The net output data is from the Btu meter across the boiler supply and return pipes between the boilers and the storage tank, and the input data is from our gas pulse measurements. We say *net* because the boiler pumps run constantly at constant flow regardless of heating calls. When there are no heating calls, the loop takes some energy out of the tank.

It is not clear what caused the spike in boiler output in late August 2018 or whether it should be omitted. The drop boiler output in late October 2018 coincides with a drop in hot water draws, which we will see later. The gradual increase from September 2018 to early 2019 correlates with colder ambient temperatures which increases boiler load during water draws. The improved efficiency seems to indicate that the boilers are oversized.




Figure C-8: Daily Boiler Gas Usage and Boiler Net Heat Output to Tank




Figure C-9: Daily Average Boiler Efficiency

Source: NegaWatt Consulting

Figure C-10 shows cumulative daily water volume readings from the flow meters that are part of the Btu meters. Here is the meaning of each data series:

- 1. "flow-hot-return" is measured at the return line into the storage tank.
- 2. "flow-hot-supply" is measured at the supply line exiting the tank to serve the building.

- 3. "flow-boiler" is not shown in order to zoom into the other data series.
- 4. "flow-cold" is the difference between "flow-hot-supply" and "flow-hot-return" because the flow at the cold water line was too low to get good readings. This data series was subsequently ignored in favor of "flow-cold-positive."
- 5. "flow-cold-positive" is also the difference "flow-hot-supply" and "flow-hot-return," but negative minutely values (due to sensor inaccuracy) were excluded before aggregating to daily intervals. The modified minutely data was also used for the cold water Btu calculations. The accuracy of the cold water data is worse than the other data series due to the combined inaccuracy of two Btu meters.




Figure C-10: Daily Water Volumes

Figure C-11 shows the thermal energy in Btu from each Btu meters, with the caveat that the "cold" data is calculated. Note that the calculation is automatically performed every second by our eGauge data logger before it is saved as minutely data in the logger. The data series "energy-cold-and-return" is the sum of "energy-cold" and "energy-hot-return." It should always be slightly lower than "energy-boiler," but that is sometimes not the case which makes that data suspect. An unrelated observation is that the dip in "energy-cold" in late October 2018 lines up with the boiler input and output dips in Figure C-11.




Figure C-11: Daily Thermal Energy

Figure C-12 shows the boiler gas input in therms for each individual boiler and for both combined. It shows that boiler "1" consistently handles more of the load, and that boiler "2" stopped firing in late October 2018 for some reason and did not come back online for the rest of the baseline period.




Figure C-12: Daily Boiler Gas Usage

Figure C-13 shows the temperature measurements. Note that the cold water temperature is around 80°F in the summer.




Figure C-13: Daily Average Temperatures

Source: NegaWatt Consulting

Figure C-14 shows the average temperature deltas associated with each Btu measurement. "Boiler dT" is much lower than optimal. The constant pump operation is a contributing factor, and the boilers also seem oversized for the load. As expected, "Hot Supply to Cold dT" show that the load of hot water draws generally increases with lower ambient and cold water temperatures, assuming temperature setpoint is fixed.




Figure C-14: Daily Average Temperature Deltas

Retrofit System

Retrofit System Conditions

The retrofit system consists of the GEHP and solar thermal systems which both pre-heat the cold-water makeup water going to the existing DHW system. The project team did not otherwise modify the existing DHW system whereas the site staff did make seasonal control changes and deal with some pump and perhaps boiler failures. As far as the retrofit equipment, the GEHP system had much lower equipment COP system than expected, but functioned properly otherwise.

Estimated Retrofit Annual Domestic Hot Water Gas Usage & Emissions

The below three figures (Figures C-15, C-16 and C-17) show the daily gas usage versus daily ambient dry bulb temperature during the retrofit period after anomalous data was removed. The date range was from June 1, 2020 to April 11, 2021 and there were 233 usable observations. Figure C-15 is for the GEHP, Figure C-16 is for the existing boilers during the same dates, and the Figure C-17 is the combined gas usage. Trendline information is shown above each plot. Pump power was not evaluated. Gas usage increased compared to the baseline period. Perhaps the domestic hot water load in the building was higher during this time period versus the baseline period due to more people being at home during the COVID19 pandemic. The pandemic began in early 2020, which was after the end of our baseline M&V period and before our retrofit M&V period.








Figure C-16: Boiler Gas Usage versus Dry Bulb Temperature (Retrofit Period)



Source: NegaWatt Consulting





Applying the trendline equation to daily outside air temperature data for California Climate Zone 6, this yields 20,926 therms per year per Table C-4. Associated GHG emissions are shown using CEC's emissions factor of 11.7 pounds of CO₂e per therm. Gas cost is shown using CEC's statewide average residential rate of \$1/therm.

Retrofit	Retrofit	Retrofit Annual	Retrofit	Date Range
Annual DHW	Annual DHW	DHW Gas Cost	Annual CO2e	
Gas Usage	Gas Usage	[\$, Statewide	from DHW Gas	
[therms]	[MMBtu]	Average]	Usage [lbs.]	
20,926	2,093	\$20,926	244,837	6/1/20-4/11/21

Table C-4: Estimated Retrofit Annual Values

Includes GEHP and Boiler Gas Usage. Additional electrical usage for new pumps not addressed. Source: NegaWatt Consulting

Additional Retrofit M&V Results

The figures below (Figures C-18 through C-26) show the primary data collected during the retrofit period at the new GEHP plant and the existing boiler plant. Note that although we have been collecting most M&V data to date, we lost Modbus communication with the GEHP equipment and related sensors in mid-April 2021. That is why the date range in the above table is shorter than the date range of the below timeline plots. In any case, an important finding during the retrofit period was that the GEHP COP was lower than expected (Figure C-19). The manufacturer and project team have attempted multiple fixes and will continue to attempt additional fixes.

Another important finding is that the retrofit energy usage was much higher than the baseline energy usage. However, it is clear from the temperature data that the GEHP and solar thermal system preheated the supply water as designed (see "tank_supply_F" and "citywater_F" in Figure C-20). We expect that at least some of the gas usage increase was due to COVID-19 impacts. Surprisingly, gas bills from the project site indicate that overall yearly site gas usage was steady from 2018 through 2020.

The solar thermal system heat output is compared to the GEHP heat output in Figure C-18. There are only a few data points for the solar thermal system because anomalous temperature data was removed. The average ratio of solar thermal system heat output to GEHP heat output for days where there was useable *non-zero* data for each was 66 percent (i.e., the solar thermal system provided 66 percent as much heat output as the GEHP system on average when both systems were operational and M&V data was available). There were 47 such observations. Figure C-18 also indicates that the solar thermal system can output significantly more energy when the GEHP system is not running. This is because it works better when the inlet water is colder.




Figure C-18: Daily GEHP Gas Usage, GEHP Heat Output, and Solar Thermal Heat Output (Retrofit Period)




Figure C-19: Daily Average GEHP COP (Retrofit Period)





Figure C-20: Daily Average Temperatures at the GEHP Plant (Retrofit Period)

Figure C-21: Daily Water Flow through the GEHP and Solar Thermal (Retrofit Period)



Source: NegaWatt Consulting




Figure C-22: Daily Boiler Gas Usage and Boiler Net Heat Output to Tank (Retrofit Period)

Source: NegaWatt Consulting




Figure C-23: Daily Average Boiler Efficiency (Retrofit Period)






Figure C-24: Daily Boiler Gas Usage (Retrofit Period)





Source: NegaWatt Consulting

Figure C-26: Daily Average Temperature Deltas at Boiler Plant (Retrofit Period)



Savings Estimate

Gas usage was higher during the retrofit period as compared to the baseline period, so savings are not reported.